UNCLASSIFIED

AD 444337

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.



AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES ON THE HASP 1.0-INCH DIAMETER DART


RELEASED TO DDC

- BY THE NAVAL ORDNANCE LABORATORY
- Without restrictions
- For Release to Military and Government Agencies Only.
- Approval by NOL required for release to contractors.
- ☐ Approval by BuWeps required for all subsequent release.

30 APRIL 1964

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 63-210



Aerodynamics Research Report 208

AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES ON THE HASP 1.0-INCH DIAMETER DART

Prepared by: H. J. Gauzza

ABSTRACT: The High Altitude Sounding Projectile, HASP, has been the subject of a design study aimed at enhancing the round's performance. The techniques used and the results obtained from this study are described. It was found that by decreasing the dart's diameter to 1.0-inch and using the standard MK 32 MOD 0 HASP motor, altitudes of the order of 300,000 feet could be achieved. However, this improved performance is not attainable simply by scaling down the present 1.375-inch diameter dart. Indeed, the following significant changes are required; an increased static margin, a decreased fin-cant angle, use of a fin material whose strength does not materially deteriorate at elevated temperatures, and thermal protection for the motor casing.

PUBLISHED SEPTEMBER 1964

U. S. NAVAL ORDNANCE LABORATORY White Oak, Silver Spring, Maryland

30 April 1964

AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES ON THE HASP 1.0-INCH DIAMETER DART

These analyses were performed at the request of the HASP Project Manager, Mr. M. J. Parker, under Task Numbers FAME 04001/212 4/F003 02 003 and FAME 04002/212 4/F003 02 003.

The purpose of these studies was two-fold; to determine the feasibility of attaining a 300,000 foot altitude with a smaller diameter dart using the standard, MK 32 MOD 0 motor, and to make recommendations to the HASP Design and Development Committee, of which the author is a member, regarding the design and development of such a system.

R. E. ODENING Captain, USN Commander

K. R. ENKENHUS
By direction

CONTENTS

	្នា	Page
Symbols Traject Static Static Dynamic Aerodyn Conclus	ions	1 2 5 7 8 13 17 19
	ILLUSTRATIONS	-
Figure	Title	
1 2 3	Dart-Booster Assembly Drawing Maximum Altitudes for the 1.0-Inch Dart Trajectories for the 1.0-Inch, 5.0 Lb Dart for the MK 32 MOD 0 Motor	he
4	Static Stability Margin of 1.0-Inch Dart-Booster Combination	
5	Dynamic Stability Characteristics	
6	Pitch and Roll Characteristics	
7	Motor Wall Temperature and Stress as a Function Time	of
8	Aluminum 2024-T4 Fin Temperatures and Strength a Function of Time	s a
9	Stainless Steel Fin Temperatures and Strength as Function of Time	a
10	Nose Cone Temperature as a Function of Time	
	TABLES	
Table	Title	
1	Tabulated Trajectory Data	
2	Tabulated Aerodynamic Heating Data	

INTRODUCTION

The HASP projectile consists of a dart and rocket motor. Its purpose is to obtain meteorological data on a routine basis from altitudes up to 250,000 feet (ref. (1)). Designed for use aboard ship, HASP does not require special launchers or tracking equipment but can utilize the ship's 5-inch guns and gun director radar.

The object of the design study described in this report was to determine means by which the HASP system, using the present ...otor, could be modified to attain an altitude of 300,000 feet. Preliminary trajectory calculations based on realistic weight and drag reductions of the system indicated that the design objective appeared feasible if other anticipated problems associated with aerodynamic stability and heating could be resolved.

Concurrently with the design study there was a prototype dart development and field test. The 1.0-inch diameter. 5-pound prototype for reaching 300,000 feet was built similar to the standard 1.375-inch diameter dart. The resultant configuration is shown in Figure 1. It was necessary to retain the fin-span and tip-chord dimensions of the 1.375-inch dart so that the round would be compatible with the launcher. The root-chord was scaled down. This resulted in a fin with a 60° leading-edge sweep, which was then set at an incidence angle of 30 minutes. The fin material consisted of 0.060-inch thick aluminum plate. Nose cone dimensions were scaled down consistent with the packaging requirements of the fuze. The scaled-down body length was increased somewhat to get additional weight forward to insure the static stability of the dart-booster combination.

Initial firings of the configuration described above have been unsuccessful. The primary difficulty has been the failure to track the dart and it is strongly suspected that the dart is experiencing erratic flight behavior.

This report analyzes the prototype to determine possible causes of malfunction. As a result of the analysis, a number of recommendations are made.

SYMBOLS

A	reference area
AL	quadrant elevation
A(W)	wall surface area being heated
b	fin span
c _d	drag coefficient, F _d /qA
$\mathbf{c}^{\mathbf{r}}$	lift coefficient, F ₂ /qA
$^{ extsf{C}}_{ extsf{L}_{oldsymbol{lpha}}}$	lift coefficient slope, $dC_L/d\alpha$
C _m	pitching moment coefficient, m/qA
C _m	pitching moment coefficient slope, $dC_m/d\alpha$
$C_{\mathbf{m}_{\mathbf{q}}}^{+} C_{\mathbf{m}_{\mathbf{\alpha}}}$	pitch damping coefficient, $dC_m/d(q\ell/2V)+dC_m/d(\dot{\alpha}\ell/2V)$
C pg	Magnus moment coefficient, $d^2C_m/d(p\ell/2V)d\beta$
C _N	normal force coefficient, F _n /qA
$^{\mathrm{C}}_{\mathrm{N}_{\boldsymbol{lpha}}}$	normal force coefficient slope, $dC_{N}/d\alpha$
$\mathtt{CP}_{\mathbf{F}}$	Magnus force center of pressure
C(W)	specific heat of wall material
D	outer diameter
D(B)	diameter of bird(dart)
D(M)	diameter of motor
đ	body diameter
E(W)	emissivity of wall surface
F _d	drag
F ₁ .	lift force

F _n	normal force
F _t	thrust
g.	acceleration of gravity
go	acceleration of gravity at sea level
Н	heat transfer coefficient
ISP	specific impulse
ISP(0)	specific impulse at zero ambient pressure
I _x	axial moment of inertia
I _Y	transverse moment of inertia
K(T)	constant in equation for specific impulse
k	thermal conductivity of ambient air
k _a	dimensionless axial radius of gyration, $(I_x/M/^2)^{\frac{1}{2}}$
k _t	dimensionless transverse radius of gyration,
·	$(I_{\gamma}/M\ell^2)^{\frac{1}{2}}$
L	wall thickness
e.	reference length
$\epsilon_{ m E}$	effective body length
M	mass
M	free-stream Mach number
M(B)	mass of bird
M(O)	initial mass of rocket(booster plus bird)
M (P)	initial mass of propellant
MR	mass rate of flow of propellant combustion products
m	pitching moment
P	ambient pressure

p	roll frequency
$^{ m p}_{ m c}$	critical roll frequency
Q	heat flux
QE	quadrant elevation
q	dynamic pressure
R	density of wall material
RN	Reynolds number, $\rho VX/\mu$
r	body radius
s	Stefan-Boltzman constant, 0.475x10 ⁻¹²
T	free-stream temperature, °R
T(0)	initial temperature
T(R)	adiabatic wall temperature
T(W)	wall temperature at surface, °R
t	time
ta	time of apogee
t _b	time of burnout
v	velocity
V(0)	initial velocity
V (W)	volume of wall material being heated
W	weight
₩	flow rate
W(B)	weight of bird
x	distance aft of fin leading edge or nose cone tip
x _b	center of gravity distance from base
x	range

x	horizontal velocity
¥	horizontal acceleration
z .	altitude
z(o)	initial altitude
ż .	vertical velocity
ž	vertical acceleration
α	pitch incidence relative to axes fixed in body
β	sideslip relative to axes fixed in body
δ	fin cant angle
•	angle of trajectory with horizontal
μ	viscosity of ambient air
ρ	density of air

TRAJECTORIES

Preliminary performance calculations using 1.0-inch darts with weights varying from 4 to 6 pounds have indicated the feasibility of attaining altitudes in the vicinity of 300,000 feet with the standard MK 32 MOD 0 motor. Maximum altitudes obtainable for quadrant elevations of 75 and 80 degrees, as functions of the various dart weights, are indicated in Figure 2. These range from approximately 290,000 feet to 310,000 feet.

Detailed trajectories were computed in support of the range firings. These provided data for the range safety officer as well as for the radar tracking personnel who have found it difficult to track an object so small and moving as fast as the 1.0-inch dart. The method used for computing the HASP trajectories is described as follows. The dart and motor travel together until propellant burnout. At burnout, the dart separates from the motor and continues upward on its own momentum, reaching some maximum altitude. The assumptions are as follows: (1) the forces acting on the dart-booster combination (considered to be a particle) are drag, thrust and gravity; (2) the forces acting on the dart alone are drag and gravity; and, (3) the earth is assumed to be stationary

and flat. The equations describing the motion are as follows:

motor and dart
$$\begin{cases} W\ddot{x}/g = \cos \theta (F_t - F_d) \\ W\ddot{z}/g = \sin \theta (F_t - F_d) - W \end{cases}$$
 (1)

dart alone
$$\begin{cases} W\ddot{x}/g = -F_{d} \cos \theta & (3) \\ W\ddot{z}/g = -F_{d} \sin \theta - W & (4) \end{cases}$$

where

$$W = g[M(0) - (MR)t]$$

$$W(B) = gM(B)$$

$$\cos \theta = \dot{x}/\sqrt{\dot{x}^2 + \dot{z}^2}$$

$$\sin \theta = \dot{z}/\sqrt{\dot{x}^2 + \dot{z}^2}$$

$$F_t = \dot{W} ISP/(g/g_0)$$

$$F_d = C_d \rho D^2 (\dot{x}^2 + \dot{z}^2)/2$$

$$ISP = ISP(0) - K(T)P$$

The ARDC standard atmosphere was specified and the drag coefficient was varied as follows:

$$C_d = 0.430$$
, motor and dart

$$C_{d} = \begin{cases} 0.2749 \text{ for } M < 1.0 \\ 0.4522 \text{ for } 1.0 < M < 1.5 \\ 0.1942 + 0.5806/M^{2} \text{ for } M > 1.5 \end{cases}$$
 dart alone

The boundary conditions are as follows: when t=0, x=0, \dot{x} =0, \dot{z} =0, \dot{z} =0, 0=AL and M=M(0); when t=t_b, M=M(0)-M(P); when t<t_b, M=M(B); when t=t_a, \dot{z} =0, and z=z_{max}.

The preceding equations have been programmed for and used on the IBM 7090. The results are presented in the form of plotted (Figure 3) as well as tabulated data (Table 1) and appear at the end of this report. Initial conditions are listed at the head of each run. Trajectories were run at quadrant elevations of 75, 80 and 85 degrees for both the lower and upper specific impulses recorded during static tests of a sampling of the production motors (ref. (2)). This established a corridor within which the dart is expected to travel. Data were printed out at 0.1 second intervals during burning, and at 1.0 second intervals thereafter to impact. Burning lasts for 1.9 and 1.86 seconds for the lower and upper specific impulses, respectively.

STATIC STABILITY

While the dart lengths were expected to vary from approximately 30 to 35 calibers from the 4.0 to the 6.0 pound darts, respectively, their centers of gravity would all be located at approximately 50 percent of their lengths. This center of gravity location is approximately the same for the standard 1.375-inch dart which, according to reference (3), possesses a good margin of static stability over the Mach number range of interest. It was concluded, therefore, that the 1.0-inch dart which will maintain the same fin span as the 1.375-inch dart and approximately the same scaled fin area will also possess adequate static stability for all the weights considered.

The problem arose when the dart-booster combinations were considered. Calculations indicated that the 5 and 6 pound darts in combination with the booster will possess only marginal stability in the Mach number region between 3.5 and 4.0. The 4.0 and 4.8 pound darts in combination with the booster will go unstable at approximately Mach 2.5 and 3.1, respectively, (Figure 4). The center of gravity locations for the various dart-booster combinations were computed at launch and burnout, and a straight line variation assumed between the two end points. Center of pressure calculations for the 1.0-inch dart-booster combinations were performed using normal force slopes and center of pressure data for the 1.375-inch dart and dart-booster combination (ref. (3)). This involved subtracting the static stability contribution of the 1.375-inch dart and replacing it with that of the 1.0-inch dart.

Since it was apparent that the dart-booster combinations mentioned above would benefit by an increase in static stability, it was suggested that the following remedies be considered: (1) the addition or adjustment of weight to the forward end of the dart-booster combinations, thereby improving the center of gravity location; (2) reducing the fin area of the dart; and, (3) increasing the fin area of the booster. It was cautioned that in implementing any one or a combination of the above procedures, care must be exercised not to adversely affect other parts of the system.

The HASP Committee decided that the 5 lb. dart would be acceptable for field tests despite the fact that its static stability in combination with the booster was somewhat marginal.

DYNAMIC STABILITY

Dynamic characteristics, including the gyroscopic and dynamic stability factors as well as pitch and roll frequencies, were determined for the dart prototype, which had the 30 minute fin incidence angle of the standard 1.375-inch dart. This was based on the theories of Murphy, Nicolaides, Charters and Mantle (refs. (4), (5), (6) and (7), respectively).

It was discovered that the dart was dynamically unstable, but could be made dynamically stable by simply reducing the fin incidence angle. The dynamic stability criteria for spinning symmetric missiles (ref. (8)) were applied to the prototype dart in the following manner:

First, the damping derivative in pitch is approximated from slender body theory:

$$C_{m_a} + C_{m_a} = -2C_{L_a} (x_b/d)^2 = -4350$$
 (5)

where

Next, the Magnus moment coefficient can be estimated from the following equation:

$$C_{\text{mp}} = 8 \left[\frac{\ell_{\text{E}} (^{\text{CP}}_{\text{F}} - x_{\text{b}})}{d^2} \right] = -1755 \tag{3}$$

where

 ${\rm CP_F}=\ell_{\rm E}$ -(9/14) $\ell_{\rm E}$ (ref. (9) suggests that the center of pressure of the Magnus force, ${\rm CP_F}$, for turbulent boundary layer is 9/14 of the effective body length, $\ell_{\rm E}$, from the nose)

 $L_{\rm E}$ = 33.18 in. (according to ref. (9) this can be obtained by replacing the nose section with an effective cylinder which has the same boundary layer at its base that the nose has at its base)

The roll rate is determined from the following equation:

$$p = \frac{3\delta V}{2} \left[\frac{(\frac{b}{2})^3 - r^3}{(\frac{b}{2})^3 - r^3} \right] \frac{1}{2\pi}$$
 (7)

At burnout velocity,

 $\delta = 0.00873$ radians

V = 5750 ft/sec

b/2 = 0.1407 ft

r = 0.0416 ft

These values yield a maximum spin rate of

$$p = 80 \text{ cps}$$

Murphy (ref. (4)) suggests that the reciprocal of the gyroscopic stability factor and the dynamic stability factor form a boundary for the region of dynamic stability. This boundary (Figure 5) is described by the equation:

$$4\hat{m}/\hat{p}^2 = S_d(2 - S_d)$$
 (8)

The gyroscopic stability factor is defined as:

$$4\hat{\mathbf{m}}/\hat{\mathbf{p}}^2\tag{9}$$

where

$$\hat{\mathbf{m}} = \frac{\rho \mathbf{A}^{p}}{2\mathbf{M}} \frac{\mathbf{M}^{2}}{\mathbf{I}_{\mathbf{Y}}} \mathbf{C}_{\mathbf{m}_{\alpha}} + \frac{\rho \mathbf{A}^{3}}{4\mathbf{I}_{\mathbf{Y}}} \mathbf{C}_{\mathbf{m}_{\mathbf{Q}}} \mathbf{C}_{\mathbf{N}_{\alpha}}$$

and

$$\hat{p} = \frac{I_x}{I_y} \left(\frac{p!}{v} \right)$$

The dynamic stability factor is defined as:

$$S_{d} = \frac{2^{\binom{C_{N_{\alpha}} - C_{d} + k_{a} - {}^{3}C_{m_{p\beta}}}}{C_{N_{\alpha}} - 2C_{d} - k_{t} - {}^{2}C_{m_{q}} + C_{m_{\alpha}}}$$
(10)

At the time of booster separation, the flight conditions are:

V = 5750 ft/sec

z = 4650 ft

 $0 = 2.07 \times 10^{-3} \text{slug/ft}^3$

p = 503 rad/sec

The geometric and aerodynamic parameters of the dart are:

$$I_x = 2.36 \times 10^{-4} \text{slug -ft}^2$$

$$I_{y} = 0.1181 \text{ slug -ft}^{2}$$

t = 0.0833ft (ref. length taken as diameter)

 $A = 0.00545 ft^2$

M = 0.155 slugs

$$C_{m} = -32/rad$$

$$C_{N_{\alpha}} = 6.42/\text{rad}$$
 $C_{m_{q}} + C_{m_{\dot{\alpha}}} = -4350$
 $C_{m_{pg}} = -1755$
 pg
 $C_{d} = 0.25$
 $k_{a}^{2} = I_{x}/Mt^{2} = 0.219$
 $k_{+}^{2} = I_{y}/Mt^{2} = 110$

Applying the above data, the following is obtained.

$$4\hat{m}/\hat{p}^2 = -16,550$$

and,

$$S_d = -353$$

The requirement for dynamic stability is:

$$4\hat{m}/\hat{p}^2 - S_d (2-S_d) < 0$$
 (11)

For this configuration:

$$-16,550 + 125,200 > 0$$

The requirement for dynamic stability is not satisfied by the present configuration.

Further, a calculation of the critical roll rate at separation

$$p_{c} = \frac{1}{\pi I_{x}} \sqrt{\frac{qAtC_{m}I_{Y}}{S_{d}(2-S_{d})}} = 29.5 \text{ cps}$$
 (12)

reveals that this value will be exceeded by the roll rate generated with a 30 minute fin cant (~80 cps). Consequently,

means by which the dynamic stability can be improved are next considered.

It is noted that the gyroscopic stability factor varies inversely with roll rate and directly with dynamic pressure, whereas the dynamic stability factor is a function of the vehicle's external configuration, the mass moments of inertia and the stability margin. Since any changes in the moments of inertia and external geometry would require major design changes, the easiest way of improving the dynamic stability is to decrease the spin rate by decreasing the fin incidence angle. Before the spin rate can be arbitrarily decreased, the steady state pitch frequency must be calculated to determine how much the roll frequency may be reduced without getting into resonance problems. The pitch frequency (Figure 6) was calculated at various points along the trajectory according to the following equation:

$$f = \frac{1}{2\pi} \sqrt{\frac{\rho V^2 A \ell C_m}{2I_Y}}$$
 (13)

Also included in this plot as a function of time are the roll rates for the 30 minute fin cant and the critical roll rates for the configuration calculated from equations (7) and (12), respectively. It is seen that the roll rates for the 30 minute fin cant exceed the critical roll rates of the configuration. It is further evident that a sizable reduction in roll rate, which will fall below the critical roll rate and yet remain far enough above the pitching rate to avoid resonance problems, can be accomplished.

It was decided to compute a cant angle for the present configuration that would generate a roll rate approximately 50 percent higher than the natural pitching frequency at burnout, which is considered the most critical region. This should avoid resonance problems and still stay well below the critical spin rate. This angle was determined to be 6 minutes.

It should be noted that the preceding analysis is influenced to a large degree by the accuracy of the theoretical estimates of the pitch damping and Magnus moment coefficients. However, the approach is considered conservative and appropriate to determining means by which the dynamic stability of

a particular configuration can be improved.

The dynamic stability parameter, S_d, indicated in Figure 5 is probably quite conservative due to the value assumed for the Magnus moment coefficient. Consequently, the critical roll rate, p_c, indicated in Figure 6 is also conservative. Therefore, the altitude at which the configuration with the 6 minute fin cant exceeds the critical roll rate is in reality probably a good deal higher than that indicated. Therefore, the dart should fly well if the following items which contribute to the perturbations of the vehicle are not excessive: (1) booster thrust misalignments; (2) aerodynamic misalignments; and, (3) non-alignment of the booster dart.

AERODYNAMIC HEATING

Other areas in which failures would cause erratic flight and consequent difficulty in tracking the dart include aerodynamic heating of the motor casing, fins and nose cone.

The MK 32 MOD 0 motor, boosting the lighter 1.0-inch dart, attains higher velocities at lower altitudes with the consequence being higher heating rates than those for which it was designed. To make it as light as possible, the motor casing was designed to insure just enough strength, consequently, it was questionable if the rather critical margin of safety would be exceeded in the presence of the increased heating rates.

In order to determine whether the strength of the 3.0-inch diameter, 0.060-inch thick wall motor casing was exceeded, it was first necessary to determine the effect of the aerodynamic heating on the strength of the 2014-T6AL material used. The motor develops a chamber pressure of 1550 psia. The aerodynamic heating at two selected points on the rocket motor casing up to the time of separation was determined using the method of reference (10). The maximum motor stress was then calculated to see if this value exceeded the tensile yield strength of the motor casing at any time during the burning phase of the propellant. Figure 7 summarizes the results of these calculations. Aerodynamic heating at points 39.5 and 94.5 inches from the dart nose, as well as the tensile yield strength of the rocket motor casing are presented as functions of time. The calculations indicate that failure in the

immediate area of burnout (at approximately 1.9 seconds of burning) is possible. Further, it is conjectured that the failures would be random, i.e., some motor cases will remain intact while others will burst.

It has been recommended, in order to insure consistent performance, that an ablative coating be applied to the surface of the motor casing to minimize the effect of aerodynamic heating.

Other components of the system examined in the light of aerodynamic heating were the fins and nose cone. It was suspected that the aerodynamic heating experienced by the aluminum fins might have been severe enough to cause structural failure and subsequent erratic flight. Also of interest, especially for fuzing considerations, is the aerodynamic heating experienced by the nose cone. The pyro-mechanical fuze uses the aerodynamic heating of the nose cone to soften and melt a ring made of an eutectic alloy which allows the firing pin to be released starting the pyro delay train. This burns approximately 100 seconds and initiates the expelling charge in the fuze. Early release of the firing pin could result in premature initiation of the expelling charge and payload ejection.

The fin under consideration is an aluminum flat plate with a 60-degree swept, rounded leading edge and a thickness of 0.060 inches. An area near the center of the fin was chosen to be representative of the heating experienced by the fin. This area was 1.25 inches aft of the fin leading edge.

The nose cone is a tangent ogive made of carbon steel with a wall thickness of 0.204 inches. Two points on the nose cone, 6.032 and 11.422 inches aft of the nose tip, considered critical for the fuze were investigated.

The method used to estimate the fin and nose cone temperatures of the dart is the generally-accepted one of treating the heat flow into the wall as a one-dimensional problem; i.e., assuming that the heat flux parallel to the surface is small compared to that perpendicular to the surface. This technique, as indicated in reference (11), has been successful in predicting (somewhat conservatively) the actual heating rates experienced by other sounding rockets during their flight tests.

The equation for wall temperature rise is:

$$\frac{dT(W)}{dt} = \left(\frac{A(W)}{RV(W)}\right) \frac{1}{C(W)} \left[H(T(R)-T(W))-E(W)ST(W)^4\right]$$
(14)

where H is assumed to be the local heat transfer coefficient correspondent to the location of interest.

The recovery factor is assumed to be equal to 0.89 or 0.84 depending on whether the flow is turbulent or laminar. Therefore, if the ratio of specific heats of air is 1.4, the expressions for the adiabatic wall temperatures, depending upon boundary layer type are:

$$T(R) = T(1+0.167M^2)$$
 (laminar) (15)
 $T(R) = T(1+0.178M^2)$ (turbulent)

The only remaining unknown in equation (14) is the heat transfer coefficient, H. Now, the value of the heat transfer coefficient depends very critically on whether the flow is laminar or turbulent and, therefore, an estimation of both values is in order. The following expressions for a flat plate, derived from expressions for Nusselt numbers which assumed the Prandtl number for air to be constant and equal to 0.7, have been found to give good results.

H = 0.295
$$\frac{k}{X}$$
 RN ^{0.5} (laminar) (16)

$$H = 0.0263 \frac{k}{X} RN^{0.8} \text{(turbulent)}$$
 (17)

However, experimental data obtained on yawed circular cylinders and swept leading edges have indicated that the heat transfer is reduced along the stagnation line by approximately the cosine of the yaw or sweep angle. Reference (12) speculates that this effect is probably present for some distance aft of the fin leading edge and indicates that the transitional region is not known with any degree of certainty. Therefore, in the present calculations the assumption has been made that the effect of sweep is present at the station in question. This assumption compensates for

the ultra-conservatism of equation (14). The expressions for the heat transfer to a flat plate have been reduced by the cosine of the sweep angle ($\cos 60^{\circ} = 0.5$) as follows:

$$H = 0.148 \frac{k}{X} RN^{0.5} (laminar)$$
 (18)

$$H = 0.0132 \text{ k RN}^{0.8} \text{(turbulent)}$$
 (19)

Equations (18) and (19) were used to determine the heat transfer coefficients for the fins. Equations (16) and (17), according to reference (12), may be modified by multiplying the constants by $\sqrt{3}$ and 1.15, respectively, to allow for the three dimensional expansion over the nose cone. This yields the following equations:

$$H = 0.512 \frac{k}{X} RN^{0.5} (laminar)$$
 (20)

$$H = 0.0302 \frac{k}{X} RN^{0.8} \text{(turbulent)}$$
 (21)

Equations (20) and (21) were used to determine the heat transfer coefficients for the nose cone.

The free-stream Reynolds number of transition of the boundary layer from laminar to turbulent flow was assumed to be one million. Equations (18) and (20) were used when the Reynolds number fell below this value. Equations (19) and (21) were used when the converse was true.

The one-dimensional heat transfer analysis as outlined in the preceding paragraphs was carried out on the IBM 7090 computer with the following printout: velocity, altitude, Mach number, Reynolds number, adiabatic wall temperature, heat flux and wall temperature as functions of time. The data so computed are presented in Table 2. A key identifying the various cases precedes the tabulated data and the characteristics of the material under study appear at the head of each case. The input data may be identified by referring to the list of symbols included in this report.

Figure 8 indicates the heating and strength of the present aluminum fin as a function of time. It is noted that the tensile yield strength of the material goes to zero at approx-

imately 2.5 seconds of flight time while the aerodynamic heating is still on the rise. This condition is, obviously, to be avoided. If existing fins are to be used, they should be fitted with a steel cuff on the leading edge and the walls given an ablative coating. A better approach would be to redesign the fin.

An acceptable fin, one that will retain structural integrity, may be made of stainless steel. Heat calculations using stainless steel and the present fin thickness of 0.060 inches were run and the tensile yield strength evaluated. Again, as shown in Figure 9, the strength of the fin appears inadequate. This was remedied, however, by simply increasing the fin thickness to 0.100 inches which then yielded results, Figure 9, that appear to meet the present requirements. It has been recommended that future fins be made according to the present planform but be made of 0.100 inches thick stainless steel and include a wedge leading edge.

Figure 10 shows the temperature history of the nose cone at two locations. This information was used in the design of the pyro-mechanical fuze.

CONCLUSIONS

It is concluded from the results of this study that aerodynamic instabilities or structural failure due to aerodynamic heating could have occurred in the first firings of the HASP 300,000 foot round.

Static stability considerations indicated the desirability of improving the static margin of the dart-booster combination. This could be accomplished most simply by adding weight to the forward end of the combination and, thereby, improving the center of gravity location. It is suggested that this could be done by replacing the present 5 pound dart with a 6 pound version. The trajectory studies have indicated that a 6 pound dart in conjunction with the MK 32 MOD 0 motor will still reach an altitude of 300,000 feet with a quadrant elevation of 80 degrees.

The dynamic stability analysis was influenced to a large degree by the accuracy of the theoretical estimates of the pitch damping and Magnus moment coefficients. However, the approach used is considered conservative. The calculations

indicated that the present fin-cant angle of 30 minutes for the 1.0-inch dart is not optimum and may in fact contribute to dynamic instability. The optimum fin-cant angle was determined to be 6 minutes. It is recommended that this fin incidence angle be included in subsequent dart configurations built for field tests.

Aerodynamic heating studies conducted on the MK 32 MOD 0 motor casing indicated a marginal condition which, to avoid random performance, should be corrected by providing the motor casings with an ablative coating. The aerodynamic heating studies on the dart also revealed the inadequacy of the present 0.060-inch thick aluminum fins to maintain structural integrity, and make it imperative that future fins be constructed of 0.100-inch thick stainless steel.

In summary, it is recommended that the following corrective measures be applied to the HASP 300,000 foot system prior to any future field testing:

- a. Change the dart weight from 5 to 6 pounds.
- b. Change the dart fin incidence angle from 30 to 6 minutes.
- c. Change the fin material from 0.060-inch thick aluminum to 0.100-inch thick stainless steel.
 - d. Provide the motor casing with an ablative coating.

259.9	3802 .9	56696.1	-84.2	103659.0	0.4	5.0	3.1
260.9	3813.0	52907.3	-84.2	104044.3	0.3	5.0	3.7
261.9	3818.7	49110.3	-84.3	104427.3	0.1	5.0	4.5
262.9	381911	45309.9	-84.3	104807.3	0.1	5.0	5.3
263.9	3813.3	41511.8	-84.4	105184.0	0.3	5.0	6.4
264.9	3800.2	37722.6	-84.4	105556.6	0.5	5.0	7.6
265.9	3778.9	33950.2	-84.5	105924.4	0.8	5.0	8.9
266.9	3749.7	30202.7	-84.5	106286.7	1.0	5.0	10.1
267.9	3712.0	26488.2	-84.5	106642.7	1.3	5.0	11.5
268.9	3665 .6	22815.2	-84.6	106991.7	1.6	5.0	12.9
269.9	3610.2	19192.5	-84.6	107332.9	1.9	5.0	14.3
270.9	3545.6	15629.3	-84.7	107665.5	2.2	5.0	15.7
271.9	3471.9	12134.8	-84.7	107988.8	2.4	5.0	17.1
272.9	3389.3	8717.8	-84.8	108302.0	2.7	5.0	18.5
273.9	3298.2	5387.1	-84.8	108604.3	3.0	5.0	19.8
274.9	3199.2	2150.8	-84.9	108895.2	3.2	5.0	20.9
275.6	3127.5	-0.0	-84.9	109087.0	3.3	5.0	21.7

INITIAL DATA

Z(0) = 0. AL= 1.3089E CO V(0) = 10.0000E+02 ISP(0) = 2.3323E 02 K(T) = 6.4800E+01 D(B) = 8.3333E+02 D(M) = 2.5000E+01 M(B) = 1.5540E+01 M(0) = 8.7743E+01M(P) = 5.2278E+01 MR = 2.8110E+01

T 1 11 F			PATH				
TIME	VEL.	ALT.	ANGLE	RANGE	ACCEL.	WGT.	DRAG
(SEC)	(FT/SEC)	(FT)	(DEG)	(FT)	(G)	(LBS)	(LBS)
•	0.1	0.	75.0	C.	70.7	28.2	0.0
. 1	231.3		74.5	3.1	73.0	27.3	1.1
. 2	470.2		74.3		75.4	26.4	4.6
u.3	716.9	•	74.2	28.6	77.9	25.5	10.7
0.4	971.6		74.2	51.5	80.5	24.6	19.5
0.5	1234.7		74.1	81.6	83.1	23.7	
0.6	1506.4		74.1	119.1		22.8	46.6
0.7	1786.7		74.1	164.3	88.5	21.9	65.3
0.8	2076.1	764-7		217.3	91.3	21.0	87.7
0.9	2374.5	978.6	74.0	278.6	94.2	20.1	114.0
1.0	2682.4		74.0		97.2	19.2	144.4
1.1	2999.8	1494.6	74.0	426.6		18.3	179.2
1.2	3326.9	1798.5	74.0	514.0		17.4	218.4
1.3	3664.0	2134.4	73.9	610.6		16.5	262.3
1.4 1.5	4011.2	2503.1	73.9	716.7		15.6	310.9
1.6	4368 . 7	2905.6	73.9	832.7		14.7	364.4
1.7	4736.8 5115.6	3343.0	73.9 73.9	958.8	116.1	13.8	422.9
1.8	5505.6	3816.2	73.9	1095.4		12.9	486.3
1.9	5744 . 2	4326.3 4649.2	73.9	1242.7		11.9	554.7
1.9	5744.2	4649.2	73.9	1336.0 1336.0	125.1 11.2	11.4 5.0	597.9 51.1
2.9	5425.7	10007.2	73.8	2888.9		5.0	39.0
3.9	5173.5	15090.5	73.7	4371.3		5.0	30.3
4.9	4969.3	19953.3	73.6	5798.6		5.0	23.9
5.9	4801.0	24635.7	73.5	7182.2	4.8	5.0	19.1
6.9	4660.2	29167.9	73.4	8530.9		5.0	15.3
7.9	4540.9	33573.2	73.3	9851.2	3.4	5.0	12.4
8.9	4438.7	37870.1	73.1	11148.5			9.9
9.9	4351.5	42073.8	73.0			5.0	7.8
10.9	4276.0	46197.3	72.9		2.2	5.0	
11.9	4209.6	50250.3	72.8	14943.8	2.0	5.0	5.0
12.9	4150.2		72.6		1.8		4.0
13.9	4096.4	58174.1	72.5	17421.7	1.6	5.0	3.3
14.9	4047.0	62055.6	72.4	18650.4	1.5	5.0	2.6
15.9	4001.1	65888.8	72.2	19873.9			2.2
16.9	3958.0	69676.8	72.1	21093.2	1.3		1.8
17.9	3917.3	73421.9	71.9	22309.0	1.3	5.0	1.5
18.9	3878.4	77126.1	71.8	23521.8		5.0	1.2
19.9	3841.1	80791.0	71.6	24732.3		5.0	1.0
20.9	3805.0	84418.0	71.5			5.0	0.8
21.9	3770.0	88008.0	71.3	27147.5	1.1	5.0	0.7
22.9	3735.9	91562.1	71.2	28352.9		5.0	0.6
23.9	3702.5	95080.8	71.0	29557.1	1.1	5.0	0.5

TABLE 1
TABULATED TRAJECTORY DATA

Key to Tabulated Data

Run	<u>QE</u>	ISP
1A	75	lower
2 A		upper
1B	80	lower
2B		upper
1C	85	lower
2C		upper

INITIAL DATA

Z(0) = 0. AL= 1.3089E 00 V(0) = 10.0000E-02 ISP(0) = 2.2623E 02 K(T) = 6.4800E-01 D(B) = 8.3333E-02 D(M) = 2.5000E-01 M(B) = 1.5540E-01 M(0) = 8.7743E-01M(P) = 5.2278E-01 MR = 2.7514E-01

			PATH				
TIME	vel.	ALT.	ANGLE	RANGE	ACCEL.	WGT.	DRAG
(SEC)	(FT/SEC)	(FT)	(DEG)	(FT)	(G)	(LBS)	(LBS)
0.	0.1	0.	75.0	. 0.	67.0	28.2	0.0
0.1	219.1	10.5	74.4	2.9	69.2	27.3	1.0
0.2	445.2	42.4	74.3	11.9	71.4	26.5	4.1
0.3	678.5	96.4	74.2	27.1	73.7	25.6	9.6
0.4.	919.4	173.2	74.1	48.9	76.1	24.7	17.5
0.5	1168.0	273.6	74.1	77.5	78.5	23.8	28.2
0.6	1424.5	398.1	74.0	113.0	81.0	22.9	41.7
0.7	1689.1	547.7	74.0	155.9	83.5	22.0	58.4
0.8	1962.0	723.1	74.0	206.2	86.1	21.1	78.4
0.9	2243.4	925.2	74.0	264.2	88.8	20.3	101.9
1.0	2533.6	1154.6	73.9	330.3		19.4	129.1
1.1	2832.6	1412.4	73.9	404.6	94.3	18.5	160.2
1.2	3140.7	1699.3	73.9	487.3	97.2	17.6	195.2
1.3	3458.1	2016.2	73.9	578.8	100.1	16.7	234.5
1.4	3784.8	2364.0	73.9	679.4	103.1	15.8	278.0
1.5	4121.3	2743.6	73.9	789.3	106.1	14.9	325.9
1.6	4467.5	3156.1	73.8	908.7	109.2	14.1	378.3
1.7	4823.9	3602.2	73.8	1038.0	112.3	13.2	435.2
1.8	5190.6	4083.0	73.8	1177.4	115.6	12.3	496.6
1.9	5568.0	4599.5	73.8	1327.3	119.0	11.4	562.6
1.9	5568.2	4599.8	73.8	1327.4	119.0	11.4	562.7
1.9	5568.2	4599.8	73.8	1327.4	10.6	5.0	48.4
2.9	5264.0	9794.2	73.7	2839.8	8.4	5.0	37.2
3.9	5021.3	14725.2	73.6	4284.6	6.8	5.0	29.1
4.9	4823.5		73.5	5676.4		5.0	23.1
5.9	4659.6	23986.3	73.4	7025.8		5.0	18.5
6.9	4521.7	28382.4	73.3	8341.0		5.0	14.9
7.9	4404.1	32654.0	73.2	9628.5	3.4	5.0	12.1
8.9	4302.9		73.0	10893.2	2.9	5.0	9.8
9.9	4215.8	40890.3	72.9	12139.5	2.5	5.0	7.8
10.9	4140-1	44881.7	72.8	13371.0		5.0	6.3
11.9	4073.3	48802.5					5.0
12.9	4013.5	52660.1	72.5	15800.2	1.8	5.0	4.1
13.9	3959.2	56460-6	72.4	17002.1	1.6	5.0	3.3
14.9	3909.3	60208.5	72.2	18197.4	1.5	5.0	2.7
15.9	3862.9	63907.7	72.1	19387.3	1-4	5.0	2.2
16.9	3819.4	67561.1	71.9	20572.9	1.3	5.0	1.8
17.9	3778.3	71171.2	71.8	21754.7	1.3	5.0	1.5
18.9	3739.0	74740.1	71.6	22933.4	1.2	5.0	1.3
19.9	3701.3	78269.2	71.5	24109.6	1.2	5.0	1.0
20.9	3664.8	81760.0	71.3	25283.7	1.2	5.0	0.9
21.9	3629.5	85213.6	71.2	26455.9	1.1	5.0	0.7
22.9	3595.0	88630.8	71.0	27626.6	1.1	5.0	0.6

			70.0	28796.1	1.1	5.0	0.5
23.9	3561-4	92012.4	70.8	29964.5	1.1	5.0	0.4
24.9	3528.3	95359.1	76.7		1.1	5.0	0.4
25.9	3495.8	98671-4	70.5	31132.0	1.0	5.0	0.3
26.9	3463.7	101949-6	70.3	32298.8		4.9	0.3
27.9	3431.9	105194.2	70.1	33464.9	1.0	4.9	0.2
28.9	3400.5	108405.4	70.0	34630.4	1.0		0.2
29.9	3369.4	111583.5	69.8	35795.5	1.0	4.9	0.2
30.9	3338.4	114728.6	69.6	36960.2	1.0	4.9	
31.9	3307.7	117841.0	69.4	38124.5	1.0	4.9	0.1
32.9	3277.1	120920.8	69.2	39288.6	1.0	4.9	0.1
33.9	3246.7	123968.0	69.0	40452.3	1.0	4.9	0.1
34.9	3216.5	126982.9	68.8	41615.9	1.0	4.9	0.1
35.9	3186.4	129965.5	68.6	42779.2	1.0	4.9	0.1
36.9	3156-4	132915.8	68.4	43942.4	1.0	4.9	0.1
	3126.5	135834.0	68.2	45105.4	1.0	4.9	0.1
37.9	3096.7	138720.1	67.9	46268.2	1.0	4.9	0.0
38.9	3067.0	141574.1	67.7	47431.0	1.0	4.9	.0.0
39.9	3037.4	144396.2	67.5	48593.6	1.0	4.9	0.0
40.9		147186.2	67.3	49756.2	1.0	4.9	0.0
41.9	3007.8	149944.4	67.0	50918.6	1.0	4.9	0.0
42.9	2978.4		66.8	52081.0	1.0	4.9	0.0
43.9	2949.0	152670.6	66.5	53243.3	1.0	4.9	0.0
44.9	2919-8	155365.0		54405.6	1.0	4.9	0.0
45.9	2890.6	158027.5	66.3	55567.8	1.0	4.9	0.0
46.9	2861.5	160658.3	66.0	56729.9	1.0	4.9	0.0
47.9	2832.4	163257.2	65.8	57892.0	1.0	4.9	0.0
48.9	2803.5	165824.4	65.5		1.0	4.9	0.0
49.9	2774.6	168359.7	65.2	59054.1	1.0	4.9	0.0
50.9	2745.8	170863.4	65.0	60216.1	1.0	4.9	0.0
51.9	2717.1	173335.3	64.7	61378.1		4.9	0.0
52.9	2688.4	175775.5	64.4	62540.1	1.0	4.9	0.0
53.9	2659.9	178184.1	64.1	63702.0	1.0	4.9	0.0
54.9	2631.4	180560.9	63.8	64864.0	1.0	4.9	0.0
55.9	2603.0	182906.1	63.5	66025.8	1.0		0.0
56.9	2574.7	185219.6	63.2	67187.7	1.0	4.9	0.0
57.9	2546.5	187501-4	62.9	68349.6	1.0	4.9	
58.9	2518.4	189751.6	62.5	69511.4	1.0	4.9	0.0
59.9	2490.4	191970-2	62-2	70673-2	1.0	4.9	0.0
60.9	2462.5	194157.2	61.8	71835.0	1.0	4.9	0.0
	2434.6	196312.5	61.5	72996.8	1.0	4.9	
61.9	2406.9	198436.3	61.1	74158. 5	1.0	4.9	0.0
62.9	2379.3	200528-4	60.8	75320. 3	1.0	4.9	0.0
63.9	2351.8	202589-0	60.4	76482.0	1.0	4.9	0.0
64.9	2324.4	204618-0	60.0	77643.8	1.0	4.9	0.0
65.9		206615-4	59.6	78805.5	1.0	4.9	0.0
66.9	2297.1	208581-3	59.2	79967.2	1.0	4.9	0.0
67.9	2269.9	210515.6	58.8	81128.9	1.0	4.9	0.0
68.9	2242.8	212418-4	58.4	82290.6	1.0	4.9	0.0
69.9	2215.9		57.9	83452.3	1.0	4.9	0.0
70.9	2189.1	214289.6	57.5	84614.0	1.0	4.9	0.0
71.9	2162-5	216129.3	57.1	85775.7	1.0	4.9	0.0
72.9	2135.9	217937.5		86937.3	1.0	4.9	0.0
73.9	2109.6	219714.1	56.6	88099.0	1.0	4.9	0.0
74.9	2083.3	221459.3	56.1	89260.7	1.0	4.9	0.0
75.9	2057.2	223172.9	55.6		1.0	4.9	0.0
76.9	2031.3	224855.0	55-1	90422.3	1.0	4.9	0.0
77.9	2005.6	226505.6	54.6	91584.0	1.0	4.9	0.0
78.9	1980.0	228124.8	54.1	92745.6		4.9	0.0
79.9	1954-6	229712.4	53.5	93907.3	1.0	4.9	0.0
80.9	1929.3	231268.6	53.0	95068.9	1.0	4.9	0.0
81.9	1904.3	232793.3	52.4	96230.6	1.0	4.7	
			~				

82.9	1879.5	234286.5	51.8	97392.2	1.0	4.9	0.0
83.9	1854.8	235748.2	51.2	98553.8	1.0	4.9	0.0
			50.6	99715.5	1.0	4.9	0.0
84.9	1830.4	237178.5					
85.9	1806.2	238577.4	50.0	100877.1	1.0	4.9	0.0
86.9	1782.2	239944.7	49.3	102038.7	1.0	4.9	0.0
87.9	1758.5	241280.7	48.7	103200.4	1.0	4.9	0.0
88.9	1735.0	242585.1	48.0	104362.0	1.0	4.9	0.0
89.9	1711.8	243858.2	47.3	105523.6	1.0	4.9	0.0
				106685.2	1.0	4.9	0.0
90.9	1688.8	245099.8	46.5				
91.9	1666.2	246310.0	45.8	107846.8	1.0	4.9	0.0
92.9	1643.8	247488.7	45.0	109008.5	1.0	4.9	0.0
93.9	1621.7	248636.0	44.3	110170.1	1.0	4.9	0.0
94.9	1599.9	249751.9	43.4	111331.7	1.0	4.9	0.0
95.9	1578.5	250836.4	42.6	112493.3	1.0	4.9	0.0
		251889.5	41.8	113654.9	1.0	4.9	0.0
96.9	1557.4					4.9	0.0
97.9	1536.6	252911.1	40.9	114816.5	1.0		
98.9	1516.3	253901.4	40.0	115978.1	1.0	4.9	0.0
99.9	1496.3	254860.2	39.1	117139.8	1.0	4.9	0.0
100.9	1476.7	255787.7	38.1	118301.4	1.0	4.9	0.0
101.9	1457.5	256683.7	37.2	119463.0	1.0	4.9	0.0
102.9	1438.8	257548.3	36.2	120624.6	1.0	4.9	0.0
				121786.2		4.9	0.0
103.9	1420-5	258381.6	35.1		1.0		
104.9	1402.6	259183.4	34.1	122947.8	1.0	4-9	0.0
105.9	1385.3	259953 .9	33.0	124109.4	1.C	4.9	0.0
106.9	1368.4	260693.0	31.9	125271.0	1.0	4.9	0.0
107.9	1352.1	261400.7	30.8	126432.6	1.0	4.9	0.0
108.9	1336.3	262077.0	29.6	127594.2	1.0	4.9	0.0
			28.4	128755.8	1.0	4.9	0.0
109.9	1321.1	262721.9				4.9	0.0
110.9	1306.4	263335.5	27.2	129917.4	1.0		
111.9	1292.4	263917.6	26.0	131079.0	1.0	4.9	0.0
112.9	1278.9	264468.4	24.7	132240.6	1.0	4.9	0.0
113.9	1266.1	264987.9	23.4	133402.2	1.0	4.9	0.0
114.9	1254.0	265475.9	22.1	134563.8	1.0	4.9	0.0
115.9	1242.5	265932.6	20.8	135725.4	1.0	4.9	0.0
		266357.9	19.4	136887.0	1.0	4.9	0.0
116.9	1231.7					4.9	0.0
117.9	1221.6	266751.8	18-0	138048.6	1.0		
118.9	1212.3	267114.4	16.6	139210.2	1.0	4.9	0.0
119.9	1203.7	267445.6	15.2	140371.8	1.0	4.9	0.0
120.9	1195.9	267745.5	13.7	141533.4	1.0	4.9	0.0
121.9	1188.8	268014-0	12.3	142695.0	1.0	4.9	0.0
122.9	1182.5	268251.1	10.8	143856.6	1.0	4.9	0.0
		268456.8	9.3	145018.2	1.0	4.9	0.0
123.9	1177.0			146179.8	1.0	4.9	0.0
124.9	1172.4	268631.2	7.8			4.9	0.0
125.9	1168.6	268774.3	6-3	147341.4	1.0		
126.9	1165.6	268885.9	4.7	148503.0	1.0	4.9	0.0
127.9	1163.4	268966.3	3.2	149664.6	1.0	4.9	0.0
128.9	1162.1	269015.2	1.6	150826.2	1.0	4.9	0.0
129.9	1161.6	269032.8	0.1	151987.8	1.0	4.9	0.0
	1162.0	269019.0	-1.5	153149.4	1.0	4.9	0.0
130.9			-3.0	154311.0	1.0	4.9	0.0
131.9	1163.2	268973.9				4.9	0.0
132.9	1165.2	268897.4	-4.5	155472.6	1.0		
133.9	1168.1	268789.6	-6.1	156634.1	1.0	4.9	0.0
134.9	1171.9	268650-4	-7.6	157795.7	1.0	4.9	0.0
135.9	1176.4	268479.8	-9.1	158957.3	1.0.	4.9	0.0
	1181.8	268277.9	-10.6	160118.9	1.0	4.9	0.0
136.9			-12.1	161280.5	1.0	4.9	0.0
137.9	1188.0	268044-6			1.0	4.9	0.0
138.9	1194.9	267779.9	-13.6	162442.1			
139.9	1202.7	267483.9	-15.0	163603.7	1.0	4.9	0.0
140.9	1211.2	267156.6	-16.5	164765.3	1.0	4.9	0.0
	- · · -						

141.9	1220.4	266797.8	-17.9	165926.9	1.0	4.9	0.0
142.9	1230.4	266407.7	-19.3	167088.5	1.0	4.9	0.0
143.9	1241.1	265986.2	-20.6	168250.0	1.0	4.9	0.0
		265533.4	-22.0	169411.6	1.0	4.9	0.0
144.9	1252.5						
145.9	1264.6	265049.1	-23.3	170573.2	1.0	4.9	0.0
146.9	1277.3	264533.6	-24.6	171734.8	1.0	4.9	0.0
147.9	1290.7	263986.6	-25.8	172896.4	1.0	4.9	0.0
148.9			-27.1	174058.0	1.0	4.9	0.0
	1304.7	263408.3					
149.9	1319.2	262798.5	-28.3	175219.6	1.0	4.9	0.0
150.9	1334.4	262157.4	-29.5	176381.2	1.0	4-9	0.0
151.9	1350.1	261485.0	-30.6	177542.7	1.0	4.9	0.0
152.9	1366.4	260781.1	-31.8	178704.3	1.0	4.9	0.0
						4.9	0.0
153.9	1383.2	260045.9	-32.9	179865.9	1.0		
154.9	1400.5	259279.3	-34.0	181027.5	1.0	4_9	0.0
155.9	1418.2	258481.3	-35.0	182189.1	1.0	4.9	0.0
156.9	1436.5	257651.9	-36.0	183350.6	1.0	4.9	0.0
157.9	1455.2	256791.1	-37.0	184512.2	1.0	4.9	0.0
						4.9	
158.9	1474.3	255898.9	-38.0	185673.8	1-0		0.0
159.9	1493.8	254975.3	-39.0	186835.4	1.0	4.9	0.0
160.9	1513.8	254020.3	-39.9	187997.0	1.0	4.9	0.0
161.9	1534.1	253033.9	-40.8	189158.5	1.0	4.9	0.0
162.9	1554.8	252016.1	-41.7	190320.1	1.0	4.9	0.0
163.9	1575.8	250966.9	-42.5	191481.7	1.0	4.9	0.0
164.9	1597.2	249886.3	-43.3	192643. 3	1.0	4.9	0.0
165.9	1619.0	248774.2	-44.2	193804.8	1.0	4.9	0.0
166.9	1641.0	247630.8	-44.9	194966.4	1.0	4.9	0.0
167.9	1663.4	246455.9	-45.7	196128.0	1.0	4.9	0.0
168.9	1686.0	245249.6	-46.5	197289.5	1.0	4.9	0.0
169.9	1708.9	244011.9	-47.2	198451.1	1.0	4.9	0.0
170.9	1732.1	242742.7	-47.9	199612.7	1.0	4.9	0.0
171.9	1755.5	241442.1	-48.6	200774.2	1.0	4.9	0.0
			-49.2	201935.8	1.0	4.9	0.0
172.9	1779.2	240110.1					
173.9	1803.2	238746.6	-49.9	203097.3	1.0	4.9	0.0
174.9	1827.3	237351.6	-50.5	204258.9	1.0	4.9	0.0
175.9	1851.7	235925.2	-51.2.	205420.5	1.0	4.9	0.0
176.9	1876.3	234467.4	-51.8	206582.0	1.0	4.9	0.0
			-52.3			4.9	
177.9	1901.1	232978.1		207743.6	1.0		0.0
178.9	1926.1	231457.4	52.9	208905.1	1.0	4.9	0.0
179.9	1951.3	229905.1	-53.5	210066.6	1.0	4.9	0.0
180.9	1976.7	228321.4	-54.0	211228.2	1.0	4.9	0.0
181.9	2002.3	226706.2	-54.5	212389.7	1.0	4.9	0.0
						4.9	0.0
182.9	2028.0	225059-6	-55.1	213551.3	1.0		
183.9	2053.9	223381.4	-55.6	214712.8	1.0	4-9	0.0
184.9	2079.9	221671.8	-56.1	215874.3	1.0	4.9	0.0
185.9	2106.1	219930.7	-56.5	217035.8	1.0	4.9	0.0
186.9	2132.5	218158.1	-57.0	218197.3	1.0	4.9	0.0
							0.0
187.9	2158.9	216353.9	-57.5	219358.8	1.0	4.9	
188.9	2185.6	214518.3	-57.9	220520.4	1.0	4.9	0.0
189.9	2212.3	212651.2	-58.3	221681.8	1.0	4.9	0.0
190.9	2239.2	210752.5	-58.8	222843.3	1.0	4.9	0.0
191.9	2266.2	208822.3	-59.2	224004.8	1.0	4.9	0.0
					1.0	4.9	0.0
192.9	2293.3	206860-6	-59.6	225166.3			
193.9	2320.6	204867.3	-60.0	226327.8	1.0	4.9	0.0
194.9	2347.9	202842.6	-60.4	227489.2	1.0	4.9	0.0
195.9	2375.4	200786.3	-60.7	228650.7	1.0	4.9	0.0
196.9	2403.0	198698.4	-61.1	229812.1	1.0	4.9	0.0
					1.0	4.9	0.0
197.9	2430.6	196579.0	-61.5	230973.5			
198.9	2458.4	194428.0	-61.8	232134.9	1.0	4.9	0.0
199.9	2486.2	192245.5	-62.2	233296. 3	1-0	4.9	0.0
			5				
			Þ				

200.9	2514.2	190031.4	-62.5	234457.7	1.0	4.9	0.0
	2542.2	187785.8	-62.8	235619.1	1.0	4.9	0.0
201.9		185508.6	-63.1	236787.4	1.0	4.9	0.0
202.9	2570.3			237941.7	1.0	4.9	0.0
203.9	2598.5	183199.8	-65.5		1.0	4.9	0.0
204.9	2626.8	180859.5	-63.8	239103.0		4.9	0.0
205.9	2655.1	178487.6	-64.1	240264.3	1.0		
206.9	2683.5	176084.1	-64-4	241425.6	1.0	4.9	0.0
207.9	2712.0	173649.0	-64.6	242586.8	1.0	4.9	0.0
208.9	2740.6	171182.3	-64.9	243748.0	1.0	4.9	0.0
209.9	2769.2	168684.1	-65.2	244909.2	1.0	4.9	0.0
210.9	2 797.9	166154.3	-65.5	24607 0.3	1.0	4.9	0.0
211.9	2826.7	163592.9	-65.7	247231.4	1.0	4.9	0.0
212.9	2855 .5	160999.9	-66.0	248392.4	1.0	4.9	0.0
213.9	2884.3	158375.3	-66.3	249553.4	1.0	4.9	0.0
214.9	2913.2	155719.2	-66.5	250714.3	1.0	4.9	0.0
215.9	2942.2	153031.5	-66.8	251875.2	1.0	4.9	0.0
216.9	2971.1	150312.3	-67.0	253036.0	1.0	4.9	0.0
217.9	3000.2	147561.5	-67.2	254196.8	1.0	4.9	0.0
218.9	3029.2	144779.2	-67.5	255357.4	1.0	4.9	0.0
219.9	3058.3	141965.4	-67.7	256518.0	1.0	4.9	0.0
220.9	3087.4	139120.1	-67.9	257678.4	1.0	4.9	0.0
221.9	3116.5	136243.4	-68.1	258838.8	1.0	4.9	0.1
222.9	3145.6	133335.2	-68.4	259999.0	1.0	4.9	0.1
	3174.7	130395.7	-68.6	261159.0	1.0	4.9	0.1
223.9		127424-8	-68.8	262318.9	1.0	4.9	0.1
224.9	3203.8		-69.0	263478.6	1.0	4.9	0.1
225.9	3232.9	124422.6		264638.1	1.0	4.9	0.1
226.9	3261.9	121389-2	-69.2		1.0	4.9	0.1
227.9	3290.9	118324.7	-69.4	265797.3		4.9	0.2
228.9	3319.8	115229.2	-69.6	266956.2	1.0		0.2
229.9	3348.6	112102.7	-69.8	268114.7	1.0	4.9	
230.9	3377.3	108945.5	-69.9	269272.9	1.0	4.9	0.2
231.9	3405.8	105757.7	-70.1	270430.6	0.9	4.9	0.2
232.9	3434.0	102539.5	-70.3	271587.8	0.9	5.0	0.3
233.9	3462.1	99291.2	-70.5	272744.4	0.9	5.0	0.3
234.9	3489.8	96013.0	-70.7	273900.3	0.9	5.0	0.4
235.9	3517.1	92705.4	-70.8	275055.3	0.9	5.0	0.5
236.9	3543.9	89368.8	-71.0	276209.2	0.9	5.0	0.6
237.9	3570.1	86003.7	-71.2	277362.1	0.9	5.0	0.7
238.9	3595.5	82610.9	-71.3	278513.5	0.8	5.0	0.8
239.9	3620.1	79191.1	-71.5	279 663•2	0.8	5.0	1.0
240.9	3643.6	75745.3	-71.7	280810.9	0.8	5.0	1.2
241.9	3665.8	72274.6	-71.8	281956.3	0.7	5.0	1.4
242.9	3686.5	68780.4	-72.0	283099.0	0.7	5.0	1.6
243.9	3705.4	65264.3	-72.1	284238.3	0.6	5.0	2.0
244.9	3722.0	61728.3	-72.3	285373.8	0.6	5.0	2.3
245.9	3736.1	58174.6	-72.4	286504.7	0.5	5.0	2.8
246.9	3747.0	54606.0	-72.6	287630.2	0.4	5.0	3.3
247.9	3754.3	51025.8	-72.7	288749.2	0.3	5.0	4.0
248.9	3757.1	47438.0	-72.9	289860.7	0.3	5.0	4.7
249.9	3754.8	43847.1	-73.0	290963.3	0.3	5.0	5.6
250.9	3746.4	40258.5	-73.1	292055.4	0.5	5.0	6.6
251.9	3731.0	36678.5	-73.3	293135.1	0.7	5.0	7.8
	3708.0	33114.2	-73.4	294200.5	0.9	5.0	8.9
252.9		29572.8	-73.6	295249.6	1.1	5.0	10.1
253.9	3677.8		-73.7	296280.3	1.3	5.0	11.3
254.9	3639.8	26061.5	-73 . 9	297290.6	1.6	5.0	12.6
255.9	3593.9	22588.0		298278.5	1.8	5.0	13.9
256.9	3539.6	19160.0	-74.0		2.1	5.0	15.2
257.9	3477.1	15785.8	-74 · 1	299241.7			16.4
258 .9	3406.3	12473.2	-74.3	300178.3	2.3	5.0	10.4

259.9	3327.5	9230.4	-74.4	301086.2	2.6	5.0	17.7
260.9	3241.0	6064.9	-74.6	301963.6	2.8	5.0	18.8
261.9	3147.3	2984.0	-74.7	302808.8	3.0	5.0	19.9
262.9	3047.3	-0.0	-74.9	303618.9	3.2	5.0	20.9

INITIAL DATA

Z(0)= 0. AL= 1.3962E 00 V(0)= 10.0000E-02 ISP(0)= 2.2623E 02 K(T)= 6.4800E-01 D(B)= 8.3333E-02 D(M)= 2.5000E-01 M(B)= 1.5540E-01 M(0)= 8.7743E-01 M(P)= 5.2278E-01 MR= 2.7514E-01

			PATH				
TIME	VEL.	ALT.		RANGE	ACCEL.	WGT.	DRAG
(SEC)	(FT/SEC)	(FT)	(DEG)	(FI)	(G)	(LBS)	(LBS)
0.	0.1	0.	80.0	0.	67.0	28.2	0.0
0.1	219.0	10.7	79.6	1.9	69.1	27.3	1.0
0.2	445.0	43.3	79.5	8.0	71.4	26.5	4.1
0.3	678.3	98.5	79.5	18.2	73.7	25.6	
0.4	919.1	176.9	79.4	32.8		24.7	17.5
0.5	1167.6	279.4	79.4	52. 0		23.8	
0.6	1424.1	406-7	79.4	75.9	81.0	22.9	
0.7	1688.6	559.6	79.3	104.7	83.5	22.0	58.4
0.8	1961.5	738.9	79.3	138.5	86.1	21.1	78.3
0.9	2242.9	945.4	79.3	177.5	88.8	20.3	
1.0	2533.0	1179.9	79.3	221.8	91.5	19.4	
1.1	2832.0		79.3	271.7	94.3	18.5	
1.2	3140.1	1736.7	79.3	327.3	97.2	17.6	194.9
1.3	3457.5		79.3	388.8	100.1	16.7	234.1
1.4	3784.3	2416.4	79.2	456.3	103.1	15.8	277.5
1.5	4120.8	2804.6	79.2	530.2	106.1	14.9	325.2
1.6	4467.2	3226.4	79.2	610.4	109.2	14.1	377.4
1.7	4823.8	3682.7	79.2	697.3		13.2	434.1
1.8	5190.8	4174.4	79.2	791.0	115.7	12.3	495.3
1.9	5568.5	4702.8	79.2	891.7	119.1	11.4	561.0
1.9	5568.7	4703.1	79.2	891.7	119.1	11.4	561.0
1.9	5568.7	4703.1	79.2	891.7	10.6	5.0	48.3
2.9	5265.2	10017.6	79.1	1908.3	8.4	5.0	36.9
3.9	5023.6	15065.0	79.1	2879.7	5.7	5.0	28.8
4.9	4827.1	19897.3	79.0	3815.8	5.5	5.0	22.8
5.9	4664.6	24553.0	78.9	4723.9	4.6		18.2
6.9	4528.1	29061.3	78.8	5609.4	3.9		14.6
7.9	4412.0	33444.9	78.8	6476.6			11.8
8.9	4312.2	37721.7	78.7	7329.0			9.5
9.9	4226.6	41906.5	78.6				
10.9	4152.2	46011.9	78.5	9000.2			6.0
11.9	4086.5	50047.5	78.4	9823.4	1.9	5.0	4.8
12.9	4027.4	54020.8	78.3	10640.4	1.8	5.0	3.9
13.9	3973.8	57937.7	78.2	11452.4	1-6	5.0	3.1
14.9	3924.3	61802.9	78.1	12260.3	1.5	5.0	2.5
15.9	3878.2	65620.0	78.1	13064.7	1.4	5.0	2.1
16.9	3834.8	69392.1	78.0	13866.4	1.3	5.0	1.7
17.9	3793.6	73121.4	77.9	14665.9	1.3	5.0	1.4
18.9	3754.2	76810.0	77.7	15463.4	1.2	5.0	1.2
19.9	3716.3	80459.3	77.6	16259.3	1.2	5.0	1.0
20.9	3679.5	84070.7	77.5	17053.9	1-1	5.0	0.8
21.9	3643.8	87645-3	77.4	17847.5	1.1	5.0	0.6
22.9	3608.9	91183.8	77.3	18640.1	1.1	5.0	0.5

								0 4.
	23.9	3574.7	94687.2	77.2	19431.9	1.1	5.0	0.4
	24.9	3541.0	98155.9	77.1	20223.2	1.1	5.0	0.4
			101590.4	77.0	21013.9	1.1	5.0	0.3
	25.9	3507.8				1.0	4.9	0.3
	26.9	3474.9	104991.0	76.9	21804.1			
	27.9	3442.4	108358.3	76.7	22594.0	1.0	4.9	0.2
	28.9	3410.1	111692.3	76.6	23383. 6	1.0	4.9	0.2
		3378.1	114993.3	76.5	24172.9	1.0	4.9	0.2
•	29.9					1.0	4.9	0.1
	30.9	3346.2	118261.5	76.4	24961.9			
	31.9	3314.5	121497.0	76.2	25750.8	1.0	4.9	0.1
	32.9	3282.9	124700.1	76.1	26539.4	1.0	4.9	0.1
-		3251.5	127870.7	76.0	27327.9	1.0	4.9	0.1
	33.9				28116.3	1.0	4.9	0.1
	34.9	3220.2	131009.0	75.8				0.1
	35.9	3189.0	134115.1	75.7	28904.6	1.0	4.9	
	36.9	3157.8	137189.1	75.5	2969 2.8	1.0	4.9	0.1
	37.9	3126.7	140230.9	75.4	30480.8	1.0	4.9	0.0
			143240.7	75.3	31268.9	1.0	4.9	0.0
	38.9	3095-8					4.9	0.0
	39.9	3064-8	146218.5	75.1	32056.8	1.0		
	40.9	3034.0	149164.4	74.9	32844.7	1.0	4.9	0.0
	41.9	3003.2	152078.3	74.8	33632.5	1.0	4.9	0.0
		2972.4	154960.3	74.6	34420.3	1.0	4.9	0.0
	42.9					1.0	4.9	0.0
	43.9	2941.7	157810.5	74.5	35208.0			
	44.9	2911.1	160628.9	74.3	35995.7	1.0	4.9	0.0
	45.9	2880.4	163415.5	74.1	36783.4	1-0	4.9	0.0
		2849.9	166170.2	74.0	37571.0	1.0	4.9	0.0
	46-9				38358.6	1.0	4.9	0.0
	47.9	2819.4	168893.3	73.8				
	48.9	2788.9	171584.5	73.6	39146.2	1.0	4.9	0.0
	49.9	2758.5	174244.1	73.4	39933.7	1.0	4.9	0.0
~	50.9	2728.1	176871.9	73.2	40721.3	1.0	4.9	0.0
				73.0	41508.8	1.0	4.9	0.0
	51.9	2697.8	179468.0				4.9	0.0
	52.9	2667.5	182032.5	72.8	42296.3	1.0		
	53.9	2637.3	184565-3	72.6	43 083.8	1.0	4.9	0.0
	54.9	2607.1	187066.4	72.4	43871.2	1.0	4.9	0.0
			189535.9	72.2	44658.7	1.0	4.9	0.0
	55.9	2576.9				1.0	4.9	0.0
	56.9	2546.8	191973.7	72.0	45446.1			
	57.9	2516.8	194380.0	71.8	46233.6	1.0	4.9	0.0
	58.9	2486.8	196754.6	71.5	47021.0	1.0	4.9	0.0
		2456.8	199097.6	71.3	47808.4	1.0	4.9	0.0
	59.9				48595.8	1.0	4.9	0.0
•	60.9	2426.9	201409.0	71.1				0.0
	61.9	2397.1	203688.8	70.8	49383.2	1.0	4.9	
	62.9	2367.3	205937.1	70.6	50170.6	1.0	4.9	0.0
	63.9	2337.5	208153.8	70.3	50958.0	1.0	4.9	0.0
				70.1	51745.4	1.0	4.9	0.0
	64.9	2307.8	210338-9			1.0	4.9	0.0
	65.9	2278.2	212492.5	69.8	52532.8			
	66.9	2248.6	214614.6	69.5	53320.2	1.0	4.9	0.0
	67.9	2219.1	216705.1	69-2	54107.5	1.0	4.9	0.0.
			218764-1	68.9	54894.9	1.0	4.9	0.0
	68.9	2189.7			55682.3	1.0	4.9	0.0
	69.9	2160.3	220791.5	68.6				0.0
	70.9	2131.0	222787.5	68.3	56469.6	1.0	4.9	
	71.9	2101.8	224751.9	68.0	57257.0	1.0	4.9	0.0
		2072.6	226684.9	67.7	58044.3	1.0	4.9	0.0
	72.9			67.3	58831.7	1.0	4.9	0.0
	73.9	2043.5	228586.3			1.0	4.9	0.0
4"	74.9	2014.5	230456.3	67.0	59619.0			
	75.9	1985.5	232294.8	66.6	60406.4	1.0	4.9	0.0
	76.9	1956.7	234101.8	66.3	61193.7	1.0	4.9	0.0
			235877.4	65.9	61981.0	1.0	4.9	0.0
	77.9	1927.9				1.0	4.9	0.0
	78.9	1899.2	237621.5	65.5	62768.4			
	79.9	1870.7	239334.1	65.1	63555.7	1.0	4.9	0.0
	80.9	1842.2	241015.3	64.7	64343.1	1.0	4.9	0.0
		1813.8	242665.0	64.3	65130.4	1.0	4.9	0.0
	81.9	1013.0	44600340				•	
				9				
						•		

82.9	1785.5	244283.3	63.8	65917.7	1.0	4.9	0.0
83.9	1757.4	24587C.2	63.4	66705.1	1.0	4.9	0.0
84.9	1729.3	247425.6	62.9	67492.4	1.0	4.9	0.0
85.9	1701.4	248949.6	62.4	68279.7	1.0	4.9	0.0
	1673.6	250442.2	61.9	69067.1	1.0	4.9	0.0
86.9	1646.0	251903.4	61.4	69854.4	1.0	4.9	0.0
87.9		253333.1	60.9	70641.7	1.0	4.9	0.0
88.9	1618.5	254731.5	60.3	71429.0	1.0	4.9	0.0
89.9	1591.1	256098.4	59.8	72216.4	1.0	4.9	0.0
90.9	1563.9	257434.C	59.2	73003.7	1.0	4.9	0.0
91.9	1536.8	258738.1	58.6	73791.0	1.0	4.9	0.0
92.9	1510.0	260010.9	57.9	74578.4	1.0	4.9	0.0
93.9	1483.3	261252.2	57.3	75365.7	1.0	4.9	0.0
94.9	1456.8		56.6	76153.0	1.0	4.9	0.0
95.9	1430.5	262462.2	55.9	76940.3	1.0	4.9	0.0
96.9	1404.4	263640.8	55.2	77727.7	1.0	4.9	0.0
97.9	1378.5	264788.0	54.4	78515.0	1.0	4.9	0.0
98.9	1352.9	265903.9		79302.3	1.0	4.9	0.0
99.9	1327.5	266988-4	53.6	80089.6	1.0	4.9	0.0
100.9	1302.4	268041-5	52.8	80876.9	1.0	4.9	0.0
101.9	1277.5	269063.3	52.0	81664.3	1.0	4.9	0.0
102.9	1253.0	270053-7	51.1		1.0	4.9	0.0
103.9	1228.7	271012.7	50.2	82451.6	1.0	4.9	0.0
104.9	1204.8	271940.4	49.2	83238.9		4.9	0.0
105.9	1181.3	272836.7	48.2	84026.2	1.0	4.9	0.0
106.9	1158.1	273701.7	47.2	84813.6	1.0	4.9	0.0
107.9	1135.3	274535.3	46.1	85600.9	1.0	4.9	0.0
108.9	1112.9	275337.6	45.0	86388.2	1.0		0.0
109.9	1091.0	276108.6	43.8	87175.5	1.0	4.9	
110.9	1069.6	276848.2	42-6	87962.8	1.0	4.9	0.0
111.9	1048.6	277556.5	41.3	88750.2	1.0	4.9	0.0
112.9	1028.2	278233.4	40.0	89537.5	1.0	4.9	0.0
113.9	1008.3	278879-1	38.7	90324.8	1.0	4.9	0.0
114.9	989.0	279493.3	37.2	91112.1	1.0	4.9	0.0
115.9	970.4	280076.3	35.8	91899.4	1.0	4.9	0.0
116.9	952.4	280627.9	34.2	92686.8	1.0	4.9	0.0
117.9	935.2	281148.2	32.7	93474.1	1.0	4.9	0.0
118.9	918.6	281637.2	31.0	94261.4	1.0	4.9	0.0
119.9	902.9	282094-8	29.3	95048.7	1.0	4.9	0.0
120.9	888.0	282521.2	27.5	95836.0	1.0	4.9	
121.9	873.9	282916.2	25.7	96623.4	1.0	4.9	0.0
122.9	860.8	283279.9	23.8	97410.7	1.0	4.9	0.0
123.9	848.6	283612.2	21.9	98198.0	1.0	4.9	0.0
124.9	837.5	283913.3	19.9	98985.3	1.0	4.9	0.0
125.9	827.3	284183.1	17.9	99772.6	1.0	4.9	0.0
12 9	818.2	284421.5	15.8	100560.0	1.0	4.9	0.0
127.9	810.3	284628.6	13.7	101347.3	1.0	4.9	0.0
128.9	803.4	284804.4	11.5	102134.6	1.0	4.9	0.0
129.9	797.8	284948.9	9.3	102921.9	1.0	4.9	0.0
130.9	793.3	285062.1	7.1	103709.2	1.0	4.9	0.0
131.9	790.1	285143.9	4.8	104496.6	1.0	4.9	0.0
132.9	788.1	285194.5	2.5	105283.9	1.0	4.9	0.0
133.9	787.3	285213.7	0.3	106071.2	1.0	4.9	0.0
134.9	787.8	285201.6	+2.0	106858.5	1.0	4.9	0.0
135.9	789.5	285158.3	-4.3	107645.8	1.0	4.9	0.0
136.9	792.5	285083.6	-6.5	108433.2	1.0	4.9	0.0
137.9	796.7	284977.5	-8.8	109220.5	1.0	4.9	0.0
138.9	802.0	284840.2	-11.0	110007.8	1.0	4.9	0.0
139.9	808.4	284671.6	-13.2	110795.1	1.0	4.9	0.0
140.9	816.3	284471.6	-15.3	111582.4	1.0	4.9	0.0

						4.9	0.0
141.9	825.1	284240-4	-17.4	112369.8	1.0	4.9	0.0
142.9	835.0	283977.8	-19.5	113157.1	1.0		0.0
143.9	846.0	283683.9	-21.5	113944.4	1.0	4.9	0.0
144.9	857.9	283358.7	-23.4	114731.7	1.0	4.9	
145.9	870.9	283002.2	-25.3	115519.0	1.0	4.9	0.0
146.9	884.7	282614.3	-27.1	116306.4	1.0	4.9	0.0
147.9	899.4	282195.2	28.9	117093.7	1.0	4.9	0.0
148.9	915.0	281744.7	-30.6	117881.0	1.0	4.9	0.0
149.9	. 931.3	281262.9	-32.3	118668.3	1.0	4.9	0.0
150.9	948.4	280749.8	-33.9	119455.6	1.0	4.9	0.0
151.9	966.2	280205.3	-35.4	120242.9	1.0	4.9	0.0
152.9	984.7	279629.5	-36.9	12103 0.3	1.0	4.9	0.0
153.9	1003.9	279022.4	-38.3	121817.6	1.0	4.9	0.0
154.9	1023.6	278384.0	-39.7	122604.9	1.0	4.9	0.0
155.9	1043.9	277714.2	-41.C	123392.2	1.0	4.9	0.0
156.9	1064.7	277013.1	-42.3	124179.5	1.0	4.9	0.0
157.9	1086.1	276280.6	-43.5	124966.8	1.0	4.9	0.0
158.9	1107.9	275516.9	-44.7	125754.2	1.0	4.9	0.0
159.9	1130.2	274721.7	-45.8	126541.5	1.0	4.9	0.0
160.9	1152.8	273895.3	-46.9	127328.8	1.0	4.9	0.0
161.9	1175.9	273037.5	-48.0	128116.1	1.0	4.9	0.0
162.9	1199.4	272148.3	-49.0	128903.4	1.0	4.9	0.0
163.9	1223.2	271227.8	-49.9	129690.7	1.0	4.9	0.0
	1247.4	270276.0	-50.9	130478.1	1.0	4.9	0.0
164.9	1271.9	269292.7	-51.8	131265.4	1.0	4.9	0.0
165.9		268278.2	-52.6	132052.7	1.0	4.9	0.0
166.9	1296.6		-53.4	132840.0	1.0	4.9	0.0
167.9	1321.7	267232.2	-54.2	133627.3	1.0	4.9	0.0
168.9	1347.0	266154.9	-55.0	134414.6	1.0	4.9	0.0
169.9	1372.6	265046.3	-55.7	135202.0	1.0	4.9	0.0
170.9	1398.4	263906.2		135989.3	1.0	4.9	0.0
171.9	1424.5	262734.8	-56-4	136776.6	1.0	4.9	0.0
172.9	1450.7	261532.0	-57.1	137563.9	1.0	4.9	0.0
173.9	1477.2	260297.8	-57.8		1.0	4.9	0.0
174.9	1503.8	259032.3	-58.4	138351.2	1.0	4.9	0.0
175.9	1530-7	257735.3	-59.0	139138.5		4.9	0.0
176.9	1557.7	256407.0	-59.6	139925.8	1.0	4.9	0.0
177.9	1584.8	255047.3	-60.2	140713.1	1.0	4.9	0.0
178.9	1612.2	253656.1	-60.8	141500.5	1.0		
179.9	1639.6	252233.6	-61.3	142287.8	1.0	4.9	0.0 0.0
180.9	1667.3	250779.6	-61.8	143075.1	1.0	4.9	
181.9	1695.0	249294.3	-62.3	143862.4	1.0	4.9	0.0
182.9	1722.9	247777.5	-62.8	144649.7	1.0	4.9	0.0
183.9	1750.9	246229.3	-63.3	145437.0	1.0	4.9	0.0
184.9	1779.0	244649.7	-63.7	146224.3	1.0	4.9	9.0
185.9	1807.3	243038.6	-64.2	147011.6	1.0	4.9	0.0
186.9	1835.6	241396.1	-64.6	147798.9	1.0	4.9	0.0
187.9	1864.1	239722.2	-65.0	148586.2	1.0	4.9	0.0
188.9	1892.6	238016.8	-65.4	149373.5	1.0	4.9	0.0
189.9	1921.3	236280.0	-65.8	150160.8	1.0	4.9	0.0
190.9	1950.0	234511.7	-66.2	150948.1	1.0	4.9	0.0
191.9	1978.8	232712.0	-66.6	151735.4	1.0	4.9	0.0
192.9	2007.7	230880.8	-66.9	152522.7	1.0	4.9	0.0
193.9	2036.7	229018.1	-67.3	153310.0	1.0	4.9	0.0
194.9	2065.8	227124.0	-67.6	154097.3	1.0	4.9	0.0
195.9	2094.9	225198.4	-67.9	154884.6	1.0	4.9	0.0
196.9	2124-1	223241.3	-68.2	155671.8	1.0	4.9	0.0
197.9	2153.4	221252.7	-68.6	156459.1	1.0	4.9	0.0
198.9	2182.8	219232-6	-68.9	157246.4	1.0	4.9	0.0
199.9	2212.2	217181.0	-69.2	158033.7	1.0	4.9	0.0
		_,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	11				
			TT				

200.9	2241.6	215097.9	-69.4	158821.0	1.0	4.9	0.0
201.9	2271.2	212983.3	-69.7	159608.2	1.0	4.9	0.0
		210837.2	-70.0	160395.5	1.0	4.9	0.0
202.9	2300.8			161182.7	1.0	4.9	0.0
203.9	2330.4	208659.6	-70.3			4.9	0.0
204.9	2360.1	206450.4	-70.5 ·		1.0		
205.9	2389.8	204209.8	-70.8	162757.2	1.0	4.9	0.0
206.9	2419.6	201937.5	-71.0	163544.5	1.0	4.9	0.0
	2449.5	199633.8	-71.3	164331.7	1.0	4.9	0.0
207.9			-71.5	165118.9	1.0	4.9	0.0
208.9	2479-4	197298.5				4.9	0.0
209.9	2509.3	194931.6	-71.7	165906.1	1.0		
210.9	2539.3	192533.2	-71.9	166693.3	1.0	4.9	0.0
211.9	2569.3	190103.3	-72.2	167480.5	1.0	4.9	0.0
212.9	2599.4	187641-8	-72.4	168267.7	1.0	4.9	0.0
	2629.5	185148.7	-72.6	169054.9	1.0	4.9	0.0
213.9			-72.8	169842.0	1.0	4.9	0.0
214.9	2659-6	182624-0				4.9	0.0
215.9	2689.8	180067.8	-73.0	170629.2	1.0		
216.9	2720.0	177480.0	-73.2	171416.3	1.0	4.9	0.0
217.9	2750.2	174860.7	-73.4	172203.4	1.0	4.9	0.0
218.9	2780.4	172209.7	-73.6	172990.5	1.0	4.9	0.0
		169527.2	-73.7	173777.6	1.0	4.9	0.0
219.9	2810.7			174564.6	1.0	4.9	0.0
220.9	2841.1	166813.2	-73.9				0.0
221.9	2871.4	164067.5	-74.1	175351.6	1.0	4.9	
222.9	2901.8	161290.3	-74.3	176138.6	1.0	4.9	0.0
223.9	2932.1	158481.5	-74.4	176925.6	1.0	4.9	0.0
	2962.5	155641.1	-74.6	177712.5	1.0	4.9	0.0
224.9		152769-2	-74.8	178499.3	1.0	4.9	0.0
225.9	2993.0			179286.2	1.0	4.9	0.0
226.9	3023.4	149865.8	-74.9				0.0
227.9	3053.8	146930.8	-75.1	180072.9	1.0	4.9	
228.9	3084.2	143964.4	-75.2	180859.7	1.0	4.9	0.0
229.9	3114.7	140966.4	-75.4	181646.3	1.0	4.9	0.0
230.9	3145.1	137937.0	-75.5	182432.9	1.0	4.9	0.1
			-75.7	183219.4	1.0	4.9	0.1
231.9	3175.5	134876.1			1.0	4.9	0.1
232.9	3205.8	131783.9	-75.8	184005.8			0.1
233.9	3236.2	128660-4	-75.9	184792.1	1.0	4.9	
234.9	3266.4	125505.5	-76.1	185578.2	1.0	4.9	0.1
235.9	3296.7	122319.5	-76.2	186364.2	1.0	4.9	0.1
236.9	3326.8	119102.4	-76.3	187150.1	1.0	4.9	0.1
		115854.2	-76.5	187935.7	1.0	4.9	0.1
237.9	3356.8				1.0	4.9	0.2
238.9	3386.7	112575.2	-76.6	188721.2		4.9	0.2
239.9	3416.5	109265.4	-76.7	189506.3	0.9		
240.9	3446.0	105925.1	-76.8	190291.2	0.9	4.9	0.2
241.9	3475.4	102554.4	-77.0	191075.7	0.9	5.0	0.3
242.9	3504.4	99153.8	-77.1	191859.7	0.9	5.0	0.3
	3533.0	95723.4	-77.2	192643.3	0.9	5.0	0.4
243.9		92263.7	-77.3	193426.3	0.9	5.0	0.5
244.9	3561.2				0.9	5.0	0.6
245.9	3588.8	88775.3	-77.4	194208.6			0.7
246.9	3615.8	85258.7	-77.5	194990.1	0.9	5.0	
247.9	3641.9	81714.7	-77.6	195770. 5	8.0	5.0	0.9
248.9	3666.9	78144.3	-77.7	196549.8	0.8	5.0	1.0
249.9	3690.8	74548.4	-77.8	197327.6	0.8	5.0	1.2
		70928.6	-78.0	198103.7	0.7	5.0	1.5
250.9	3713.3			198877.8	0.6	5.0	1.8
251.9	3733.9	67286-2	-78.1			5.0	2.2
252.9	3752.5	63623.2	-78.2	199649.6	0.6		
253.9	3768.6	59941.8	-78.3	200418-4	0.5	5.0	2.6
254.9	3781.6	56244.9	-78.4	201183.9	0.4	5.0	3.1
255.9	3790.9	52535.7	-78.4	201945.2	0.3	5.0	3.7
		48818.0	-78.5	202701.8	0.2	5.0	4.5
256.9	3796.0			203452.6	0.2	5.0	5.3
257.9	3795.9	45096.6	-78.6			5.0	6.4
258.9	3789.7	41377.0	-78.7	204196.7	0.4	3.0	U 4 4

259.9	3776.4	37665.6	-78.8	204932.7	0.6	5.0	7.6
260.9	3755.2	33969.9	-78.9	205659.3	0.8	5.0	8.8
261.9	3726.2	30297.6	-79.0	206375.0	1.0	5.0	10.0
262.9	3689.2	26656.6	-79.1	207078.5	1.3	5.0	11.3
263.9	3643.7	23054.8	-79.2	207768.2	1.6	5.0	12.6
264.9	3589.5	19500.9	-79.3	208442.7	1.8	5.0	14.0
265.9	3526.5	16003.4	-79.4	209100.5	2.1	5.0	15.4
266.9	3454.7	12571.2	-79.5	209740.0	2.4	5.0	16.7
267.9	3374.2	9212.8	-79.6	210359.9	2.6	5.0	18.1
268.9	.3285.6	5936.5	-79.7	210958.8	2.9	5.0	19.3
269.9	3189.3	2750.2	-79.8	211535.5	3.1	5.0	20.4
270.8	3097.8	-0.0	-79.9	212028.4	3.3	5.0	21.4

INITIAL CATA

Z(0) = 0. AL= 1.4834E 00 V(0) = 10.0000E+02 ISP(0) = 2.2623E 02 K(T) = 6.4800E-01 D(B) = 8.3333E-02 D(M) = 2.5000E-01 M(B) = 1.5540E-01 M(0) = 8.7743E-01M(P) = 5.2278E-01 MR = 2.7514E-01

			PATH				
TIME	VEL.	ALT.	ANGLE	RANGE	ACCEL.	WGT.	DRAG
1 2 (16.	100						
(SEC)	(FT/SEC)	(FT)	(DEG)	(FT)	(G)	(LBS)	(LBS)
	_	_		•	47.0	00 0	0.0
0.	0.1	0.	85.0	0.	67.0	28.2	0.0
0-1	219.0	10.9	84.8	1.0	69.1	27.3	1.0
0.2	445.0	43.9	84.8	4.0	71.4	26.5	4.1
0.3	678.2	99.7	84.7	9.1	73.7	25.6	9.5
0.4	919-0	179.2	84.7	16.5	76.0	24.7	17.5
0.5	1167-4	283.0	84.7			23.8	28.1
0.6	1423.8	411.9	84.7			22.9	
0.7	1688.3	566.8	84.7			22.0	58.3
0.8	1961.2	748.4	84.7		86.1	21.1	78.3
0.9	2242.6	957.6	84.6	89.2		20.3	101.7
1.0	2532.6	1195.2	84.6	111.5		19.4	128.9
1.1	2831.6	1462.2	84.6	136.6	94.3	18.5	159.8
1.2	3139.7	1759.4	84.6	164.6		17.6	194.8
1.3	3457.1	2087.7	84.6	195.5	100.1	16.7	233.8
1.4	3784.0	2448.1	84.6	229.5	103.1	15.8	277.2
1.5	4120.5	2841.5	84.6	266.6	106.1	14.9	324.8
1.6	4467.0	3268.9	84.6	306.9	109.3	14.1	376.9
1.7	4823.7	3731.2	84.6	350.6	112.5	13.2	433.5
1.8	5190.9	4229.7	84.6	397.7	115.8	12.3	494.5
1.9	5568.9	4765-2	84.6	448.4	119.2	11.4	560.0
1.9	5569.1	4765.4	84.6	448.4	119.2	11.4	560.0
1.9	5569.1	4765.4	84.6	448.4	10.6	5.0	48.2
2.9	5265.9	10152.6	84.6	959.8	8.3	5.0	36.8
3.9	5024.9	15270-4	84.5	1448.5	6.7	5.0	28.6
4.9	4829.3	20171.6	84.5	1919.6	5.5	5.0	22.6
5.9	4667.6	24895.6	84.5	2376.7	4.6	5.0	18.0
6.9	4532.0	29471.8	84.4	2822.6	3.9	5.0	14.4
7.9	4416.8	33923.3	84.4	3259.4	3.3	5.0	11.6
8.9	4317.8	38268.2	84.3	3688. 8	2.8	5.0	9.2
9.9	4233.1	42521.6	84.3	4112.4	2.4	5.0	7.3
10.9	4159.4	46696-1	84.2	4531.3		5.0	5.8
11.9	4094.2	50801.3	84.2	4946.4		5.0	4.6
12.9	4035.7	54844.9	84.2	5358.6	1.7	5.0	3.7
13.9	3982.3	58832.5	84.1	5768.2	1.6	5.0	3.0
14.9	3933.1	62768.8	84.1	6175.9	1.5	5.0.	2.4
15.9	3887.1	66657-5	84.0	6582.0	1.4	5.0	2.0
16.9	3843.7	70501-5	84.0	6986.7	1.3	5.0	1.6
17.9	3802.5	74303.1	83.9	7390.4	1.3	5.0	1.3
18.9	3763.0	78064.2	83.9	7793.1	1.2	5.0	1.1
19.9	3724.9	81786-4	83.8	8195.0	1.2	5.0	0.9
	3687.9	85471.0	83.8	8596.4	1.1	5.0	0.7
20.9	1	89118.9	83.7	8997.2	1.1	5.0	0.6
21.9	3651.9	92731.1	83.6	9397.6	1.1	5.0	0.5
22.9	3616.7	7413101	0340	/3/100			

23.9 3582.1 96308.1 83.6 9797.7 1.1 24.9 3548.1 99850.7 83.5 10197.4 1.1 25.9 3514.4 103359.3 83.5 10596.9 1.0 26.9 3481.1 106834.1 83.4 10996.2 1.0 27.9 3448.1 110275.6 83.4 11395.4 1.0 28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	5.0 5.0 4.9 4.9 4.9 4.9	0.4 0.3 0.2 0.2 0.2 0.1 0.1
24.9 3548.1 99850.7 83.5 10197.4 1.1 25.9 3514.4 103359.3 83.5 10596.9 1.0 26.9 3481.1 106834.1 83.4 10996.2 1.0 27.9 3448.1 110275.6 83.4 11395.4 1.0 28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	5.0 5.0 4.9 4.9 4.9 4.9 4.9	0.3 0.2 0.2 0.2 0.1 0.1 0.1
25.9 3514.4 103359.3 83.5 10596.9 1.0 26.9 3481.1 106834.1 83.4 10996.2 1.0 27.9 3448.1 110275.6 83.4 11395.4 1.0 28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	5.0 4.9 4.9 4.9 4.9 4.9	0.2 0.2 0.2 0.1 0.1 0.1
26.9 3481.1 106834.1 83.4 10996.2 1.0 27.9 3448.1 110275.6 83.4 11395.4 1.0 28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	# 6 # 6 # 6 # 6 # 6	0.2 0.2 0.1 0.1 0.1
27.9 3448.1 110275.6 83.4 11395.4 1.0 28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	# - 6 # - 6 # - 6 # - 6 # - 6	0.2 0.1 0.1 0.1
28.9 3415.3 113684.0 83.3 11794.3 1.0 29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	# 9 # 9 # 9 # 9	0.1 0.1 0.1
29.9 3382.6 117059.4 83.2 12193.2 1.0 30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	# . 9 # . 9 # . 9 # . 9	0.1 0.1 0.1
30.9 3350.2 120402.1 83.2 12591.9 1.0 31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	4.9 4.9 4.9	0.1
31.9 3317.9 123712.3 83.1 12990.6 1.0 32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	4.9 4.9 4.9	0.1
32.9 3285.7 126989.9 83.0 13389.1 1.0 33.9 3253.7 130235.3 83.0 13787.6 1.0	4.9 4.9	
33.9 3253.7 130235.3 83.0 13787.6 1.0	4.9	
		0.1
34.9 3221.7 133448.3 82.9 14186.0 1.0		0.1
35.9 3189.8 136629.2 82.8 14584.4 1.0	4.9	0.1
36.9 3157.9 139777.9 82.8 14982.8 1.0	4.9	0.0
37.9 3126.1 142894.6 82.7 15381.1 1.0	4.9	0.0
38.9 3094.4 145979.3 82.6 15779.3 1.0	4.9	0.0
39.9 3062.7 149032.0 82.5 16177.6 1.0	4.9	0.0
40.9 3031.1 152052.8 82.5 16575.8 1.0	4.9	0.0
41.9 2999.5 155041.7 82.4 16973.9 1.0	4.9	0.0
42.9 2967.9 157998.7 82.3 17372.1 1.0	4.9	0.0
43.9 2936.4 160923.9 82.2 17770.2 1.0	4.9	0.0
44.9 2904.9 163817.3 82.1 18168.4 1.0	4.9	0.0
45.9 2873.4 166678.9 82.0 18566.5 1.0	4.9	0.0
46.9 2842.0 169508.7 81.9 18964.6 1.0	4.9	0.0
47.9 2810.6 172306.8 81.9 19362.6 1.0	4.9	0.0
48.9 2779.2 175073.2 81.8 19760.7 1.0	4.9	0.0
49.9 2747.8 177807.9 81.7 20158.8 1.0	4.9	0.0
50.9 2716.4 180510.8 81.6 20556.8 1.0	4.9	0.0
51.9 2685.1 183182.1 81.5 20954.9 1.0	4.9	0.0
52.9 2653.8 185821.8 81.4 21352.9 1.0	4.9	0.0
53.9 2622.5 188429.7 81.3 21750.9 1.0	4.9	0.0
54.9 2591.3 191006.0 81.2 22148.9 1.0	4.9	0.0
55.9 2560.0 193550.7 81.1 22547.0 1.0	4.9	0.0
56.9 2528.8 196063.8 80.9 22945.0 1.0 57.9 2497.6 198545.3 80.8 23343.0 1.0	4.9	0.0
	4.9	0.0
	4.9	0.0
	4.9	0.0
	4.9	0.0
	4.9	0.0
	4.9	0.0
63.9 2310.8 212771.0 80.1 25730.9 1.0 64.9 2279.7 215031.5 79.9 26128.9 1.0	4.9	0.0
65.9 2248.7 217260.4 79.8 26526.9 1.0	4.9	0.0
66.9 2217.7 219457.9 79.7 26924.9 1.0	4.9	0.0
67.9 2186.7 221623.8 79.5 27322.8 1.0	4.9	0.0
68.9 2155.7 223758.2 79.4 27720.8 1.0	4.9	0.0
69.9 2124.8 225861.1 79.2 28118.8 1.0	4.9	0.0
70.9 2093.8 227932.5 79.0 28516.8 1.0	4.9	0.0
71.9 2062.9 229972.4 78.9 28914.7 1.0	4.9	0.0
72.9 2032.1 231980.9 78.7 29312.7 1.0	4.9	0.0
73.9 2001.2 233957.9 78.5 29710.7 1.0	4.9	0.0
74.9 1970.4 235903.4 78.3 30108.6 1.0	4.9	0.0
75.9 1939.6 237817.4 78.2 30506.6 1.0	4.9	0.0
76.9 1908.8 239700.0 78.0 30904.6 1.0	4.9	0.0
77.9 1878.1 241551.1 77.8 31302.5 1.0	4.9	0.0
78.9 1847.3 243370.8 77.6 31700.5 1.0	4.9	0.0
79.9 1816.7 245159.0 77.3 32098.5 1.0	4.9	0.0
80.9 1786.0 246915.9 77.1 32496.4 1.0	4.9	0.0
81.9 1755.4 248641.2 76.9 32894.4 1.0	4.9	0.0

82.9	1724.8	250335.2	76.7	33292.4	1.0	4.9	0.0
83.9	1694.2	251997.8	76.4	33690.3	1.0	4.9	0.0
84.9	1663.7	253628.9	76.2	34088.3	1.0	4.9	0.0
85.9	1633.3	255228.6	75.9	34486.3	1.0	4.9	0.0
86.9	1602.8	256796.9	75.6	34884.2	1.0	4.9	0.0
87.9	1572.4	258333.9	75.3	35282.2	1.0	4.9	0.0
88.9	1542.1	259839.4	75.0	35680.1	1.0	4.9	0.0
89.9	1511.8	261313.6	74.7	36078.1	1.0	4.9	0.0
90.9	1481.5	262756.3	74.4	36476.1	1.0	4.9	0.0
91.9	1451.3	264167.7	74.1	36874.0	1.0	4.9	0.0
92.9	1421.2	265547.7	73.7	37272.0	1.0	4.9	0.0
93.9	1391.1	266896.4	73.4	37670.0	1.0	4.9	0.0
94.9	1361.1	268213.6	73.0	38067.9	1.0	4.9	0.0
95.9	1331.1	269499.5	72.6	38465.9	1.0	4.9	0.0
96.9	1301.2	270754.1	72.2	38863.8	1.0	4.9	0.0
97.9	1271.4	271977.3	71.8	39261.8	1.0	4.9	0.0
98.9	1241.7	273169.1	71.3	39659.8	1.0	4.9	0.0
99.9	1212.0	274329.6	70.8	40057.7	1.0	4.9	0.0
100.9	1182.5	275458.8	70.3	40455.7	1.0	4.9	0.0
101.9	1153.0	276556.6	69.8	40853.6	1.0	4.9	0.0
102.9	1123.6	277623.1	69.3	41251.6	1.0	4.9	0.0
103.9	1094.4	278658.2	68.7	41649.5	1.0	4.9	0.0
104.9	1065.3	279662.0	68.1	42047.5	1.0	4.9	0.0
105.9	1036.3	280634.5	67.4	42445.5	1.0	4.9	0.0
106.9	1007-4	281575.6	66.7	42843.4	1.0	4.9	0.0
107.9	978 .7	282485.5	66.0	43241.4	1.0	4.9	0.0 0.0
108.9	950.2	283364.0	65.2	43639.3	1.0	4.9 4.9	0.0
109.9	921.9	284211.2	64 - 4	44037.3	1.0	4.9	0.0
110.9	893.7	285027.1	63.6	44435.3	1.0 1.0	4.9	0.0
111.9	865.8	285811.6	62.6	44833.2	1.0	4.9	0.0
112.9	838.1	286564.9	61.7	45231.2 45629.1	1.0	4.9	0.0
113.9	810.7	287286.8	60.6	46027.1	1.0	4.9	0.0
114.9	783.6	287977.5	59.5	46425.1	1.0	4.9	0.0
115.9	756.8	288636.8	58.3	46823.0	1.0	4.9	0.0
116.9	730.3	289264.9	57.0 55.6	47221.0	1.0	4.9	0.0
117.9	704.3	289861.6 290427.0	54.1	47618.9	1.0	4.9	0.0
118.9	678.7	290961.2	52.5	48016.9	1.0	4.9	0.0
119.9	653.6 629.1	291464.0	50.8	48414.9	1.0	4.9	0.0
120.9	605.2	291935.6	48.9	48812.8	1.0	4.9	0.0
121.9	582.0	292375.8	46.9	49210.8	1.0	4.9	0.0
122.9 123.9	559.5	292784.8	44.7	49608.7	1.0	4.9	0.0
123.9	538.0	293162.5	42.3	50006.7	1.0	4.9	0.0
125.9	517.5	293508.9	39.7	50404.6	1.0	4.9	0.0
126.9	498.0	293824.0	37.0	50802.6	1.0	4.9	0.0
127.9	479.9	294107.8	34.0	51200.6	1.0	4.9	0.0
128.9	463.1	294360.4	30.8	51598.5	1.0	4.9	0.0
129.9	447.9	294581.6	27.3	51996.5	1.0	4.9	0.0
130.9	434.5	294771.6	23.7	52394.4	1.0	4.9	0.0
131.9	422.9	294930.3	19.8	52792.4	1.0	4.9	0.0
132.9	413.4	295057.7	15.7	53190.4	1.0	4.9	0.0
133.9	406.0	295153.8	11.4	53588.3	1.0	4.9	0.0
134.9	401.0	295218.6	7.0	53986.3	1.0	4.9	0.0
135.9	398.4	295252.2	2.6	54384.2	1.0	4.9	0.0
136.9	398.2	295254-4	-1.9	54782.2	1.0	4.9	0.0
137.9	400.5	295225.4	-6.4	55180.1	1.0	4.9	0.0
138.9	405.1	295165.1	-10.8	55578.1	1.0	4.9	0.0
139.9	412.1	295073.5	-15.1	55976.1	1.0	4.9	0.0
140.9	421.4	294950.7	-19.2	56374.0	1.0	4.9	0.0
, , , , ,							

141.9	432.7	294796.5	-23.1	56772.0	1.0	4.9	0.0
142.9	445.9	294611.1	-26.8	57169.9	1.0	4.9	0.0
143.9	460.8	294394.4	-30.3	57567.9	1.0	4.9	0.0
143.7	477.4	294146.4	-33.5	57965.9	1.0	4.9	0.0
			-36.5	58363.8	1.0	4.9	0.0
145.9	495.3	293867.1				4.9	0.0
146.9	514.6	293556.6	-39-3	58761.8	1.0		
147.9	535.0	293214.7	-41.9	59159.7	1.0	4.9	0.0
148.9	556.3	292841.6	-44.3	59557.7	1.0	4.9	0.0
149.9	578.6	292437.2	-46.5	59955.7	1.0	4.9	0.0
150.9	601.7	292001.4	-48.6	60353.6	1.0	4.9	0.0
151.9	625 .6	291534.4	-50.5	60751.6	1.0	4.9	0.0
152.9	650.0	291036.1	-52.2	61149.5	1.0	4.9	0.0
153.9	675.0	290506.5	-53.9	61547.5	1.0	4.9	0.0
154.9	700.6	289945.6	-55.4	61945.4	1.0	4.9	0.0
155.9	726.5	289353.4	-56.8	62343.4	1.0	4.9	0.0
156.9	752.9	288729.9	-58.1	62741.4	1.0	4.9	0.0
157.9	779.7	288075.1	-59.3	63139.3	1.0	4.5	0.0
158.9	806.7	287389.0	-60.4	63537.3	1.0	4.9	0.0
		286671.6	-61.5	63935.2	1.0	49	0.0
159.9	834.1			64333.2	1.0	4.9	0.0
160.9	861.8	285922.9	-62.5			4.9	0.0
161.9	889.6	285142.9	-63.4	64731.2	1.0		
162.9	917.8	284331.6	-64.3	65129.1	1.0	4.9	0.0
163.9	946.1	283488.9	-65.1	65527.1	1.0	4.9	0.0
164.9	974.6	282615.0	-65.9	65925.0	1.0	4.9	0.0
165.9	1003.2	281709.7	-66.6	66323.0	1.0	4.9	0.0
166.9	1032.1	280773.1	-67.3	66720.9	1.0	4.9	0.0
167.9	1061.0	279805.1	-68.0	67118.9	1.0	4.9	0.0
168.9	1090.2	278805.9	-68.6	67516.9	1.0	4.9	0.0
169.9	1119.4	277775.3	-69.2	67914.8	1.0	4.9	0.0
170.9	1148.7	276713.4	-69.7	68312.8	1.0	4.9	0.0
171.9	1178.2	275620.1	-70.3	68710.7	1.0	4.9	0.0
172.9	1207.7	274495.5	-70.8	69108.7	1.0	4.9	0.0
173.9	1237.4	273339.6	-71.2	69506.7	1.0	4.9	0.0
	1267.1	272152.3	-71.7	69904.6	1.0	4.9	0.0
174.9			-72.1	70302.6	1.0	4.9	0.0
175.9	1296.9	270933-6		70700.5	1.0	4.9	0.0
176.9	1326.8	269683.7	-72.5			4.9	0.0
177.9	1356.7	268402.3	-72.9	71098.5	1.0		
178.9	1386.7	267089.6	-73.3	71496.4	1.0	4.9	0.0
179.9	1416.8	265745.5	-73-7	71894.4	1.0	4.9	0.0
180.9	1446.9	264370.1	-74.0	72292.4	1.0	4.9	0.0
181.9	1477.1	262963.2	-74.4	72690.3	1.0	4.9	0.0
182.9	1507.4	261525.1	-74.7	73088. 3	1.0	4.9	0.0
183.9	1537.7	260055.5	-75.0	73486.2	1.0	4.9	0.0
184.9	1568.0	258554.5	-75.3	73884.2	1.0	4.9	0.0
185.9	1598.4	257022.2	-75.6	74282.1	1.0	4.9	0.0
186.9	1628.8	255458.4	~75.9	74680.1	1.0	4.9	0.0
187.9	1659.3	253863.3	-76.1	75078.0	1.0	4.9	0.0
188.9	1689.8	252236.7	-76.4	75476.0	1.0	4.9	0.0
189.9	1720.3	250578.8	-76.6	75874.0	1.0	4.9	0.0
	1750.9	248889.4	-76.9	76271.9	1.0	4.9	0.0
190.9		247168.6	-77.1	76669.9	1.0	4.9	0.0
191.9	1781.5		-77.3	77067.8	1.0	4.9	0.0
192.9	1812.2	245416.4		77465.8	1.0	4.9	0.0
193.9	1842.8	243632.8	-77.5 -77.7	77863.7	1.0	4.9	0.0
194.9	1873.5	241817.7	-77.7			4.9	0.0
195.9	1904.3	239971.2	-77.9	78261.7	1-0		
196.9	1935.0	238093.2	-78.1	78659.6	1.0	4.9	0.0
197.9	1965.8	236183.8	-78.3	79057.6	1.0	4.9	0.0
198.9	1996.6	234243.0	-78.5	79455.5	1.0	4.9	0.0
199.9	2027.5	232270.7	-78.7	79853.5	1-0	4.9	0.0
			17				

000 0	2050 7	230266.9	-78.9	80251.4	1.0	4.9	0.0
200.9	2058.3 2089.2	228231.6	-79.0	80649.4	1.5	4.9	0.0
201.9		226164.9	-79.2	81047.3	1.0	4.9	0.0
202.9	2120.1 2151.1	224066.7	-79.3	81445.2	1.0	4.9	0.0
203.9	2182.0	221937.0	-79.5	81843.2	1.0	4.9	0.0
204.9	2213.0	219775.8	-79.6	82241.1	1.0	4.9	0.0
205.9 206.9	2244.0	217583.2	-79.8	82639.1	1.0	4.9	0.0
207.9	2275.0	215359.0	-79.9	83037.0	1.0	4.9	0.0
201.7	2306.0	213103.3	-80.1	83434.9	1.0	4.9	0.0
209.9	2337.1	210816.1	-80.2	83832.9	1.0	4.9	0.0
210.9	2368.2	208497.4	-80.3	84230.8	1.0	4.9	0.0
211.9	2399.2	206147.1	-80.5	84628.7	1.0	4.9	0.0
212.9	2430.3	203765.4	-80.6	85026.7	1.0	4.9	0.0
213.9	2461.4	201352.1	-80.7	85424.6	1.0	4.9	0.0
214.9	2492.6	198907.2	-80.8	85822.5	1.0	4.9	0.0
215.9	2523.7	196430.8	-80.9	86220.4	1.0	4.9	0.0
216.9	2554.9	193922.9	81.0	86618.3	1.0	4.9	0.0
217.9	2586.1	191383.4	-81.1	87016.2	1.0	4.9	0.0
218.9	2617.2	188812.4	-81.3	87414.1	1.0	4.9	0.0 0.0
219.9	2648.4	186209.8	-81-4	87812.0	1.0	4.9	0.0
220.9	2679.7	183575.6	-81.5	88209.9	1.0	4.9 4.9	0.0
221.9	2710.9	180909-9	-81.6	88607.8	1.0 1.0	4.9	0.0
222.9	2742.1	178212.6	-81.7	89005.6	1.0	4.9	0.0
223.9	2773.3	175483.7	-81.8	89403.5	1.0	4.9	0.0
224.9	2804.6	172723.3	-81.8	89801.3 90199.2	1.0	4.9	0.0
225.9	2835.8	169931-2	-81.9	90597.0	1.0	4.9	0.0
226.9	2867.1	167107.7	-82.0	90994.8	1.0	4.9	0.0
227.9	2898.4	164252.5	-82.1 -82.2	91392.6	1.0	4.9	0.0
228.9	2929.6	161365.8	-82·2 -82·3	91790.4	1.0	4.9	0.0
229.9	2960.9	158447.5 155497.7	-82·4	92188.2	1.0	4.9	0.0
230.9	2992.2	152516.3	-82.4	92585.9	1.0	4.9	0.0
231.9	3023.4	149503.4	-82.5	92983.6	1.0	4.9	0.0
232.9	3054.7 3085.9	146459.0	-82.6	93381.3	1.0	4.9	0.0
233.9	3117.1	143383.1	-82.7	93779.0	1.0	4.9	0.0
234.9	3148.3	140275.7	-82.7	94176.6	1.0	4.9	0.0
235.9 236.9	3179.5	137136.9	-82.8	94574.2	1.0	4.9	0.1
237.9	3210.6	133966.6	-82.9	94971.7	1.0	4.9	0.1
238.9	3241.7	130765-1	-83.0	95369.2	1.0	4.9	0.1
239.9	3272.7	127532.2	-83.0	95766.7	1.0	4.9	0.1
240.9	3303.7	124268.1	-83.1	96164.0	1.0	4.9	0.1
241.9	3334.6	120972.8	-83.2	96561.3	1.0	4.9	0.1
242.9	3365.3	117646.5	-83.2	96958.5	1.0	4.9	0.1
243.9	3395.9	114289.3	-83.3	97355.6	1.0	4.9	0.2
244.9	3426.4	110901.2	-83.3	97752.6	1.0	4.9	0.2
245.9	3456.7	107482.6	-83.4	98149.4	0.9	4.9	0.2 0.3
246.9	3486.7	104033.6	-83.5	98546.1	0.9	5.0	0.3
247.9	3516.5	100554.5	-83.5	98942.5	0.9	5.0	0.4
248.9	3545.9	97045-6	-83.6	99338.7	0.9 0.9	5.0 5.0	0.5
249.9	3574.8	93507.3	-83.6	99734.7		5.0	0.6
250.9	3603.2	89940.2	-83.7	100130.3	0.9 0.9	5.0	0.7
251.9	3630.9	86344.7	-83.8	100525.5	0.8	5.0	0.8
252.9	3657.8	82721.8	-83.8	100920.2 101314.4	0.8	5.0	1.0
253.9	3683.6	79072.2	-83.9	101707.8	0.8	5.0	1.2
254.9	3708.3	75397.2	-83.9 -84.0	102100.5	0.7	5.0	1.5
255.9	3731.5	71697.9	-84.0	102492.1	0.6	5.0	1.8
256.9	3753.0	67976.1	-84.1	102882.6	. 0.6	5.0	2.1
257.9	3772.3	64233.5 60472.6	-84.1	103271.6	0.5	5.0	2.6
258.9	3789.2	0412.0	10	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			

REFERENCES

- (1) Parker, M. J., "HASP, A Family of Navy Meteorological Rockets," NOLTR 62-16, Feb 1962 (Unclassified)
- (2) Holcombe, O. J., Radke, H. H., "The 3.0 Mk32 Mod 0 Rocket Motor Manufacture, Qualification and Documentation," B. F. Goodrich, Inc., Mar 1962 (Unclassified)
- (3) Eimer, Manfred, "Summary of Loki Wind-Tunnel Tests," JPL Report No. 20-296, Mar 1956 (Confidential)
- (4) Murphy, C. H., "Criteria for the Generalized Dynamic Stability of a Rolling Missile," Journal of the Aeronautical Sciences, Vol. 24, No. 10, pp. 773-774, May 1957
- (5) Nicolaides, J. D., "Two Non-Linear Problems in the Flight Dynamics of Modern Ballistic Missiles," Institute of Aeronautical Sciences Report No. 59-17, Jan 1959
- (6) Charters, A. C., "The Linearized Equations of Motion Underlying the Dynamic Stability of Aircraft, Spinning Projectiles, and Symmetrical Missiles," NACA TN3350, 1955 (Unclassified)
- (7) Mantle, P. J., "Tricyclic and Epicyclic Analysis as Applied to Aeroballistic Range Data," Canadian Armament Research and Development Establishment, Memorandum AB-64, Aug 1960 (Unclassified)
- (8) Arthur, P. D., Barber, K. F., "Derivation and Application of the Dynamic Stability Criteria for Spinning Projectiles and Symmetric Missiles," Marquardt Corporation Report S-254, Apr 1962
- (9) Martin, J. C., "On Magnus Effects Caused by the Boundary Layer Displacement Thickness on Bodies of Revolution at Small Angles of Attack," Journal of Aeronautical Sciences, pp. 421-429, 1957
- (10) Thickstun, W. R., "Re-entry Heating Simulation," NAVORD 6791, Dec 1960 (Unclassified)

- (11) Grey, J., "Aerodynamic Design and Performance Study of the Iris Sounding Rocket," Greyrad Corporation Report No. ARC-11, Mar 1960 (Unclassified)
- (12) Harms, R. J., Schmidt, C. M., Hanawalt, A. J. and Schmitt, D. A., "A Manual for Determining Aerodynamic Heating of High-Speed Aircraft, Volume I," Bell Aircraft Corporation Report No. 7006-3352-001, Jun 1959

24.9	3669.6	98564.9	70.9	30760.4	1.1	5.0	0.4
25.9	3637.3	102014.8	70.7	31962.8	1.1	5.0	0.3
	3605.4	105430.8	70.5	33164.6	1.0	4.9	0.3
26.9		108813.4	70.4	34365.8	1.0	4.9	0.2
27.9	3573.8		70.2	35566.5	1.0	4.9	0.2
28.9	3542.4	112162.8			1.0	4.9	0.2
29.9	3511.4	115479-2	70.0	36766.8		4.9	0.1
30.9	3480.5	118762.7	59.8	37966.7	1.0		
31.9	3449.9	122013.6	69.7	39166.3	1.0	4.9	0.1
32.9	3419.4	125232.0	69.5	40365.7	1.0	4.9	0.1
33.9	3389.0	128418.0	69.3	41564.8	1.0	4.9	0.1
34.9	3358.8	131571.7	69.1	42763.7	1.0	4.9	0.1
35.9	3328.7	134693.1	68.9	43962.5	1.0	4.9	0.1
36.9	3298.7	137782.4	68.7	45161.1	1.0	4.9	0.1
		140839.6	68.5	46359.5	1.0	4.9	0.0
37.9	3268.8		68.3	47557.9	1.0	4.9	0.0
38.9	3239.0	143864.7		48756.1	1.0	4.9	0.0
39.9	3209.2	146857.9	68.1		1.0	4.9	0.0
40.9	3179.6	149819.1	67.9	49954.3		4.9	0.0
41.9	3150.1	152748.4	67.6	51152.3	1.0		
42.9	3120.6	155645.8	67.4	52350.3	1.0	4.9	0.0
43.9	3091.2	158511.3	67.2	53548.3	1.0	4.9	0.0
44.9	3061.9	161345.1	67.0	54746.1	1.0	4.9	0.0
45.9	3032.6	164147-0	66.7	55944.0	1.0	4.9	0.0
46.9	3003.4	166917.1	66.5	57141.8	1.0	4.9	0.0
		169655.5	66.3	58339.5	1.0	4.9	0.0
47.9	2974.3		66.0	59537.2	1.0	4.9	0.0
48.9	2945.3	172362.2		60734.9	1.0	4.9	0.0
49.9	2916.3	175037-1	65.8		1.0	4.9	0.0
50.9	2887.4	177680.3	65.5	61932.5		4.9	0.0
51.9	2858.6	180291-8	65.2	63130.1	1.0		
52.9	2829.9	182871.6	65.0	64327.7	1.0	4.9	0.0
53.9	2801.2	185419.8	64.7	65525. 3	1.0	4.9	0.0
54.9	2772.6	187936.3	64.4	66722.8	1.0	4.9	0.0
55.9	2744.1	190421.2	64.1	6792 0.3	1.0	4.9	0.0
56.9	2715.7	192874.4	63.8	69117.8	1.0	4.9	0.0
57.9	2687.4	195296.0	63.5	70315.3	1.0	4.9	0.0
	2659.1	197686.0	63.2	71512.8	1.0	4.9	0.0
58.9			62.9	7.27 10 . 2	1.0	4.9	0.0
59.9	2630.9	200044-4		73907.7	1.0	4.9	0.0
60.9	2602.8	202371.3	62.6	75105.1	1.0	4.9	0.0
61.9	2574.8	204666.5	62.3			4.9	0.0
62.9	2546.9	206930-2	62.0	76302.5	1.0		0.0
63.9	2519.1	209162.3	61.6	77499.9	1.0	4.9	
64.9	2491.4	211362-8	61.3	78697.4	1.0	4.9	0.0
65.9	2463.8	213531.8	60.9	79894.7	1.0	4.9	0.0
66.9	2436.3	215669.3	60.6	81092.1	1.0	4.9	0.0
67.9	2408.8	217775.2	60 - 2	82289.5	1.0	4.9	0.0
68.9	2381.5	219849-6	59.8	83486.9	1.0	4.9	0.0
	2354.4	221892.5	59.4	84684.3	1.0	4.9	0.0
69.9		223903.9	59.0	85881.6	1.0	4.9	0.0
70.9	2327.3		58.6	87079.0	1.0	4.9	0.0
71.9	2300.3	225883.8		88276.4	1.0	4.9	0.0
72.9	2273.5	227832-2	58.2		1.0	4.9	0.0
73.9	2246.8	229749.1	57.8	89473.7		4.9	0.0
74.9	2220.2	231634.5	57-4	90671.1	1.0		
75.9	2193.8	233488.5	56.9	91868.4	1.0	4.9	0.0
76.9	2167.5	235311.0	56.5	93065.8	1.0	4.9	0.0
77.9	2141.3	237102.0	56.0	94263.1	1.0	4.9	0.0
78.9	2115.3	238861.5	55.5	95460.5	1.0	4.9	0.0
79.9	2089.5	240589.6	55.0	96657.8	1.0	4.9	0.0
80.9	2063.8	242286.3	54.5	97855.1	1.0	4.9	0.0
		243951.5	54.0	99052.5	1.0	4.9	0.0
81.9	2038.2		53.5	100249.8	1.0	4.9	0.0
82.9	2012-9	245585.3	7 J G	10027700	, , ,	- 	

83.9	1987.7	247187.6	53.0	101447.1	1.0	4.9	0.0
84.9	1962.7	248758.5	52.4	102644.5	1.0	4.9	0.0
85.9	1937.9	250298.0	51.8	103841.8	1.0	4.9	0.0
86.9	1913.3	251806.1	51.3	105039.1	1.0	4.9	0.0
87.9	1888.9	253282.7	50.7	106236.5	1.0	4.9	0.0
88.9	1864.7	254728.0	50.1	107433.8	1.0	4.9	0.0
89.9	1840.8	256141.9	49.4	108631.1	1.0	4.9	0.0
90.9	1817.0	257524.3	48.8	109828.4	1.0	4.9	0.0
91.9	1793.5	258875.4	48.1	111025.7	1.0	4.9	0.0
92.9	1770.3	260195.0	47.4	112223.1	1.0	4.9	0.0
93.9	1747.3	261483.3	46.7	113420.4	1.0	4.9	0.0
			46.0	114617.7	1.0	4.9	
94.9	1724.6	262740.2					0.0
95.9	1702.1	263965.7	45.3	115815.0	1.0	4.9	0.0
96.9	1680.0	265159.9	44.5	117012.3	1.0	4.9	0.0
97.9	1658.1	266322.6	43.8	118209.7	1.0	4.9	0.0
98.9	1636.6	267454.0	43.0	119407.0	1.0	4.9	0.0
99.9	1615.4	268554.1	42.2	120604.3	1.0	4.9	0.0
100.9	1594.5	269622-8	41.3	121801.6	1.0	4.9	0.0
101.9	1573.9	270660.1	40.5	122998.9	1.0	4.9	0.0
102.9	1553.8	271666.0	39.6	124196.3	1.0	4.9	0.0
103.9	1534.0	272640.6	38.7	125393.6	1.0	4.9	0.0
104.9	1514.6	273583.9	37.8	126590.9	1.0	4.9	0.0
105.9	1495.6	274495.8	36.8	127788.2	1.0	4.9	0.0
106.9	1477.0	275376.4	35.8	128985.5	1.0	4.9	0.0
107.9	1458.9	276225.6	34.8	130182.8	1.0	4.9	0.0
108.9	1441.2	277043.5	33.8	131380.1	1.0	4.9	0.0
109.9	1424.0	277830.1	32.8	132577.5	1.0	4.9	0.0
110.9	1407.3	278585.3	31.7	133774.8	1.0	4.9	0.0
111.9	1391.1	279309.2	30.6	134972.1	1.0	4.9	0.0
112.9	1375.4	280001.7	29.5	136169.4	1.0	4.9	0.0
113.9	1360.3	280663.0	28.3	137366.7	1.0	4.9	0.0
114.9	1345.7	281292.9	27.2	138564.0	1.0	4.9	0.0
115.9	1331.7	281891.5	26.0	139761.3	1.0	4.9	0.0
116.9	1318.3	282458.7	24.7	140958.7	1.0	4.9	0.0
117.9	1305.5	282994.7	23.5	142156.0	1.0	4.9	0.0
118.9	1293.3	283499.3	22.2	143353.3	1.0	4.9	0.0
119.9	1281.8	283972.6	20.9	144550.6	1.0	4.9	0.0
120.9	1271.0	284414.6	19.6	145747.9	1.0	4.9	0.0
121.9	1260.8	284825.3	18.3	146945.2	1.0	4.9	0.0
122.9	1251.3	285204.6	16.9	148142.5	1.0	4.9	0.0
123.9	1242.6	285552.7	15.5	149339.8	1.0	4.9	0.0
	1234.6	285869.4	14.1	150537.2	1.0	4.9	0.0
124.9		286154.8	12.7	151734.5	1.0	4.9	0.0
125.9	1227.3			152931.8	1.0	4.9	0.0
126.9	1220.8	286409.0	11.3			4.9	0.0
127.9	1215.1	286631.8	9.8	154129.1	1.0	4.9	0.0
128.9	1: 10.2	286823.3	8.4	155326.4	1.0		0.0
129.9	1206.0	286983.5	6.9	156523.7	1.0	4.9	
130.9	1202.7	287112.4	5.4	157721.0	1.0	4.9	0.0
131.9	1200.1	287210.0	3.9	158918.3	1.0	4.9	0.0
132.9	1198.4	287276.2	2.4	160115.6	1.0	4.9	0.0
133.9	1197.5	287311.2	0.9	161313.0	1.0	4.9	0.0
134.9	1197.4	287314.9	-0.6	162510.3	1.0	4.9	0.0
135.9	1198.1	287287.2	-2.1	163707.6	1.0	4.9	0.0
136.9	1199.6	287228.3	-3.6	164904.9	1.0	4.9	0.0
137.9	1202.0	287138.0	-5.1	166102.2	1.0	4.9	0.0
138.9	1205.1	287016.5	-6.5	167299.5	1.0	4.9	0.0
139.9	1209.1	286863.6	-8.0	168496.8	1.0	4.9	0.0
140.9	1213.9	286679.5	-9.5	169694.1	1.0	4.9	0.0
141.9	1219.4	286464.0	-10.9	170891.4	1.0	4.9	0.0

142.9	1225.7	286217.2	-12.4	172088.7	1.0	4.9	0.0
143.9	1232.8	285939.1	-13.8	173286.0	1.0	4.9	0.0
144.9	1240.6	285629.7	-15.2	174483.4	1.0	4.9	0.0
145.9	1249.2	285289.0	-16.6	175680.7	1.0	4.9	0.0
146.9	1258.5	284917.0	-17.9	176878.0	1.0	4.9	0.0
	1268.5	284513.6	-19.3	178075.3	1.0	4.9	0.0
147.9		284079.0	-20.6	179272.6	1.0	4.9	0.0
148.9	1279.2	283613.0	-21.9	180469.9	1.0	4.9	0.0
149.9	1290.5	283115.7	-23.2	181667.2	1.0	4.9	0.0
150.9	1302.6		-24.4	182864.5	1.0	4.9	0.0
151.9	1315.2	282587.1	-25.7	184061.8	1.0	4.9	0.0
152.9	1328.5	282027.2		185259.1	1.0	4.9	0.0
153.9	1342.3	281436.0	-26.9	186456-4	1.0	4.9	0.0
154.9	1356.8	280813.4	-28.1	187653.7	1.0	4.9	0.0
155.9	1371.8	280159.5	-29.2		1.0	4.9	0.0
156.9	1387.4	279474.3	-30.3	188851.1	1.0	4.9	0.0
157.9	1403.5	278757.7	-31.4	190048.4		4.9	0.0
158.9	1420.0	278009.9	-32.5	191245.7	1.0	4.9 4.9	0.0
159.9	1437.1	277230.7	-33.6	192443.0	1.0		
160.9	1454.7	276420-1	-34.6	193640.3	1.0	4.9	0.0
161.9	1472.7	275578.2	-35.6	194837.6	1.0	4.9	0.0
162.9	1491.2	274705.0	-36.ô	196034.9	1.0	4.9	0.0
163.9	1510.1	273800.4	-37.5	197232.2	1.0	4.9	0.0
164.9	1529.4	272864.5	-38.5	198429.5	1.0	4.9	0.0
165.9	1549.1	271897.3	-39.4	199626.8	1.0	4.9	0.0
166.9	1569.2	270898.7	-40.3	200824.1	1.0	4.9	0.0
167-9	1589.6	269868.7	-41.]	202021.4	1.0	4.9	0.0
168.9	1610.4	268807.4	-42.0	203218.7	1.0	4.9	0.0
169.9	1631.6	267714.7	-42.8	204416.0	1.0	4.9	0.0
170-9	1653.0	266590,7	-43.6	205613.3	1.0	4.9	0.0
171.9	1674.8	265435.2	-44-4	206810.6	1.0	4.9	0.0
172.9	1696.9	264248.5	-45.1	208007.9	1.0	4.9	0.0
173.9	1719.3	263030.3	-45.9	209205.2	1.0	4.9	0.0
174.9	1741.9	261780.8	-46-6	210402.5	1.0	4.9	0.0
175.9	1764.9	260499.9	-47.3	211599.8	1.0	4.9	0.0
176.9	1788.0	259187.6	-48.0	212797.1	1.0	4.9	0.0
177.9	1811.5	257843.9	-48.6	213994.4	1.0	4.9	0.0
178.9	1835 . 1	256468.8	-49.3	215191.7	1.0	4.9	0.0
179.9	1859.1	255062.3	-49.9	216389.0	1.0	4.9	0.0
180.9	1883.2	253624.5	-50.5	217586.3	1.0	4.9	0.0
181.9	1907.5	252155.2	-51.1	218783.6	1.0	4.9	0.0
182.9	1932.1	250654.5	-51.7	219980.9	1.0	4.9	0.0
183.9	1956.8	249122.4	-52.3	221178.2	1.0	4.9	0.0
184.9	1981.8	247558.9	-52.8	222375. 5	1.0	4.9	0.0
185.9	2006.9	245964.0	-53.4	223572.8	1.0	4.9	0.0
186.9	2032.2	244337.6	-53.9	224770.1	1.0	4.9	0.0
187.9	2057.7	242679.8	-54.4	225967.3	1.0	4.9	0.0
188.9	2083.3	240990.6	-54.9	227164.6	1.0	4.9	0.0
189.9	2109.2	239269.9	-55.4	228361.9	1.0	4.9	0.0
190.9	2135.1	237517.8	-55.9	229559. 2	1.0	4.9	0.0
191.9	2161.2	235734.2	-56.4	230756.5	1.0	4.9	0.0
192.9	2187.5	233919.2	-56.8	231953.7	1.0	4.9	0.0
193.9	2213.9	232072.7	-57.3	233151.0	1.0	4.9	0.0
194.9	2240.4	230194.8	-57.7	234348.3	1.0	4.9	0.0
195.9	2267.1	228285.4	-58.1	235545.5	1.0	4.9	0.0
196.9	2293.9	226344.5	-58.5	236742.8	1.0	4.9	0.0
197.9	2320.8	224372.1	-58.9	237940.1	1.0	4.9	0.0
198.9	2347.8	222368.2	-59.3	239137.3	1.0	4.9	0.0
199.9	2374.9	220332.9	-59.7	240334.6	1.0	4.9	0.0
200.9	2402.2	218266.1	-60.1	241531.8	1.0	4.9	0.0
			-				

	0.00 /	01/1/7 7	10 5	21/2720 0	1.0	4.9	0.0
201.9	2429.6	216167.7	-60.5	242729.0	1.0	4.9	0.0
202.9	2457.0	214037.9	-60.8	243926.3			0.0
203.9	2484.6	211876.5	-61.2	245123.5	1.0	4.9	
204.9	2512.2	209683-6	-61.5	246320.7	1.0	4.9	0.0
205.9	2540.0	207459.2	-61.9	247517.9	1.0	4.9	0.0
206.9	2567.8	205203.3	-62.2	248715.1	1.0	4.9	0.0
207.9	2595.8	202915.8	-62.5	249912.3	1.0	4.9	0.0
208.9	2623.8	200596.8	-62.9	251109.5	1.0	4.9	0.0
209.9	2651.9	198246.3	-63.2	252306.7	1.0	4.9	0.0
210.9	2680.1	195864.2	-63.5	253503.8	1.0	4-9	0.0
211.9	2708.3	193450.6	-63.8	254700.9	1.0	4.9	0.0
212.9	2736.7	191005.4	-64.1	255898.1	1.0	4.9	0.0
213.9	2765.1	188528.7	-64.3	257095.2	1.0	4.9	0.0
214.9	2793.6	186020.4	-64.6	258292.3	1.0	4.9	0.0
215.9	2822.1	183480.5	-64.9	2 59 489.3	1.0	4.9	0.0
216.9	2850.7	180909.1	-65.2	260686.4	1.0	4.9	0.0
217.9	2879.4	178306.1	-65.4	261883.4	1.0	4.9	0.0
218.9	2908.1	175671.5	-65.7	263080.4	1.0	4.9	0.0
219.9	2936.9	173005.4	-65.9	264277.3	1.0	4.9	0.0
220.9	2965.8	170307.7	-66.2	265474.3	1.0	4.9	0.0
221.9	2994.7	167578.4	-66.4	266671.2	1.0	4.9	0.0
222.9	3023.6	164817.5	-66.7	267868.0	1.0	4.9	0.0
223.9	3052.6	162025-1	-66.9	269064.8	1.0	4.9	0.0
224.9	3081.6	159201.1	-67.1	270261.6	1.0	4.9	0.0
225.9	3110.7	156345.6	-67.4	271458.3	1.0	4.9	0.0
		153458.5	-67.6	272654.9	1.0	4.9	0.0
226.9	3139.8	150539.8	-67.8	273851.5	1.0	4.9	0.0
227.9	3169-0	147589.7	-68.0	275048.0	1.0	4.9	0.0
228.9	3198.1		-68.2	276244.4	1.0	4.9	0.0
229.9	3227.3	144608.0	-68.4	277440.7	1.0	4.9	0.0
230.9	3256.5	141594.9	-68.7	278636.9	1.0	4.9	0.1
231.9	3285.8	138550.3		279832.9	1.0	4.9	0.1
232.9	3315.0	135474.3	-68.9	281028.8	1.0	4.9	0. i
233.9	3344.2	132366.9	-69.0		1.0	4.9	0.1
234.9	3373.4	129228.1	-69.2	282224.6		4.9	0.1
235.9	3402.5	126058.1	-69.4	283420.1	1.0 1.0	4.9	0.1
236.9	3431.6	122856.9	-69.6	284615.5		4.9	0.1
237.9	3460.7	119624-6	-69.8	285810.5	1.0		0.2
238 .9	3489.6	116361.3	-70.0	287005.3	1.0	4.9	0.2
239.9	3518.5	113067-1	-70.2	288199.8	1.0	4.9	0.2
240.9	3547.2	109742-2	-70.3	289393.8	0.9	4.9	0.3
241.9	3575.6	106386.7	-70.5	290587.4	0.9	4.9	
242.9	3603.9	103001.0	-70.7	291780.4	0.9	5.0	0.3
243.9	3631.9	99585.2	-70.8	292972.8	0.9	5.0	0.4
244.9	3659.5	96139.7	-71.0	294164.4	0.9	5-0	0.4
245.9	3686.6	92665.0	-71.2	295355.2	0.9	5.0	0.5
246.9	3713.2	89161.5	-71.3	296544.8	0.9	5.0	0.6
247.9	3739.1	85629.8	-71.5	297733.2	0.9	5.0	0.7
248.9	3764.1	82070.9	-71.6	298920.1	0.8	5.0	0.9
249.9	3788.1	78485.5	-71.8	300105.1	0.8	5.0	1.1
250.9	3810.8	74874.7	-71.9	301288.0	0.8	5.0	1.3
251.9	3832.0	71240.0	-72.1	302468.2	0.7	5.0	1.6
252.9	3851.5	67582.9	-72.2	303645.4	0.6	5.0	1.9
253.9	3868.7	63905.3	-72.4	304818.9	0.6	5.0	2.2
254.9	3883.4	60209.6	-72.5	305988.0	0.5	5.0	2.7
255.9	3894.9	56498.4	-72.7	307151.9	0.4	5.0	3.2
256.9	3902.6	52775.1	-72.8	308309.6	0.3	5.0	3.9
257.9	3905.9	49043.8	-72.9	309459.9	0.3	5.0	4.6
258.9	3903.8	45309.0	-73.1	310601.4	0.3	5.0	5.5
259.9	3895.5	41576.4	-73.2	311732.4	0.5	5.0	6.6
				_			

3879-8	37852.6	-73.3	312851.2	0.7	5.0	7.8
	-	-73.5	313955.5	0.9	5.0	9.1
		-73.6	315043.1	1.2	5.0	10-4
		-73.8	316111.9	1.4	5.0	11.7
		-73.9	317159.6	1.7	5.0	13.1
-		-74.0	318183.9	2.0	5.0	14.5
			319182.5	2.2	5.0	15.9
		-74.3	320153.3	2.5	5.0	17.3
	9331-0	-74-4	321093.9	2.8	5.0	15.6
-	6050-8	-74.6	322002.5	3.0	5.0	19.9
			322877.1	3.2	5.0	21.0
3156.9	-0.0	-74.9	323654.2	3.4	5.0	22.0
	3879.8 3855.8 3823.9 3783.6 3734.7 3676.8 3609.9 3534.0 3449.5 3356.6 3256.1	3855.8 34145.1 3823.9 30461.8 3783.6 26810.5 3734.7 23199.5 3676.8 19637.4 3609.9 16132.8 3534.0 12694.5 3449.5 9331.0 3356.6 6050.8 3256.1 2861.6	3855.8 34145.1 -73.5 3823.9 30461.8 -73.6 3783.6 26810.5 -73.8 3734.7 23199.5 -73.9 3676.8 19637.4 -74.0 3609.9 16132.8 -74.2 3534.0 12694.5 -74.3 3449.5 9331.0 -74.4 3356.6 6050.8 -74.6 3256.1 2861.6 -74.7	3855.8 34145.1 -73.5 313955.5 3823.9 30461.8 -73.6 315043.1 3783.6 26810.5 -73.8 316111.9 3734.7 23199.5 -73.9 317159.6 3676.8 19637.4 -74.0 318183.9 3609.9 16132.8 -74.2 319182.5 3534.0 12694.5 -74.3 320153.3 3449.5 9331.0 -74.4 321093.9 3356.6 6050.8 -74.6 322002.5 3256.1 2861.6 -74.7 322877.1	3855.8 34145.1 -73.5 313955.5 0.9 3823.9 30461.8 -73.6 315043.1 1.2 3783.6 26810.5 -73.8 316111.9 1.4 3734.7 23199.5 -73.9 317159.6 1.7 3676.8 19637.4 -74.0 318183.9 2.0 3609.9 16132.8 -74.2 319182.5 2.2 3534.0 12694.5 -74.3 320153.3 2.5 3449.5 9331.0 -74.4 321093.9 2.8 3356.6 6050.8 -74.6 322002.5 3.0 3256.1 2861.6 -74.7 322877.1 3.2	3855.8 34145.1 -73.5 313955.5 0.9 5.0 3823.9 30461.8 -73.6 315043.1 1.2 5.0 3783.6 26810.5 -73.8 316111.9 1.4 5.0 3734.7 23199.5 -73.9 317159.6 1.7 5.0 3676.8 19637.4 -74.0 318183.9 2.0 5.0 3609.9 16132.8 -74.2 319182.5 2.2 5.0 3534.0 12694.5 -74.3 320153.3 2.5 5.0 3449.5 9331.0 -74.4 321093.9 2.8 5.0 3356.6 6050.8 -74.6 322002.5 3.0 5.0 3256.1 2861.6 -74.7 322877.1 3.2 5.0

INITIAL DATA

I(0)=0. AL= 1.3962E 00 V(0)=10.0000E-02 ISP(0)=2.3323E 02 K(T)=6.4800E-01 D(B)=8.3333E-02 D(M)=2.5000E-01 M(B)=1.5540E-01 M(0)=8.7743E-01M(P)=5.2278E-01 MR=2.8110E-01

			PATH				
TIME	VEL.	ALT.	ANGLE	RANGE	ACCEL.	WGT.	DRAG
(SEC)	(FT/SEC)	(FT)	(DEG)	(FT)	(G)	(LBS)	(LBS)
0.	0.1	0.	80.0	0.	70.7	28.2	0.0
	231.3	11.3	79.6	2.1	73.0	27.3	1.1
0.2	470.0	45.7	79.5	8.4	75.4	26.4	4.6
0.3	716.7	104.0	79.5	19.2	77.9	25.5	10.7
	971.4	186.9	79.4	34.6	80.4	24.6	19.5
0.5	1234.4		79.4	54.8	83.1	23.7	31.4
0.6	1506.0	429.9	79.4	80.0	85.8	22.8	46.6
0.7	1786.3		79.4	110.3	88.5	21.9	65.3
0.8	2075.6	781.3	79.4	146.0		21.0	87.6
0.9	2374.0	999.9	79.3	187.1	94.2	20.1	113.9
1.0	2681.8	1248.2	79.3	233.9	97.1	19.2	144.3
1.1	2999.2	1527.3	79.3	286.5	100.2	18.3	178.9
1.2	3326.3	1838.0	79.3	345.2	103.2	17.4	218.1
1.3	3663.4	2181.3	79.3	410.1	106.3	16.5	261.9
1.4	4010.7	2558.2	79.3	481.4	109.5	15.6	310.4
1.5	4368.3	2969.8	79.3	559.3	112.8	14.7	363.7
1.6	4736.6	3417.0	79.3	644.1	116.1	13.8	421.9
1.7	5115.7	3900 .9	79.3		119.6	12.9	485.0
1.8	5506.0	4422.6	79.3		123.1	11.9	553.1
1.9	5744.8	4752.8	79.2	897.5	125.3	11.4	596.2
1.9	5744.8	4752.8	79.2	897.5	11.2		51.0
2.9	5427.1	10233.8	79.2		8.7		
3.9	5176.1	15436.1	79.1	2937.7			
4.9	4973.3	20415.6	79.1	3897.7			
5.9	4806.5	25213.4	79.0	4828.7			
6.9	4667.3	29860.5	78.9	5736.7	4.0		
7.9	4549.5	34380.6	78.8	6626.0	3.4		
8.9	4448.9	38792.7	78.8	7500.4	2.9		
9.9	4363.3	43112.5	78.7	8362.7			
10.9	4289.1	47352.9	78.6	9215.6	2.2		
11.9	4223.7	51523.9	78.5	10061.0	1.9		4.7
12.9	4165.2	55633.0	78.4		1.7		
13.9	4112.0	59686.2	78.3	11734.6	1.6	5.0	3.0
14.9	4063.0	63688.1	78.2	12565.0	1.5	5.0	2.5
15.9	4017.4	67642.4	78.1	13392.1	1.4	5.0	2.0
16.9	3974.5	71552.2	78.0	14216.6	1.3	5.0	1.6
17.9	3933.7	75419.6	77.9	15038.8	1.3	5.0	1.3
18.9	3894 .7	79246.8	77=9	15859.3	1.2	5.0	1.1
19.9	3857.1	83035.1	77.8	16678.4	1.2	5.0	0.9
20.9	3820.8	86785.8	77.6	17496.1	1.1	5.0	0.7
21.9	3785.4	90500.0	77.5	18312.9	1.1	5.0	0.6
22.9	3750.7	94178.6	77.4	19128.9	1.1	5.0	0.5
23.9	3716.8	97822.3	77,3	19944.2	1.1	5.0	0.4

		•					
24.9	3683.3	101431.4	77.2	20758.9	1.1	5.0	0.3
25.9	3650.3	105006.7	77.1	21573.1	1.0	4.9	0.3
26.9	3617.6	108548.3	77.0	22386.9			
					1.0	4.9	0.2
27.9	3585.2	112056.6	76.9	23200.4	1.0	4.9	0.2
28.9	3553.0	115531.8	76.8	24013.5	1.0	4.9	0.2
29.9	3521.1	118974.2	76.7	24826.5	1.0	4.9	0.1
30.9	3489.3	122383.8	76.5	25639.2	1.0	4.9	0.1
31.9	3457.7	125761.0	76.4	26451.8	1.0	4.9	0.1
32.9	3426.2	129105.7	76.3	27264.2	1.0	4.9	0.1
33.9	3394.8	132418.0	76.2	28076.4	1.0	4.9	0.1
34.9	3363.6	135698.2	76.0	28888.6	1.0	4.9	0.1
35.9	3332.4	138946.2	75.9	29700.7	1.0	4.9	0.1
36.9	3301.3	142162.1	75.8	30512.6	1.0	4.9	0.0
37.9	3270.2	145345.9	75.6	31324.5	1.0	4.9	0.0
38.9	3239.3	148497.8	75.5	32136.3	1.0	4.9	0.0
39.9	3208.3	151617.7	75.3	32948.1	1.0	4.9	0.0
40.9	3177.5	154705.7	75.2				
				33759.8	1.0	4.9	0.0
41.9	3146.7	157761.9	75.1	34571.5	1.0	4.9	0.0
42.9	3115.9	160786.2	74.9	35383.1	1.0	4.9	0.0
43.9	3085.2	163778.7	74.7	36194.7	1.0	4.9	0.0
44.9	3054.6	166739.4	74.6	37 006.3	1.0	4.9	0.0
45.9	3024.0	169668.3	74.4	37817.8	1.0	4.9	0.0
46.9	2993.4	172565.4	74.3	38629.3	1.0	4.9	0.0
47.9	2962.9	175430.9	74.1	39440.8	1.0	4.9	0.0
48.9	2932.4	178264.6	73.9	40252.3	1.0	4.9	0.0
49.9							
	2901.9	181066.7	73.8	41063.7	1.0	4.9	0.0
50.9	2871.5	183837.0	73.6	41875.2	1.0	4.9	0.0
51.9	2841.2	186575.7	73.4	42686.6	1.0	4.9	0.0
52.9	2810.9	189282.7	73.2	43498.0	1.0	4.9	0.0
53.9	2780.6	191958.1	73.0	44309.4	1.0	4.9	0.0
54.9	2750.4	194601.9	72.8	45120.8	1.0	4.9	0.0
55.9	2720.2	197214.0	72.6	45932.1	1.0	4.9	0.0
56.9	2690.0	199794.6	72.4	46743.5	1.0	4.9	0.0
57.9	2659.9	202343.6	72.2	47554.8	1.0	4.9	0.0
		-					
58.9	2629.9	204860.9	72.0	48366.2	1.0	4.9	0.0
59.9	2599.9	207346.7	71.8	49177.5	1.0	4.9	0.0
60.9	2569.9	209801.0	71.6	49988.8	1.0	4.9	0.0
61.9	2540.0	212223.6	71.4	50800.2	1.0	4.9	0.0
62.9	2510.1	214614.8	71.1	51611.5	1.0	4.9	0.0
63.9	2480.3	216974.4	70.9	52422.8	1.0	4.9	0.0
64.9	2450.5	219302.5	70.7	53234.1	1.0	4.9	0.0
65.9	2420.8	221599.0	70.4	54045.4	1.0	4.9	0.0
66.9	2391.1	223864.1	70.2	54856.7	1.0	4.9	0.0
67.9		226097.6	69.9				0.0
	2361.5			55668.0 548.70.3	1.0	4.9	
68.9	2332.0	228299.7	69.6	56479.3	1.0	4.9	0.0
69.9	2302.5	230470-2	69.4	57290.6	1.0	4.9	0.0
70.9	2273.1	232609.3	69.1	58101.9	1.0	4.9	0.0
71.9	2243.7	234716.9	68.8	58913.2	1.0	4.9	0.0
72.9	2214.4	236793.1	68.5	59724.5	1.0	4.9	0.0
73.9	2185.1	238837.7	68.2	60535.8	1.0	4.9	0.0
74.9	2156.0	240851-0	67.9	61347.0	1.0	4.9	0.0
75.9	2126.9	242832.7	67.6	62158.3	1.0	4.9	0.0
76.9			67.2	62969.6	1.0	4.9	0.0
	2097.8	244783.1					
77.9	2068.9	246702.0	66.9	63780.9	1.0	4.9	0.0
78.9	2040.0	248589.5	66.6	64592.2	1.0	4.9	0.0
79.9	2011.2	250445.5	66.2	65403.5	1.0	4.9	0.0
80.9	1982.5	252270.2	65.8	66214.7	1.0	4.9	0.0
81.9	1953.9	254063.4	65.5	67026.0	1.0	4.9	0.0
82.9	1925.4	255825.2	65.1	67837.3	1.0	4.9	0.0

•							
83.9	1897.0	257555.6	64.7	68648.6	1.0	4.9	0.0
84.9	1868.6	259254.6	64.3	69459.8	1.0	4.9	0.0
85.9	1840.4	260922.3	63.8	70271.1	1.0	4.9	0.0
86.9	1812.3	262558.5	63.4	71082.4	1.0	4.9	0.0
87.9	1784.3	264163.4	63.0	71893.7	1.0	4.9	0.0
88.9	1756.4	265736.9	62.5	72704.9	1.0	4.9	0.0
89.9	1728.6	267279.0	62.0	73516.2	1.0	4.9	0.0
90.9	1701.0	268789.8	61.5	74327.5	1.0	4.9	0.0
91.9	1673.5	270269.2	61.0	75138.7	1.0	4.9	0.0
92.9	1646.2	271717.2	60.5	75950.0	1.0	4.9	0.0
93.9	1618.9	273133.9	59.9	76761.3	1.0	4.9	0.0
94.9	1591.9	274519.2	59.4	77572.6	1.0	4.9	0.0
95.9	1565.0	275873.2	58.8	78383.8	1.0	4.9	0.0
96.9	1538.3	277195.9	58.2	79195.1	1.0	4.9	0.0
97.9	1511.8	278487.2	57.5	80006.4	1.0	4.9 4.9	0.0
98.9	1485.4	279747.2	56.9	80817.6	1./ 1.J	4.9	0.0
99.9	1459.3	280975.8	56.2	81628.9 82440.2	1.0	4.9	0.0
100.9	1433.4 1407.6	282173.2	55.5 54.8	832 5 1.5	1.0	4.9	0.0
101.9	1382.2	283339.2 284473.9	54.1	84062.7	1.0	4.9	0.0
102.9 103.9	1356.9	285577.3	53.3	84874.0	1.0	4.9	0.0
104.9	1332.0	286649.3	52 . 5	85685.3	1.0	4.9	0.0
104.9	1307.3	287690.1	51.6	86496.5	1.0	4.9	0.0
106.9	1282.9	288699.6	50.8	87307.8	1.9	4.9	0.0
107.9	1258.8	289677.7	49.9	88119.1	1.0	4.9	0.0
108.9	1235.0	290624.6	48.9	88930.3	1.0	4.9	0.0
109.9	1211.6	291540.1	48.0	89741.6	1.0	4.9	0.0
110.9	1188.6	292424.4	47.0	90552.9	1.0	4.9	0.0
111.9	1165.9	293277.4	45.9	91364.2	1.0	4.9	0.0
112.9	1143.6	294099.1	44.8	92175.4	1.0	4.9	0.0
113.9	1121.8	294889.5	43.7	92986.7	1.0	4.9	0.0
114.9	1100.4	295648.6	42.5	93798.0	1.0	4.9	0.0
115.9	1079.5	296376.4	41.3	94609.2	1.0	4.9	0.0
116.9	1059.2	297073.0	40.0	95420.5	1.0	4.9	0.0
117.9	1039.3	297738.3	38.7	96231.8	1.0	4.9	0.0
118.9	1020.1	298372.3	37.3	97043.0	1.0	4.9	. 0.0
119.9	1001.4	298975.0	35.9	97854.3	1.0	4.9	0.0
120.9	983.4	299546.5	34.4	98665.6	1.0	4.9	0.0
121.9	966.1	300086.7	32.9	99476.8	1.0	4.9	0.0
122.9	949.5	300595.6	31.3	100288.1	1.0	4.9	0.0
123.9	933.6	301073.3	29.7	101099.4	1.0	4.9	0.0
124.9	918.5	301519.7	28.0	101910.7	1.0	4.9	0.0
125.9	904.3	301934.8	26.2	102721.9	1.0	4.9	0.0
126.9	890-9	302318.7	24.4	103533.2	1.0	4.9	0.0
127.9	878-5	302671.3	22.6	104344.5	1.0	4.9 4.9	0.0
128.9	867.0	302992.7	20.6	105155.7	1.0	4.9	0.0
129.9	856.4	303282.7	18.7	105967.0	1.0 1.0	4.9	0.0
130.9	846.9	303541.6	16.7	106778.3 107589.5	1.0	4.9	0.0
131.9	838-5	303769.2	14.6	108400.8	1.0	4.9	0.0
132.9	831.1	303965.5	12.6	109212.1	1.0	4.9	0.0
133.9 134.9	824.9 819.8	304130.5 304264.3	10.4 8.3	110023.3	1.0	4.9	0.0
134.9	815.9	304366.9	6.1	110834.6	1.0	4.9	0.0
136.9	813.2	304438.2	3.9	111645.9	1.0	4.9	0.0
137.9	811.6	304478.2	1.7	112457.1	1.0	4.9	0.0
138.9	811.3	304487.0	-0.5	113268.4	1.0	4.9	0.0
139.9	812-2	304464-5	-2.7	114079.7	1.0	4.9	0.0
140.9	814.2	304410.8	-4.9	114891.0	1.0	4.9	0.0
141.9	817.5	304325.8	-7.1	115702.2	1.0	4.9	0.0
	~		- - -			•	

		40.400		11/012 6	1.0		ο Λ
142.9	821.9	304209.6	-9.2	116513.5 117324.8	1.0	4.9 4.9	0.0
143.9	827.5	304062.1	-11.4 -13.5	118136.0	1.0	4.9	0.0
144.9	834-2	303883.4	-15.5	118947.3	1.0	4.9	0.0
145.9	842-1	303673.4	-17.6	119758.6	1.0	4.9	0.0
146.9	851.0	303432.1 303159.6	-19.6	120569.8	1.0	4.9	0.0
147.9	860-9	302855.8	-21.5	121381.1	1.0	4.9	0.0
148.9	871.9	302520.8	-23.4	122192.4	1.0	4.9	0.0
149.9	883 - 8 896 - 7	302154.5	-25.2	123003.6	1.0	4.9	0.0
150.9		301756.9	-27.0	123814.9	1.0	4.9	0.0
151.9	910.4 925.0	301328.1	-28.7	124626.2	1.0	4.9	0.0
152.9	940.5	300868.0	-30.4	125437.4	1.0	4.9	0.0
153.9 154.9	956.7	300376.7	-32.0	126248.7	1.0	4.9	0.0
155.9	973.6	299854.1	-33.6	127060.0	1.0	4.9	0.0
156.9	991.2	299300.2	-35.1	127871.2	1.0	4.9	0.0
157.9	1009.5	298715.0	-36.5	128682.5	1.0	4.9	0.0
158.9	1028.4	298098.6	-37.9	129493.8	1.0	4.9	0.0
159.9	1047.9	297450.9	-39.3	130305.1	1.0	4.9	0.0
160.9	1068.0	296771.9	-40.6	131116.3	1.0	4.9	0.0
161.9	1088.6	296061.6	-41.8	131927.6	1.0	4.9	0.0
162.9	1109.7	295320.1	-43.0	132738.9	1.0	4.9	0.0
163.9	1131.3	294547.3	-44.2	133550.1	1_0	4.9	0.0
164.9	1153.3	293743.2	-45.3	134361.4	1.0	4.9	0.0
165.9	1175.8	292907.8	-46.4	135172.7	1.0	4.9	0.0
166.9	1198.6	292041.1	-47.4	135983.9	1.0	4.9	0.0
167.9	1221.8	291143.2	-48.4	136795.2	1.0	4.9	0.0
168.9	1245.4	290213.9	-49.4	137606.5	1.0	4.9	0.0
169.9	1269.3	289253.3	-50.3	138417.7	1.0	4.9	0.0
170.9	1293.5	288261-5	-51.2	139229.0	1.0	4.9	7.0
171.9	1318.1	287238.3	-52.0	140040.3	1.0	4.9	0.0
172.9	1342.9	286183.9	-52.8	140851.5	1.0	4.9	0.0
173.9	1368.0	285098.1	-53.6	141662.8	1.0	4.9	0.0
174.9	1393.3	283981.0	-54.4	142474.1	1.0	4.9	0.0
175.9	1418.9	282832.6	-55.1	143285.3	1.0	4.9	0.0
176.9	1444.7	281652.9	-55.8	144096.6	1.0	4.9	0.0
177.9	1470.7	280441.8	-56.5	144907.9	1.0	4.9	0.0
178.9	1496.9	279199-4	-57.2	145719.1	1.0	4.9	0.0
179.9	1523.4	277925.7	-57.8	146530.4	1.0	4.9	0.0
180.9	1550.0	276620.7	-58-4	147341.7	1.0	4.9 4.9	0.0
181.9	1576.8	275284.3	-59.0	148152.9	1.0	4.9	0.0
182.9	1603.7	273916-6	-59.6	148964.2	1.0 1.0	4.9	0.0
183.9	1630.8	272517-6	-60.2	149775.5	1.0	4.9	0.0
184.9	1658.1	271087-2	-60.7	150586.7 151398.0	1.0	4.9	0.0
185.9	1685.5	269625-4	-61.2	152209.3	1.0	4.9	0.0
186.9	1713.1	268132.3	-61.7 -62.2	153020.5	1.0	4.9	0.0
187.9	1740.8	266607.8	-62.2 -62.7	153831.8	1.0	4.9	0.0
188.9	1768.6	265052.0	-63.2	154643.1	1.0	4.9	0.0
189.9	1796.5	263464.8	-63.6	155454.3	1.0	4.9	0.0
190.9	1824.6	261846-2	-64.0	156265.6	1.0	4.9	0.0
191.9	1852.7	260196.2	-64.5	157076.8	1.0	4.9	0.0
192.9	1881.0	258514.9 256802.1	-64.9	157888.1	1.0	4.9	0.0
193.9	1909.4	255058.0	-65.3	158699.4	1.0	4.9	0.0
194.9	1937.8 1966.4	253282.4	-65.6	159510.6	1.0	4.9	0.0
195.9	1995.0	251475.5	-66.0	160321.9	1.0	4.9	0.0
196.9 197.9	2023.8	249637.1	-66.4	161133.2	1.0	4.9	0.0
198.9	2052.6	247767.4	-66.7	161944.4	1.0	4.9	0.0
199.9	2032.0	245866.2	-67.1	162755.7	1.0	4.9	0.0
200.9	2110.5	243933.5	-67.4	163566.9	1.0	4.9	0.0
4.00 • 7	_,,,,,,						

201.9	2139.5	241969.5	-67.7	164378.2	1.0	4.9	0.0
202.9	2168.7	239974.0	-68.0	165189.4	1.0	4.9	0.0
203.9	2197.9	237947.1	-68.3	166000.7	1.0	4.9	0.0
204.9	2227.1	235888.7	-68.6	166811.9	1.0	4.9	0.0
205.9	2256.4	233798.9	-68.9	167623.2	1.0	4.9	0.0
206.9	2285.8	231677.6	-69.2	168434.4	1.0	4.9	0.0
207.9	2315.3	229524.8	-69.5	169245.7	1.0	4.9	0.0
		227340.6	-69.8	170056.9	1.0	4.9	0.0
208.9	2344.8	225124.9	-70.0	170868.2	1.0	4.9	0.0
209.9	2374.3		-70.3	171679.4	1.0	4.9	0.0
210.9	2403.9	222877.7	-70.5	172490.6	1.0	4.9	0.0
211.9	2433.6	220599.0	-70.8	173301.9	1.0	4.9	0.0
212.9	2463.3	218288.9	-71.0	174113.1	1.0	4.9	0.0
213.9	2493.1	215947.2		174924.3	1.0	4.9	0.0
214.9	2522.9	213574.0	-71.2		1.0	4.9	0.0
215.9	2552.8	211169.3	-71.5	175735.5	1.0	4.9	0.0
216.9	2582.7	208733.1	-71.7	176546.7		4.9	0.0
217.9	2612.6	206265-4	-71.9	177357.9	1.0		
218.9	2642.6	203766-2	-72.1	178169.1	1.0	4.9	0.0
219.9	2672.6	201235-4	-72.3	178980.3	1.0	4.9	0.0
220.9	2702.7	198673.1	-72.5	179791.5	1.0	4.9	0.0
221.9	2732.8	196079-2	-72.7	180602.7	1.0	4.9	0.0
222.9	2762.9	193453-8	-72.9	181413.9	1.0	4.9	0.0
223.9	2793.1	190796.8	-73.1	182225.0	1.0	4.9	0.0
224.9	2823.3	188108.3	-73.3	183036.2	1.0	4.9	0.0
225.9	2853.6	185388.3	-73.5	183847.3	1.0	4.9	0.0
226.9	2883.8	182636.6	-73.7	184658.4	1.0	4.9	0.0
227.9	2914.1	179853-4	-73.8	185469.5	1.0	4-9	0.0
228.9	2944.5	177038.7	-74.0	186280.6	1.0	4.9	0.0
229.9	2974.8	174192-4	-74.2	187091.6	1.0	4.9	0.0
230.9	3005.2	171314.5	-74.3	187902.7	1.0	4.9	0.0
231.9	3035.6	168405.0	-74.5	188713.7	1.0	4-9	0.0
232.9	3066.0	165464.0	-74.7	189524.7	1.0	4.9	0.0
233.9	3096.4	162491.4	-74.8	190335.6	1.0	4.9	0.0
234.9	3126.9	159487.3	-75.0	191146.6	1.0	4.9	0.0
235.9	3157.4	156451.6	-75.1	191957.5	1.0	4.9	6.0
236.9	3187.8	153384.4	-75.3	192768.3	1.0	4.9	0.0
237.9	3218.3	150285.6	-75.4	193579.1	1.0	4.9	0.0
238.9	3248.8	147155.3	-75.5	194389.8	1.0	4.9	0.0
239.9	3279.3	143993.6	-75.7	195200.5	1.0	4.9	0.0
240.9	3309.7	140800-4	-75.8	196011.1	1.0	4.9	0.1
241.9	3340.2	137575.8	-76.0	196821.7	1.0	4.9	0.1
242.9	3370.6	134319.7	-76.1	197632.1	1.0	4.9	0.1
243.9	3400.9	131032.4	-76.2	198442.5	1.0	4.9	0.1
244.9	3431.3	127713.7	-76.3	199252.7	1.0	4.9	0.1
245.9	3461.5	124363.9	-76.5	200062.7	1.0	4.9	0.1
246.9	3491.7	120982.9	-76.6	200872.7	1.0	4.9	0.1
247.9	3521.8	117571.0	-76.7	201682.4	1.0	4.9	0.1
248.9	3551.7	114128.1	-76.8	202491.9	1.0	4.9	0.2
249.9	3581.5	110654.5	-76.9	203301.1	0.9	4.9	0.2
250.9	3611.0	107150.5	-77.1	204110.1	0.9	4.9	0.2
251.9	3640.3	103616.1	-77.2	204918.7	0.9	5.0	0.3
252.9	3669.3	100051-7	-77.3	205726.8	0.9	5.0	0.4
253.9	3697.9	96457.8	-77.4	206534.5	0.9	5.0	0.4
254.9	3726.0	92834.6	-77.5	207341.5	0.9	5.0	0.5
255.9	3753.4	89182-8	-77.6	208147.8	0.9	5.0	0.6
256.9	3780.1	85503.1	-77.7	208953.3	0.8	5.0	0.8
257.9	3805.9	81796.2	-77.8	209757.7	0.8	5.0	0.9
258.9	3830.5	78063.3	-77.9	210560.8	0.8	5.0	1.1
259.9	3853-8	74305.6	-78.0	211362.4	0.7	5.0	1.4

260.9	3875.5	70524.4	-78.1	212162.2	0.7	5.0	1.6
261.9	3895.1	66721.7	-78.2	212959.8	0.6	5.0	2.0
262.9	3912.4	62899.6	-78.3	213754.8	0.5	5.0	2.4
263.9	3926.7	59060.6	-78.4	214546.7	0.4	5.0	2.9
264.9	3937.5	55208.0	-78.5	215334.8	0.3	5.0	3.5
265.9	3944.0	51345.5	-78.6	216118.4	0.2	5.0	4.2
266.9	3945.6	47477.7	-78.7	216896.6	0.2	5.0	5.1
267.9	3941.0	43610.2	-78.8	217668.3	0.3	5.0	6.1
268.9	3929-4	39749.2	-78.9	218432.3	0.5	5.0	7.3
269.9	3909.3	35902.5	-78.9	219187.3	0.8	5.0	8.7
270.9	3880.7	32078.5	-79.0	219931.5	1.0	5.0	10.0
271.9	3843.5	28285.7	-79.1	220663.5	1.3	5.0	11.4
272.9	3797.2	24532.6	-79.2	221381.6	1.6	5.0	12.8
273.9	3741.6	20828.5	-79.3	222084.4	1.9	5.0	14.3
274.9	3676-4	17182.6	-79.4	222770.0	2.2	5.0	15.8
275.9	3601.6	13604.5	-79.5	223437.0	2.5	5.0	17.3
276.9	3517.4	10103.5	-79.6	224083.7	2.8	5.0	18.7
277.9	3424.3	6688.7	-79.7	224708.6	3.0	5.0	20.1
278.9	3322.7	3368.6	-79.8	225310.5	3.3	5.0	21.3
279.9	3213.6	151.3	-79.9	225888.0	3.5	5.0	22.4
279.9	3208.2	-0.0	-79.9	225915.0	3.5	5.0	22.5

INITIAL DATA

Z(0) = G. AL= 1.4834E 00 V(0) = 10.0000E-02 ISP(0) = 2.3323E 02 K(T) = 6.4800E-01 D(B) = 8.3333E-02 D(M) = 2.5000E-01 M(B) = 1.5540E+01 M(0) = 8.7743E-01M(P) = 5.2278E-01 MR = 2.8110E-01

			PATH				
TIME	VEL.	ALT.	ANGLE	RANGE	ACCEL.	WGT.	DRAG
(SEC)	(FT/SEC)	(FT)	(DEG)	(FT)	(G)	(LBS)	(LBS)
0.	0.1	0.	85.0	0.	70.7	28.2	0.0
0.1	231.2	11.5	84.8	1.0	73.0	27.3	1.1
0.2	469.9	46.3	84.8	4.2	75.4	26.4	4.6
0.3	716.5	105.3	84.7	9.6	77.9	25.5	10.7
0.4	971.2	189.3	84.7	17.4	80.4	24.6	19.5
0.5	1234.2		84.7	27.6		23.7	31.4
0.6	1505.7		84.7	40.2		22.8	46.6
0.7	1786.0		84.7	55.5	88.5	21.9	65.2
0.8	2075.3		84.7	73.4	91.3	21.0	87.6
0.9	2373.7	1012.7	84.7	94.1	94.2	20.1	113.8
1.0	2681.5	1264.3	84.7	117.6	97.1	19.2	144.2
1.1	2998.8	1547.0	84.6	144.0	100.1	18.3	178.8
1.2	3326.0	1861.8	84.6	173.5	103.2	17.4	217.9
1.3	3663.1	2209.6	84.6	206.2	106.3	16.5	261.6
1.4	4010.4	2591.5	84.6	242.0	109.5	15.6	310.0
1.5	4368.1	3008.5	84.6	281.2	112-8	14.7	363.2
1.6	4736.4	3461.7	84.6	323.8	116.2	13.8	421.3
1.7	5115.7	3952.0	84.6	370.0	119.6	12.9	484.3
1.8	5506.3	4480.7	84.6	419.8	123.2	11.9	552.2
1.9	5745.2	4815.4	84.6	451.3	125.4	11.4	595.1
1.9	5745.2	4815.4	84.6	451.3	11.2		50.9
2.9	5427.9	10370.6	84.6	976.3	8.7	5.0	38.5
3.9	5177.6	15644.9	84.6	1477.6	7.0	5.0	29.8
4.9	4975.7	20695.0	84.5	1960.7	5.7	5.0	23.3
5.9	4809-9	25562.7	84.5	2429.4	4.7	5.0	18.5
6.9	4671.5	30279.3	84.4	2886.5	3.9	5.0	14.7
7.9	4554.6	34869.0	84.4	3334.4	3.4	5.0	11.8
8.9	4455.1	39350.9	84.4	3775.0	2.8	5.0	9.3
9.9	4370.4	43741.0	84.3	4209.6	2-4	5.0	7.3
10.9	4296.9	48052.5	84.3	4639.6	2.1	5.0	
11.9	4232.1	52295.0	84.2	5065.9		5.0	
12.9	4174.0	56476.2	84.2	5489.3		5.0	3.6
13.9	4121.1	60601.9	84.2	5910.2	1.6	5.0	2.9
14.9	4072.4	64676.9	84.1	6329.3	1.5	5.0	2.4
15.9	4026.9	68704.7	84.1	6746.7	1.4	5.0	1.9
16.9	3984.0	72688.3	84.0	7162.9	1.3	5.0	1.6
17.9	3943.2	76629.9	84.0	7578.1	1.2	5.0	1.3
18.9	3904.1	80531.6	83.9	7992.4	1.2	5.0	1.0
19.9	3866.4	84394-6	83.9	8406.0	1-2	5.0	0.8
20.9	3829.8	88220.4	83.8	8819.0	1-1	5.0	0.7
21.9	3794.1	92009.9	83-8	9231.5	1-1	5.0	0.6
22.9	3759.2	95764.0	83.7	9643.7	1.1	5.0	0.5
23.9	3724.9	99483.2	83.7	10055.5	1.1	5.0	0.4

		107140 2	83.6	10467.1	1.1	5.0	0.3
24.9	3691.0	103168.2	83.5	10878.4	1.0	4.9	0.3
25.9	3657.5	106819-3	83.5	11289.6	1.0	4.9	0.2
26.9	3624.4	110436.9	83.4	11700.6	1.0	4.9	0.2
27.9	3591.5	114021-3	83.4	12111.4	1.0	4.9	0.2
28.9	3558.8	117572.8		12522.2	1.0	4.9	0.1
29.9	3526.3	121091-4	85.3	12932.8	1.0	4.9	0.1
30.9	3494-0	124577.4	83.3	13343.4	1.0	4.9	0.1
31.9	3461.8	128030.9	83.2	13753.9	1.0	4.9	0.1
32.9	3429.7	131452.1	83.1		1.0	4.9	0.1
33.9	3397.6	134841.0	83.1	14164.3 14574.7	1.0	4.9	0.1
34.9	3365.7	138197.7	83.0		1.0	4.9	0.0
35.9	3333.9	141522-2	82.9	14985.0	1.0	4.9	0.0
36.9	3302.1	144814.7	82.9	15395.5	1.0	4.9	0.0
37.9	3270.3	148075-2	82.8	15805.6		4.9	0.0
38.9	3238.7	151303.8	82.7	16215.8	1.0	4.9	0.0
39.9	3207.0	154500.4	82.7	16626.1	1.0	4.9	0.0
40.9	3175.4	157665.1	82.6	17036.2	1.0	4.9	0.0
41.9	3143.8	160798.0	82.5	17446.4	1.0	4.9	0.0
42.9	3112.3	163899.1	82.4	17856.6	1.0	4.9 4.9	0.0
43.9	3080.8	166968.4	82.3	18266.7	1.0		0.0
44.9	3049.3	170005.9	82.3	18676.8	1.0	4.9	0.0
45.9	3017.9	173011.6	82.2	19086.9	1.0	4.9	
46.9	2966.5	175985.6	82.1	19497.0	1.0	4.9	0.0
47.9	2955.0	178927.9	82.0	19907.1	1.0	4.9	0.0
48.9	2923.7	181838.5	81.9	20317.2	1.0	4.9	0.0
49.9	2892.3	184717.5	81.8	20727.2	1.0	4.9	0.0
50.9	2861.0	187564.7	81.8	21137.3	1.0	4.9	0.0
51.9	2829.7	190380.4	81.7	21547.3	1.0	4.9	0.0
52.9	2798.4	193164.3	81.6	21957.4	1.0	4.9	0.0
53.9	2767.1	195916.7	81.5	22367.4	1.0	4.9	0.0
54.9	2735.8	198637.5	81.4	22777.5	1.0	4.9	0.0
55.9	2704.6	201326.6	81.3	23187.5	1.0	4.9	0.0
	2673.4	203984.2	81.2	23597.5	1.0	4.9	0.0
56.9	2642.2	206610.1	81.1	24007.5	1.0	4-9	0.0
57.9	2611.0	209204.6	81.0	24417.6	1.0	4.9	0.0
58.9	2579.9	211767.4	80.9	24827.6	1.0	4.9	0.0
59.9	2548.7	214298.7	80.7	25237.6	1.0	4.9	0.0
60.9	2517.6	216798.5	80.6	25647.6	1.0	4.9	0.0
61.9		219266.7	80.5	26057.6	1.0	4.9	0.0
62.9	2486.5 2455.4	221703.5	80.4	26467.6	1.0	4.9	0.0
63.9		224108.7	80.3	26877.6	1.0	4.9	0.0
64.9	2424.4	226482.4	80.1	27287.6	1.0	4.9	0.0
65.9	2393.3	228824.6	80.0	27697.6	1.0	4.9	0.0
66.9	2362.3	231135.3	79.9	28107.6	1.0	4.9	0.0
67.9	2331.3	233414.6	79.7	28517.6	1.0	4.9	0.0
68.9	2300.3	235662.4	79.6	28927.6	1.0	4.9	0.0
69.9	2269.4	237878.7	79.4	29337.6	1.0	4.9	0.0
70.9	2238.5	240063.6	79.3	29747.6	1.0	4.9	0.0
71.9	2207.5	242217.0	79.1	30157.6	1.0	4.9	0.0
72.9	2176.6		79.0	30567.6	1.0	4.9	0.0
73.9	2145.8	244338.9	78.8	30977.6	1.0	4.9	0.0
74.9	2114.9	246429.5	78.7	31387.6	1.0	4.9	0.0
75.9	2084.1	248488.6	78.5	31797.6	1.0	4.9	0.0
76.9	2053.3	250516.2	78.3	32207.6	1.0	4.9	0.0
77.9	2022.5	252512.5		32617.6	1.0	4.9	0.0
78.9	1991.8	254477.3	78.1	33027.6	1.0	4.9	0.0
79.9	1961-1	256410-8	77.9	33437.6	1.0	4.9	0.0
80.9	1930.4	258312-8	77.7	33847.6	1.0	4.9	0.0
81.9	1899.7	260183.5	77.5	34257.6	1.0	4.9	0.0
82.9	1869.1	262022.8	77.3			- * *	
			3	3			

83.9	1838.5	263830.6	77.1	34667.5	1.0	4.9	0.0
84.9	1807.9	265607.1	76.9	35077. 5	1.0	4.9	0.0
	1777.4	267352.3	76.7	35487.5	1.0	4.9	0.0
85.9		269066.1	76.4	35897.5	1.0	4.9	0.0
86.9	1746.9		76.2	36307.5	1.0	4.9	0.0
87.9	1716.4	270748.5			1.0	4.9	0.0
88.9	1686.0	272399.5	75.9	36717.5			0.0
89.9	1655.6	274019.2	75.7	37127.5	1.0	4.9	
90.9	1625.3	275607.6	75.4	37537. 5	1.0	4.9	0.0
91.9	1594.9	277164.6	75.1	37947. 5	1.0	4.9	0.0
92.9	1564.7	278690.3	74.8	38357. 5	1.0	4.9	0.0
93.9	1534.5	280184.6	74.5	38767.5	1.0	4.9	0.0
94.9	1504.3	281647.7	74.2	39177.4	1.0	4.9	0.0
	1474.2	283079-4	73.9	39587.4	1.0	4.9	0.0
95.9		284479.7	73.5	39997.4	1.0	4.9	0.0
96.9	1444.1		73.1	40407.4	1.0	4.9	0.0
97.9	1414.2	285848.8		40817.4	1.0	4.9	0.0
98.9	1384.2	287186.6	72.8			4.9	0.0
99.9	1354.3	288493.0	72.4	41227.4	1.0		
100.9	1324.6	289768.2	72.0	41637.4	1.0	4.9	0.0
101.9	1294.8	291012.0	71.5	42047.4	1.0	4.9	0.0
102.9	1265.2	292224.6	71.1	42457.4	1.0	4.9	0.0
103.9	1235.6	293405.9	70.6	42867.4	1.0	4.9	0.0
104.9	1206.2	294555.8	70.1	43277.4	1.0	4.9	0.0
		295674.5	69.6	43687.3	1.0	4.9	0.0
105.9	1176.8	296761.9	69.1	44097.3	1.0	4.9	0.0
106.9	1147.5		68.5	44507.3	1.0	4.9	0.0
107.9	1118.4	297818.1			1.0	4.9	0.0
108.9	1089.3	298842.9	67.9	44917.3		4.9	0.0
109.9	1060.4	299836.5	67.3	45327.3	1.0		
110.9	1031.7	300798.9	66.6	45737.3	1.0	4.9	0.0
111.9	1003.0	301729.9	65.9	46147.3	1.0	4.9	0.0
112.9	974.6	302629.7	65.1	46557.3	1.0	4.9	0.0
113.9	946.3	303498.2	64.3	46967.3	1.0	4.9	0.0
114.9	918.3	304335.5	63.5	47377.3	1.0	4.9	0.0
		305141.5	62.6	47787.2	1.0	4.9	0.0
115.9	890-4	305916.3	61.6	48197.2	1.0	4.9	0.0
116.9	862.8		60.6	48607.2	1.0	4.9	0.0
117.9	835-4	306659.8		49017.2	1.0	4.9	0.0
118.9	808.3	307372.1	59.5			4.9	0.0
119.9	781.6	308053.1	58.4	49427.2	1.0	4.9	0.0
120.9	755.1	308702.9	57.1	49837.2	1.0		0.0
121.9	729.1	309321.4	55.8	50247.2	1.0	4.9	
122.9	703.5	309908.7	54.4	50657.2	1.0	4.9	0.0
123.9	678.4	310464.8	52.8	51067.2	1.0	4.9	0.0
124.9	653.7	310989.6	51.2	51477.2	1.0	4.9	0.0
125.9	629.7	311483.2	49.4	51887.1	1.0	4.9	0.0
		311945.5	47.5	52297.1	1.0	4.9	0.0
126.9	606-4		45.4	52707.1	1.0	4.9	0.0
127.9	583.7	312376.6		53117.1	1.0	4.9	0.0
128.9	561.9	312776.5	43.1	53527.1	1.0	4.9	0.0
129.9	541.0	313145.2	40.7			4.9	0.0
130.9	521.2	313482.6	38.1	53937.1	1.0		0.0
131.9	502.5	313788.8	35.3	54347.1	1.0	4.9	
132.9	485.1	314063.8	32.3	54757.1	1.0	4.9	0.0
133.9	469.2	314307.5	29.1	55167.1	1.0	4.9	0.0
134.9	454.8	314520.0	25.7	55577.1	1.0	4.9	0.0
	442-2	314701.3	22.0	55987.0	1.0	4.9	0.0
135.9		314851.4	18.2	56397.0	1.0	4.9	0.0
136.9	431.5		14.1	56807.0	1.0	4.9	0.0
137.9	422.8	314970.2		57217.0	1.0	4.9	0.0
138.9	416-3	315057.8	10.0		1.0	4.9	0.0
139.9	412.0	315114-2	5.7	57627.0		4.9	0.0
140.9	410.1	3151 39 .4	1.3	58037.0	1.0		0.0
141.9	410.6	315133.3	-3.0	58447.0	1.0	4.9	0.0

142.9	413.4	315096.1	-7.4	58857.0	1.0	4.9	0.0
143.9	418.5	315027.6	-11.6	59267.0	1.0	4.9	0.0
144.9	425.9	314927.8	-15.7	59676.9	1.0	4.9	0.0
145.9	435.4	314796.9	-19.7	60086.9	1.0	4.9	0.0
146.9	446.9	314634.7	-23.4	60496.9	1.0	4.9	0.0
147.9	460.2	314441.3	-27.0	60906.9	1.0	4.9	0.0
148.9	475.2	314216.7	-30.4	61316.9	1.0	4.9	0.0
149.9	491.7	313960.9	-33.5	61726.9	1.0	4.9	0.0
150.9	509.6	313673.8	-36.4	62136.9	1.0	4.9	0.0
151.9	528.8	313355.5	-39.2	62546.9	1.0	4.9	0.0
152.9	549.0	313006.0	-41.7	62956.9	1.0	4.9	0.0
153.9	570.3	312625.2	-44.0	63366.9	1.0	4.9	0.0
154.9	592.4	312213.2	-46.2	63776.8	1.0	4.9	0.0
155.9	615.3	311770.0	-48.2	64186.8	1.0	4.9	0.0
156.9	639.0	311295.5	-50.1	64596.8	1.0	4.9	0.0
157.9	663.2	310789.8	-51.8	65006.8	1.0	4.9	0.0
158.9	688.0	310252.9	-53.4	65416.8	1.0	4.9	0.0
159.9	713.4	309684.7	-54.9	65826.8	1.0	4.9	0.0
160.9	739.2	309085.3	-56.3	66236. 8	1.0	4.9	0.0
161.9	765.3	308454.7	-57.6	66646.8	1.0	4.9	0.0
162.9	791.9	307792.8	-58.8	67056.8	1.0	4.9	0.0
163.9	818.8	307099.7	-60.0	67466.8	1.0	4.9	0.0
164.9	846.0	306375.3	-61.0	67876.7	1.0	4.9	0.0
165.9	873.5	305619.7	-62.0	68286.7	1.0	4.9	0.0
166.9	901.2	304832.8	-62.9	68696.7	1.0	4.9	0.0
167.9	929.1	304014.6	-63.8	69106.7	1.0	4.9	0.0
168.9	957.3	303165.2	-64.6	69516.7	1.0	4.9	0.0
169.9	985.6	302284.6	-65.4	69 926.7	1.0	4.9	0.0
170.9	1014.1	301372.7	-66.2	70336.7	1.0	4.9	0.0
171.9	1042.8	300429.5	-66.8	70746.7	1.0	4.9	0.0
172.9	1071.6	299455.1	-67.5	71156.7	1.0	4.9	0.0
173.9	1100.6	298449.4	-68.1	71566.7	1.0	4.9	0.0
174-9	1129.6	297412-4	-68.7	71976.6	1.0	4.9	0.0
175.9	1158.8	296344.1	-69.3	72386.6	1.0	4.9	0.0
176.9	1188.2	295244.6	-69.8	72796.6	1.0	4.9	0.0
177.9	1217.6	294113.8	-70.3	73206.6	1.0	4.9	0.0
178.9	1247-1	292951.6	-70.8	73616.6	1.0	4.9	0.0
179.9	1276.7	291758.3	-71.3	74026.6	1.0	4.9	0.0
180.9	1306.3	290533.6	-71.7	74436.6	1.0	4.9	0.0
181.9	1336.1	289277.6	-72.1	74846.6	1.0	4.9	0.0
182.9	1365.9	287990.3	-72.5	75256.6	1.0	4.9	0.0
183.9	1395.8	286671.7	-72.9	75666.5	1.0	4.9	0.0
184.9	1425.8	285321.8	-73.3	76076.5	1.0	4.9	0.0
185.9	1455.8	283940.6	-73.6	76486. 5	1.0	4.9	0.0
186.9	1485.9	282528.1	-74.0	76896.5	1.0	4.9	0.0
187.9	1516.0	281084.2	-74.3	77306.5	1.0	4.9	0.0
188.9	1546.2	279609.1	-74.6	77716.5	1.0	4.9	0.0
189.9	1576.4	278102.6	-74.9	78126.5	1.0	4.9	0.0
190.9	1606.7	276564.8	-75.2	78536.5	1.0	4.9	0.0
191.9	1637.0	274995.6	-75.5	78946.5	1.0	4.9 4.9	0.0
192.9	1667.4	273395.1	-75.8 -74.0	79356.5	1.0	4.9	0.0
193.9	1697.8	271763.3	-76.0 -76.3	79766.4 80176 h	1.0	4.9	0.0
194.9	1728.2	270100.1	-76.3 -76.5	80176.4	1.0 1.0	4.9	0.0
195.9	1758.7	268405.5	-76.5 -76.8	80586.4 8098 h	1.0	4.9	0.0
196.9	1789.2	266679.6	-76.8 -77.0	80996.4 811.06.4		4.9	0.0
197.9	1819.8	264922.3	-77.0 -77.2	81406.4 81816.4	1.0	4.9	0.0
198.9	1850.3	263133.6	-77.2	82226.4	1.0	4.9	0.0
199.9	1880.9	261313.6	-77.4 -77.6	82636.4	1.0	4.9	0.0
200.9	1911.6	259462.2	-11.0	04030+4	1 . 0	7 9 7	V • V

201.9	1942.3	257579.4	-77.8	83046.3	1.0	4.9	0.0
202.9	1973.0	255665.2	-78.0	83456.3	1.0	4.9	0.0
203.9	2003.7	253719.6	-78.2	83866.3	1.0	4.9	0.0
		251742.6	-78.4	84276.3	1.0	4.9	0.0
204.9	2034.4					4.9	
205.9	2065.2	249734.2	-78.5	84686.3	1.0		0.0
206.9	2096.0	247694.4	-78.7	85096.3	1.0	4.9	0.0
207.9	2126.8	245623.1	-78.9	85506.3	1.0	4.9	0.0
208.9	2157.7	243520.5	-79.0	85916.2	1.0	4.9	0.0
209.9	2188.6	241386.4	-79.2	86326.2	1.0	4.9	0.0
210.9	2219.5	239220.8	-79.4	86736.2	1.0	4.9	0.0
211.9	2250.4	237023.9	-79.5	87146.2	1.0	4.9	0.0
212.9	2281.3	234795.4	-79.6	87556.2	1.0	4.9	0.0
213.9	2312.3	232535.5	-79.8	87966.2	1.0	4.9	0.0
214.9	2343.2	230244.2	-79.9	88376.1	1.0	4.9	0.0
215.9	2374.2	227921.4	-80.1	88786.1	1.0	4.9	0.0
216.9	2405.2	225567.1	-80.2	89196.1	1.0	4.9	0.0
217.9	2436.3	223181.3	-80.3	89606.1	1.0	4.9	0.0
			-80.4	90016.0	1.0	4.9	0.0
218.9	2467.3	220764.0			1.0	4.9	0.0
219.9	2498.4	218315.3	-80.6	90426.0			
220.9	2529.5	215835.0	-80.7	90836.0	1.0	4.9	0.0
221.9	2560.5	213323.3	-80.8	91245.9	1.0	4.9	0.0
222.9	2591.7	210780.0	-80.9	91655.9	1.0	4.9	0.0
223.9	2622.8	208205.2	-81.0	92065.9	1.0	4.9	0.0
224.9	2653.9	205598.9	-81.1	92475.8	1.0	4.9	0.0
225.9	2685.1	202961.1	-81.2	92885. 8	1.0	4.9	0.0
226.9	2716.2	200291.7	-81.3	93295.7	1.0	4.9	0.0
227.9	2747.4	197590.8	-81.4	93705.7	1.0	4.9	0.0
228.9	2778.6	194858.3	-81.5	94115.6	1.0	4.9	0.0
229.9	2809.8	192094.3	-81.6	94525.6	1.0	4.9	0.0
230.9	2841.0	189298.8	-81.7	94935.5	1.0	4.9	0.0
231.9	2872.3	186471.7	-81.8	95345.4	1.0	4.9	0.0
232.9	2903.5	183613.1	-81.9	95755.3	1.0	4.9	0.0
233.9	2934.8	180722.8	-82.0	96165.3	1.0	4.9	0.0
234.9	2966.0	177801.1	-82.1	96575.2	1.0	4.9	0.0
235.9	2997.3	174847.7	-82.1	96985.1	1.0	4.9	0.0
236.9	3028.6	171862.8	-82.2	97394.9	1.0	4.9	0.0
			-82.3	97804.8	1.0	4.9	0.0
237.9	3059.8	168846.3		98214.7	1.0	4.9	0.0
238.9	3091.1	165798.3	-82.4		1.0	4.9	0.0
239.9	3122.4	162718.7	-82.5	98624.5			0.0
240.9	3153.6	159607.6	-82.5	99034.3	1.0	4.9	
241.9	3184.9	156464.9	-82.6	99444.1	1.0	4.9	0.0
242.9	3216.2	153290.7	-82.7	99853.9	1.0	4.9	0.0
243.9	3247.4	150085.0	-82.8	100263.7	1.0	4.9	0.0
244.9	3278.7	146847.8	-82.8	100673.4	1.0	4.9	0.0
245.9	3309.9	143579.1	-82 .9	101083.1	1.0	4.9	0.0
246.9	3341.1	140278.9	-83.0	101492.8	1.0	4.9	0.1
247.9	3372.2	136947.4	-83.0	101902.4	1.0	4.9	0.1
248.9	3403.3	133584.4	-83.1	102312.0	1.0	4.9	0.1
249.9	3434.4	130190-2	-83.2	102721.5	1.0	4.9	0.1
250.9	3465.3	126764.7	-83.2	103131.0	1.0	4.9	0.1
251.9	3496.2	123308.1	-83.3	103540.3	1.0	4.9	0.1
252.9	3527.0	119820.4	-83.3	103949.6	1.0	4.9	0.1
253.9	3557.7	116301.7	-83.4	104358.8	1.0	4.9	0.2
254.9	3588.2	112752.3	-83.5	104767.9	1.0	4.9	0.2
255.9	3618.4	109172.2	-83.5	105176.8	0.9	4.9	0.2
			-83.6	105585.6	0.9	4.9	0.3
256.9	3648.5	105561.8		1055994.2	0.9	5.0	0.3
257.9	3678.2	101921.3	-83.6 -83.7	106402.5	0.9	5.0	0.4
258.9	3707.6	98251.0	-83.7			5.0	0.5
259.9	3736.5	94551.4	-83.7	106810.6	0.9	J•U	0.5

260.9	3764.8	90822.9	-83.8	107218.3	0.9	5.0	0.6
261.9	3792.4	87066.3	-83.8	107625.6	0.9	5.0	0.7
262.9	3819.0	83282.3	-83.9	108032.4	0.8	5.0	0.9
263.9	3844.6	79472.0	-83.9	108438.7	0.8	5.0	1.1
264.9	3868.9	75636.6	-84.0	108844.2	0.7	5.0	1.3
265.9	3891.5	71777.4	-84.0	109248.8	0.7	5.0	1.6
266.9	3912.3	67896.2	-84.1	109652.4	0.6	5.0	1.9
267.9	3930.6	63995.3	-84.1	110054.8	0.5	5.0	2.3
268.9	3946.2	60077.1	-84.2	110455.6	0.4	5.0	2.8
269.9	3958.2	56144.8	-84.2	110854.6	0.3	5.0	3.4
270.9	3966.1	52202.2	-84.3	111251.4	0.2	5.0	4.1
271.9	3968.9	48253.9	-84.3	111645.6	0.1	5.0	5.0
272.9	3965.7	44305.3	-84.4	112036.6	0.2	5.0	6.0
273.9	3955.4	40363.1	-84.4	112423.8	0.5	5.0	7.2
274.9	3936.6	36435.0	-84.5	112806.6	0.7	5.0	8.6
275.9	5908.9	32529.7	-84.5	113164.0	1.0	5.0	9.0
274.9	3872.3	28456.1	-84.5	113555.2	1.3	5.0	11.4
277.9	3824.5	24823.2	-84.6	113919.5	1.6	5.0	12.8
278.9	3770.9	21040.4	-84.6	114276.1	1.9	5.0	14.4
279.9	3705.5	17317.7	-84.7	114623.9	2.2	5.0	15.9
280.9	3630.1	13664.7	-84.7	114942.4	2.5	5.0	17.5
281.9	3545.0	10091.4	-84.8	115290.4	2.8	5.0	18.9
282.7	3450.5	4607.3	-84.8	115007.5	3.1	5.0	20.3
283.9	3347.3	3221.4	-84.9	115912.7	3.3	5.0	21.7
284.8	3238.3	0.0	-84.9	114200.3	3.6	5.0	22.0

TABLE 2
AERODYNAMIC HEATING DATA

Key to Tabulated Data

Case	Item	Material	Thickness(in)	Characteristic Length(in)
1	fin	aluminum	0.060	1.250
2	fin	stainless steel	0.060	1.250
3	fin	stainless steel	0.100	1.250
4	nose cone	carbon steel	0.204	6.032
5	nose cone	carbon steel	0.204	11.422

TABLE 2

TABULATED AERODYNAMIC HEATING DATA

CASE 1

MATERIAL CHARACTERISTICS

			V(W) =				
A ()	1) = 1.00	0 FT2		1(0)	= 505.0		
	0.22	4 8TU/L8-	DEG F	E(W)			
R		9 LE/FT3		L	= 0.000	25 FT	
X =	0.1040 FT				•		
^ -	0.2040 11						
TIME	VEL	ALT	M	RN	T(R)	Q	T(%)
1 PINC	***					(RTU/	
ISEC)	(FT/SEC)	(FT)			(DEG R)	FT2-SEC)	(DEG R)
iscor	(1 1) 3203	****					
0.2	0.1	÷0.	0.00	66.3	518.69	0.00	505.00
041	231.3	11.3	0.21	153395.7	522.65	0.04	505.02
0.2	470.0	45.7	0.42	311447.0	535.06	0.10	505.08
043	716.7	104.0	0.64	474272.4	556.76	0.21	505-23
024	971.4	186.9	0.87	641565.3	588.63	0.39	505.53
0.15	1234.4	295.3	1.11	813185.4	631.66	0.66	506.07
046	1506.0	429.9	1.35	988963.4	686.87	1.04	506.96
0.7	1786.3	591.6	1.60	1168562.6	755.35	9.06	511.34
860	2075.6	781.3	1.86	1351742.5	838 - 28	13.10	523.80
019	2374.0	999.9	2.13	1538097.2	936.86	18.30	540.21
120	2681.8	1248.2	2.41	1727319.1	1052.42	24.74	562.84
131		1527.3	2.70	1918987.0	1186.35	32.56	593.04
112		1838.0	3.00	2112591.5	1340.07	41-86	632.30
1.3		2181.3	3.30	2307705.1	1515.16	52.75	682.24
114		2558.2	3.62	2503799.1	1713.26	65.33	744.59
145		2969.8	3.95	2700238.1	1936.00	79.66	821.18
116		3417.0	4.29	2896548.4	2185.34	95.83	913.89
1:7		3900.9	4.64	3092021.5	2463.10	113.87	1024.68
128		4422.6	5.01	3286093.7		133.86	1155.54
119		4752.8	5.23	3401186.7		141.78	1302.75
129	•	4752.8	5.23	3401186.7	2971.33	141.78	1302.75
107	J1770U	417200	,,,,	- · • ·			

```
38.96
                                                                      2131.41
                  10233.8
                             5.04
                                     2803713.1
                                                  2686.20
  2.9
        5427.1
                                                              8.41
                                                                     2324.97
                            4.90
                                    2336747.9
                                                 2468.52
 3.9
      5176.1
                 15436.1
                                                             -1.29
                                                                     2322.94
                            4.80
                                                 2296.77
                                    1962718.2
 4.9
      4973.3
                 20415.6
                                                             -5.52
                                                                     2290.23
                            4.73
                                    1657398.2
                                                 2157.63
 5.4
      4606.5
                 25213.4
                                                 2042.42
                                                             -5.92
                                                                     2210.14
 6.9
      4667.3
                 29860.5
                            4.69
                                    1404460.1
 7.9
                            4.66
                                                 1945.11
                                                             -5.42
                                                                     2126.13
      4549.5
                                    1192441.0
                 34380.6
                                                                     2068.16
                                                             -0.88
 8.4
      4448.9
                 38792.7
                            4.59
                                     971854.1
                                                 1871.07
                                                 1814.63
                                                             -0.93
                                                                     2046.03
                            4.50
                                     775079.7
 9:9
      4363.3
                 43112.5
                                                 1766.59
                                                                     2017.48
                            4.43
                                                             -0.90
10.9
      4289.1
                 47352.9
                                     621967.0
                                                                     1990.52
                 51523.9
                            4.36
                                     501696.8
                                                 1724.92
                                                             -0.86
1129
      4223.7
                                                             -0.80
                                                                     1965.44
                            4.30
                                     406491.1
                                                 1688.20
                 55633.0
12.9
      4165.2
                                                             -0.75
                                                                     1941.71
                            4.25
                                                 1655.25
      4112.0
                 59686.2
                                     330619.9
13.9
                                                             -0.69
                                                                     1919.28
                            4.19
                                                 1625.28
14.9
      4063.0
                 63688.1
                                     269823.8
                                                             -0.64
                                                                     1898.07
                            4.15
                                     220879.3
                                                 1597.70
15.9
       4017.4
                 67642.4
                                                             -0.59
                                                                     1878.01
16.19
       3974.5
                 71552.2
                            4.10
                                     181310.3
                                                 1572.05
                                                             -0.55
                                                                     1859.00
                                                 1547.90
                 75419.6
                            4.06
                                     149203.9
1739
       3933.7
                                                                     1840.97
                                                             -0.50
                            4.02
                                     123070.6
                                                 1525.06
18.9
       3894.7
                 79246.8
                                                             -0.46
                                                                     1823.84
19.9
       3857.1
                 83035.1
                            3.98
                                      101221.4
                                                 1504.37
                                                                     1807.58
                            3.91
                                       81722.6
                                                 1489.64
                                                             -0.42
                 86785.8
2019
       3820.8
                                                                     1792.16
                                                 1475.56
                                                             -0.38
                                       66326.8
2129
       3785.4
                 90500.0
                            3.84
                                                             -0.35
                                                                     1777.48
                                                 1461.99
                 94178.6
                            3.78
                                       54099.6
22.9
       3150.7
                                                             -0.32
                                                                     1763.49
                                                 1448.99
                 97822.3
                            3.72
                                       44338.3
23.19
       3716.8
                                                                     1750.12
                            3.66
                                       36502.5
                                                 1436.32
                                                             -0.29
                101431.4
24.9
       3683.3
                                                             -0.27
                                                                     1737.31
                            3.60
                                                 1424.04
                                       30182.6
2529
       3650.3
                105006.7
                                                             -0.25
                                                                     1725.03
                                                 1412.02
                            3.55
                                       25060.7
26.9
       3617.6
                108548.3
                                                                     1713.22
                                       20891.3
                                                 1400.28
                                                             -0.23
       3585.2
                112056.6
                            3.49
27.9
                                                             -0.21
                                                                     1701.85
                                       17482.5
                                                 1388.73
       3553.0
                115531.8
                            3.44
2849
                                                             -0.20
                                                                     1690.89
                                       14684.6
                                                 1377.45
       3521.1
                118974.2
                            3.39
29.9
                                                             -0.18
                                                                     1680.30
                                       12378.5
                                                 1366.32
                            3.33
30.9
       3489.3
                122383.8
                                                             -0.17
                                                                     1670.06
                                                 1355.38
       3457.7
                125761.0
                            3.28
                                       10470.8
3149
                            3.24
                                        8886.7
                                                 1344.59
                                                             -0.16
                                                                     1660.14
       3426.2
                129105.7
32.9
                                                                     1650.53
                                                 1333.95
                                                             -0.15
                            3.19
                                        7566.6
       3394.8
                132418.0
33:9
                                                             -0.14
                                                                     1641.20
                                                 1323.50
34.9
       3363.6
                135698.2
                            3.14
                                        6463.1
                                                             -0.13
                                                                     1632.14
                             3.09
                                        5537.1
                                                 1313.15
3519
       3332.4
                138946.2
                                                             -0.12
                                                                     1623.34
                             3.05
                                        4757.9
                                                 1302.93
       3301.3
36.49
                142162.1
                                                             -0.11
                                                                     1614.76
                            3.00
                                        4099.9
                                                 1292.81
37.9
       3270.2
                145345.9
                                                             -0.11
                                                                     1606.42
                                                 1282.87
                            2.96
                                        3542.9
                148497.8
3849
       3239.3
                                                             -0.10
                                                                     1598.28
                                                 1272.98
3949
       3208.3
                151617.7
                            2.92
                                        3069.8
                                                             -0.10
                                                                     1590.35
                            2.88
                                        2666.9
                                                 1263.27
40:9
       3177.5
                154705.7
                                                                     1582.60
                                        2354.8
                                                 1249.73
                                                             -0.09
                            2.84
       3146.7
                157761.9
41.9
                                                             -0.09
                                                                     1575.02
                            2.82
                                        2089.5
                                                 1235.30
42.9
       3115.9
                160786.2
                                                             -0.09
                                                                     1567.60
                                        1856.0
                                                 1221.05
                             2.79
       3085.2
                163778.7
43.9
                                                                     1560.34
                                                             -0.08
                             2.76
                                        1650.6
                                                 1206.99
44.19
       3054.6
                166739.4
                                                                     1553.23
                                        1469.4
                                                 1193.08
                                                             -0.08
                             2.73
45.9
                169668.3
       3024.0
                                                             -0.08
                                                                     1546.26
                                                 1179.30
                                        1309.6
                             2.71
46.9
       2993.4
                172565.4
                                                             -0.07
                                                                     1539.44
                                        1169.2
                                                 1165.50
47.9
       2962.9
                175430.9
                             2.68
                                                             -0.07.
                                                                     1532.74
                                        1069.9
                                                 1145.16
                             2.67
48.9
       2932.4
                178264.6
                                                                      1526.16
                                         978.6
                                                 1125.05
                                                              -0.07
                             2.66
49.9
       2901.9
                181066.7
                                                                      1519.70
                                         894.9
                                                 1105.19
                                                             -0.07
                             2.65
50.9
       2871.5
                183837.0
```

```
-0.07
                                                                       1513.35
                                          818.2
                                                  1085.60
                 186575.7
                              2.64
 51.9
       2841.2
                                                              -0.07
                                                                      1507.11
                                         747.8
                                                 1066.22
                            2.63
                189282.7
5219
      2810.9
                                                 1047.05
                                                              -0.06
                                                                      1500.98
                                         683.2
                            2.62
53.9
       2780.6
                191958:1
                                                              -0.06
                                                                      1494.96
                                                 1028.15
                                         624.1
5419
                194601.9
                            2.61
       2750.4
                                                 1009.45
                                                              -0.06
                                                                      1489.04
                                         569.9
                197214.0
                            2.60
55.9
      2720.2
                                                              -0.06
                                                                      1483.23
                            2:59
                                         520.3
                                                  990.98
56:9
       2690.0
                199794.6
                                                              -0.06
                                                                      1477.51
                                                  972.75
                            2.58
                                         474.9
                202343.6
57.9
       2659.9
                                                  954.78
                                                              -0.05
                                                                      1471.90
                                         433.3
                            2.56
58.39
       2629.9
                204860.9
                                                                      1466.37
                                                              -0.05
                                                   937.02
                                         395.3
59.19
                207346.7
                            2.55
       2599.9
                                                              -0.05
                                                                      1460.94
                                                   919.48
                            2.54
                                         360.6
                209801.0
60.9
       2569.9
                                                              -0.05
                                                                      1455.60
                                         328.8
                                                   902-18
                            2.53
       2540.0
                212223.6
61.9
                                                              -0.05
                                                                      1450.35
                                                   885.10
                                          299.8
                214614.8
                            2.52
62.9
       2510.1
                                                   868.27
                                                              -0.05
                                                                      1445.18
                                          273.3
                216974.4
                            2.50
63.9
       2480.3
                                                                      1440.10
                                                              -0.04
                                          249.0
                                                   851.64
                            2.49
64.9
       2450.5
                219302-5
                                                                      1435.10
                                                              -0.04
                                          226.9
                                                   835.26
                             2.48
                221599.0
65.9
       2420.8
                                          206.7
                                                   819.09
                                                              -0.04
                                                                      1430.18
                223864.1
                            2.46
66.9
       2391.1
                                                              -0.04
                                                                      1425.34
                                                   803.17
                                          188.3
                             2.45
67.9
       2361.5
                226097.6
                                                              -0.04
                                                                      1420.58
                                                   787.49
                                          171.5
                228299.7
                             2.44
       2332.0
68.9
                                                                      1415.89
                                                   772.02
                                                              -0.04
                             2.42
                                          156.2
       2302.5
                230470.2
6949
                                                                      1411.27
                                                              -0.03
                                                   756.78
                                          142.3
                             2.41
                232609.3
7019
       2273.1
                                                   741.76
                                                              -0.03
                                                                      1406.72
                                          129.5
                             2.39
       2243.7
                234716.9
7149
                                                                      1402.25
                                                              -0.03
                                                   726.97
                                          117.9
                             2.38
72.9
       2214.4
                236793.1
                                                                      1397.84
                                                              -0.03
                                                   712.39
                             2.36
                                          107.4
                238837-7
73.9
       2185.1
                                                              -0.03
                                                                      1393.49
                                           97.8
                                                   698.08
                             2.35
                240851.0
74.19
       2156.0
                                                                      1389.21
                                                              -0.03
                                           89.0
                                                   683.97
                             2.33
75.9
       2126.9
                242832.7
                                                                      1384.99
                                                              -0.03
                                           81.0
                                                   670.07
                             2.32
                244783.1
76:9
       2097.8
                                                                       1380.83
                                                   656.43
                                                              -0.02
                                           73.8
                             2.30
77:9
       2068.9
                246702.0
                                                                       1376.73
                                                   642.99
                                                              -0.02
                                           67.2
                             2.28
                248589.5
       2040.0
7849
                                           61.2
                                                   629.79
                                                              -0.02
                                                                       1372.69
                             2.27
                250445.5
       2011.2
79.9
                                                                       1368.70
                                           55.7
                                                              -0.02
                                                   616.81
80.9
       1982.5
                252270.2
                             2.25
                                                                       1364.77
                                                              -0.02
                                           50.7
                                                   604.07
                            .2.23
       1953.9
                254063.4
8149
                                                              -0.02
                                                                       1360.89
                                                   591.55
                                           46.2
                             2.21
       1925.4
                255825-2
82.9
                                                                       1357.06
                                                              -0.02
                                           42.1
                                                   579.26
                             2.20
                257555.6
8319
       1897.0
                                                              -0.02
                                                                       1353.28
                                                   567.16
                                           38.4
                             2.18
                259254.6
8429
       1868.6
                                                                       1349.54
                                                              -0.02
                                           35.0
                                                   555.32
                             2.16
       1840.4
                260922.3
8529
                                                                       1345.86
                                                              -0.02
                                                   543.96
                                           31.8
                             2.14
       1812.3
                262558.5
8619
                                                              -0.01
                                                                       1342.22
                                                   536.43
                                           28.4
                264163.4
                             2.11
8719
       1784.3
                                                                       1338.63
                                                   529.03
                                                               -0.01
                                           25.4
                             2.07
       1756.4
                265736.9
8839
                                                               -0.01
                                                                       1335.08
                                           22.7
                                                   521.78
                             2.04
       1728.6
                267279.0
8919
                                                               -0.01
                                                                       1331.58
                                                   514.70
                             2.01
                                           20.4
                268789.8
9049
       1701.0
                                                                       1328.12
                                                               -0.01
                                           18.3
                                                   507.76
                             1.98
                270269+2
       1673.5
9139
                                                                       1324.69
                                                   500.98
                                                               -0.01
                                           16.5
                             1.94
9219
       1646.2
                271717.2
                                                               -0.01
                                                                       1321.31
                                           14.9
                                                   494.31
       1618.9
                273133.9
                             1.91
9349
                                                                       1317.97
                                                               -0.01
                                           13.4
                                                   487.82
                             1.88
                 274519.2
       1591.9
94.9
                                                               -0.01
                                                                       1314.66
                                                   481.46
                             1.85
                                           12.2
                275873.2
9529
       1565.0
                                                                       1311.39
                                                               -0.01
                                                   475.26
                                           11:0
                 277195.9
                             1.82
4619
       1538.3
                                                                       1308.16
                                                               -0.01
                                           10.0
                                                   469.22
                             1.79
                278487.2
97.9
       1511.8
                                                               -0.01
                                                                       1304.96
                                                   463.29
                                            9.1
                             1.75
       1485.4
                 279747.2
 98.9
                                                                       1301.79
                                                               -0.01
                                                   457.54
                             1.72
                                            8.3
                 280975.8
       1459.3
 9919
```

```
451.94
                                                                 -0.01
                                                                         1298.66
                  282173.2
                               1.69
                                              7.6
 100.9
         1433.4
                                                                        1295.56
                                                    446.45
                                                               -0.01
        1407.6
                 283339.2
                              1.66
                                             6.9
101:9
                                                    441.15
                                                               -0.01
                                                                        1292.50
                                             6.3
                 284473.9
                              1.63
102.9
        1382.2
                                                               -0.01
                                                                        1289.46
                                             5.8
                                                    435.96
        1356.9
                 285577.3
                              1.60
103.9
                                                               -0.01
                                                                        1286.46
10419
        1332.0
                 286649.3
                              1.57
                                             5.4
                                                    430.95
                                                               -0.01
                                                                        1283.48
        1307.3
                              1.54
                                             4.9
                                                    426.08
105.49
                 287690.1
                                             4.5
                                                               -0.01
                                                                        1280.54
                              1.51
                                                    421.35
10629
        1282.9
                 288699.6
                                                                -0.01
                                                                        1277.62
                 289677.7
                              1.49
                                             4.2
                                                    416.76
107.9
        1258.8
                                                    412.32
                                                               -0.01
                                                                        1274.73
                              1.46
                                             3.9
10819
        1235.0
                 290624.6
                                                                        1271.87
                 291540.1
                              1.43
                                             3.6
                                                    408.04
                                                               -0.01
10939
        1211.6
                              1.40
                                                    403.91
                                                                -0.01
                                                                        1269.04
                 292424.4
                                             3.4
110.9
        1188.6
                                                                -0.01
                                             3.1
                                                    399.91
                                                                        1266.23
11119
                 293277.4
                              1.38
        1165.9
                                                                -0.01
                                                                        1263.45
        1143.6
                 294099.1
                              1.35
                                             2.9
                                                    396.05
11249
                                                    392.36
                                                                -0.00
                                                                        1260.70
                                             2.7
113.9
        1121.8
                 294889.5
                              1.32
                                                                        1257.97
                              1.30
                                             2.5
                                                    388.80
                                                                -0.00
                 295648.6
11449
        1100.4
                                                                -0.00
                                                                        1255.26
                              1.27
                                             2.4
                                                    385.39
11549
        1079.5
                 296376.4
                                                    382.14
                                                                -0.00
                                                                        1252.58
                              1.25
                                             2.2
                 297073.0
11619
        1059.2
                                                                        1249.92
                                                                -0.00
11749
        1039.3
                 297738.3
                              1.23
                                             2.1
                                                    379.02
                                                                -0.00
                                                                        1247.29
                                             2.0
                                                    376.06
11819
        1020.1
                 298372.3
                              1.20
                                                    373.23
                                                                -0.00
                                                                        1244.68
                              1.18
                                             1.9
        1001.4
                 298975.0
11949
                                                                        1242.09
                                                                -0.00
         983.4
                 299546.5
                              1.16
                                             1.8
                                                    370.62
12039
                                                                        1239.52
                                                    369.24
                                                                -0.00
12119
         966.1
                 300086.7
                              1.14
                                             1.7
                                                                        1236.98
         949.5
                              1.12
                                             1.6
                                                    367.93
                                                                -0.00
12239
                 300595.6
                                             1.5
                                                    366.70
                                                                -0.00
                                                                        1234-45
         933.6
                 301073.3
                              1.10
1:2319
                                                                        1231.95
                                             1.5
                                                    365.55
                                                                -0.00
         918.5
                 301519.7
                              1.08
12419
                                                                        1229.47
                                                    364.48
                                                                -0.00
125:9
         904.3
                 301934.8
                              1.06
                                             1.4
                                                                -0.00
                                                                        1227.01
                                                    363.49
         890.9
                 302318.7
                              1.04
                                             1.3
126.9
                                                    362.60
                                                                -0.00
                                                                        1224.57
                                             1.3
12719
         878.5
                 302671.3
                              1.03
                                             1.2
                                                    361.77
                                                                -0.00
                                                                        1222.14
12819
         867.0
                 302992.7
                              1.01
                                                                -0.00
                                                                        1219.74
                                                    361.02
                                             1.2
12929
         856.4
                 303282.7
                              1.00
                                                    360.35
                                             1.2
                                                                -0.00
                                                                        1217.36
130.9
         846.9
                 303541.6
                              0.99
                              0.98
                                             1.1
                                                    359.77
                                                                -0.00
                                                                        1214.99
13119
         838.5
                 303769.2
                                                    359.26
                                                                -0.00
                                                                        1212.65
                              0.97
                                             1.1
13219
         831.1
                 303965.5
                                                                        1210.32
                                                    358.84
                                                                -0.00
                              0.96
                                             1.1
13329
         824.9
                 304130.5
                                                                        1208.01
                                                                -0.00
                                                    358.50
13449
         819.8
                 304264.3
                              0.95
                                             1.1
                                                                -0.00
                                                                        1205.72
                                                    358.23
                              0.95
                                             1.1
:13519
         815.9
                 304366.9
                                                    358.06
                                                                -0.00
                                                                        1203.44
                                             1.0
                 304438.2
                              0.94
136.9
         813.2
                                                                -0.00
                                                                        1201-19
                                                    357.95
         811.6
                              0.94
                                             1.0
13719
                 304478.2
                                                                -0.00
                                                                        1198.94
                                                    357.93
13819
         811.3
                 304487.0
                              0.94
                                             1.0
                                                    357:99
                                                                -0.00
                                                                        1196.72
                              0.94
                                             1.0
         812.2
                 304464.5
13919
                                                                -0.00
                                                                        1194.51
                                                    358.12
                 304410.8
                              0.95
                                             1.1
14049
         814.2
                                                                -0.00
                                                                        1192.32
                                             1.1
                                                    358.34
         817.5
                              0.95
14119
                 304325.8
```

CASE 2

MATERIAL CHARACTERISTICS

			V(H) =	0.0025 FT3				
A(W)	=	1.000	FT2	1(0)	=	505.000	DEG	R
C(W)	=	0.109	BTU/LB-DEG F	E(W)	=	0.550		
R	=	485.6C0	LB/FT3	L,	=	0.0025	FT	

X = 0.1040 FT

TIME	VEL	ALT	M	RN	T(R)	Q	T(W)
ITAE	VEL	ALI	••	13.14	, , , ,	(BTU)	
(SEC)	(FT/SEC)	(FT)			(DEG R)	FT2-SEC)	(DEG R)
0.	0.1	-0.	0.00	66.3	518.69	0.00	505.00
0.11	231.3	11.3	0.21	153395.7	522.65	0.04	505.00
0.2	470.0	45.7	0.42	311447.0	535.06	0.10	505.04
0.3	716.7	104.0	0.64	474272.4	556.76	0.21	505.14
0.4	971.4	186.9	0.87	641565.3	588.63	0.39	505.35
0.5	1234.4	295.3	1.11	813185.4	631.66	0.66	505.73
0 3 6	1506.0	429.9	1.35	988963.4	686.87	1.05	506.35
0.47	1786.3	591.6	1.60	1168562.6	755.35	9.13	509.48
018	2075.6	781.3	1.86	1351742.5	838.28	13.32	518.50
0.9	2374.0	999.9	2.13	1538097.2	936.86	18.75	530.42
1 4 0	2681.8	1248.2	2.41	1727319.1	1052.42	25.54	547.03
141	2999.2	1527.3	2.70	1918987.0	1186.35	33.86	569.35
1.2	3326.3	1838.0	3.00	2112591.5	1340.07	43.85	598.58
1.3	3663.4	2181.3	3.30	2307705.1	1515.16	55.68	636.05
I.4		2558.2	3.62	2503799.1	1713.26	69.47	683.17
1.5		2969.8	3.95	2700238.1	1936.00	85.36	741.49
1.6		3417.0	4.29	2896548.4	2185.34	103.46	812.62
1.7		3900.9	4.64	3092021.5	2463.10	123.88	898.27
1.8		4422.6	5.01	3286093.7	2771.46	146.72	1000.21
1.9		4752.8	5.23	3401186.7	2971.33	157.64	1116.07
1.19		4752.8	5.23	3401186.7	2971.33	157.64	1116.07

```
1858.10
                                                              58.15
                                     2803713.1
                                                 2686.20
                  1023348
                             5.04
 2.9
       5427.1
                                                                    2106.71
                            4.90
                                    2336747.9
                                                2468.52
                                                            21.20
 349
      5176.1
                15436.1
                                    1962718.2
                                                2296.77
                                                              6.53
                                                                    2164.14
                            4.80
                20415.6
 429
      4973.3
                                                2157.63
                                                                    2158.28
                                                            -0.03
                            4.73
                                    1657398.2
 549
                25213.4
      4806.5
                                                2042.42
                                                            -2.47
                                                                    2112.23
6.9
      4667.3
                29860.5
                            4.69
                                    1404460.1
                                                                    2054.96
                                                            -3.29
      4549.5
                            4.66
                                    1192441.0
                                                1945.11
                34380.6
 749
                                                                    2005.74
                                                1871.07
                                                            -0.60
                38792.7
                            4.59
                                     971854.1
 849
      4448.9
                                                1814.63
                                                            -0.64
                                                                    1974.25
                            4.50
                                     775079.7
      4363.3
                43112.5
 949
                                                                    1941.42
                                                            -0.63
                                                1766.59
                            4.43
                                     621967.0
1019
      4289.1
                47352.9
                                                                    1910.42
                                                            -0.60
                            4.36
                                                1724.92
      4223.7
                51523.9
                                     501696.8
1119
                                                                     1881.50
                                                            -0.56
                            4.30
                                     406491.1
                                                1688.20
1239
      4165.2
                 55633.0
                                     330619.9
                                                            -0.52
                                                                     1854.30
                            4.25
                                                1655.25
1349
      4112.0
                 59486.2
                                                                     1828.68
                                                1625.28
                                                            -0.48
                            4.19
                                     269823.8
                63688.1
1419
      4063.0
                                                                     1804.51
                                                1597.70
                                                             -0.44
                            4.15
                                     220879.3
                 67642.4
1519
      4017.4
                                                             -0.41
                                                                     1781.68
      3974.5
                 71552.2
                            4.10
                                     181310.3
                                                1572.05
16.9
                                                             -0.37
                                                                     1760.06
                            4.06
                                     149203.9
                                                1547.90
      3933.7
                 75419.6
17:9
                                                             -0.34
                                                                     1739.56
                                     123070.6
                                                1525.06
                            4.02
1819
      3894.7
                 79246.8
                                                             -0.31
                                                                     1720.08
                                                1504.37
                            3.98
                                     101221.4
1939
      3857.1
                 8303511
                                                             -0.28
                                                                     1701.56
                                                1489.64
                 86785.8
                            3.91
                                      81722.6
      3820.8
2019
                                                             -0.25
                                                                     1683.96
                 90500.0
                                      66326.8
                                                 1475.56
                            3.84
2119
      3785.4
                                                1461.99
                                                             -0.23
                                                                     1667.18
                                      54099.6
                 94178.6
                            3.78
2219
      3750.7
                                                                     1651-16
                                                 1448.99
                                                             -0.20
                                      44338.3
                            3.72
2319
      3716.8
                 97822.3
                                                             -0.19
                                                                     1635.83
                            3.66
                                                 1436.32
                101431-4
                                      36502.5
      3683.3
2419
                                                                     1621.13
                                                             -0.17
                                      30182.6
                                                 1424.04
                            3.60
                105006.7
2519
      3650.3
                                                                     1607.03
                                                 1412.02
                                                             -0.15
                            3.55
                                      25060.7
2619
      3617.6
                108548.3
                                                             -0.14
                                                                     1593.46
                                                 1400.28
                            3.49
                                      20891.3
                112056.6
27.9
       3585.2
                                                                     1580.40
                                                             -0.13
                                      17482.5
                                                 1388.73
               115531.8
                            3.44
2819
       3553.0
                                                                     1567.80
                                                             -0.12
                            3.39
                                      14684.6
                                                 1377.45
       3521.1
                118974.2
2919
                                                             -0.11
                                                                     1555-65
                                       12378.5
                                                 1366.32
                            3.33
       3489.3
                122383.8
3049
                                                                     1543.89
                                                 1355.38
                                                             -0.10
                                       10470.8
                            3.28
3119
       3457.7
                125761.0
                                                             -0.09
                                                                     1532.52
                                                 1344.59
                            3.24
                                        8886.7
       3426.2
                129105.7
3219
                                                                     1521.51
                                                             -0.09
                                                 1333.95
                            3.19
                                        7566.6
       3394.8
                132418.0
3329
                                                                     1510.84
                                                             -0.08
                                        6463.1
                                                 1323.50
                            3.14
34.9
       3363.6
                135698.2
                                                                     1500.48
                                                 1313.15
                                                             -0.08
                                        5537.1
                            3.09
                138946.2
3519
       3332.4
                                                             -0.07
                                                                     1490.42
                                        4757.9
                                                 1302.93
                            3.05
       3301.3
                142162.1
36:9
                                                                     1480.65
                                                             -0.07
                                        4099.9
                                                 1292.81
                            3.00
       3270.2
                145345.9
3719
                                                                     1471.14
                                                             -0.06
                            2.96
                                        3542.9
                                                 1282.87
                148497.8
3849
       3239.3
                                                                     1461.90
                                                             -0.06
                                        3069.8
                                                 1272.98
                            2.92
3949
       3208.3
                151617.7
                                                             -0.06
                                                                     1452.89
                                        2666.9
                                                 1263.27
                            2.88
40.9
       3177.5
                154705.7
                                                             -0.05
                                                                     1444.11
                                                 1249.73
                                        2354.8
       3146.7
                            2.84
                157761.9
4119
                                                                     1435.55
                                                 1235.30
                                                             -0.05
                                        2089.5
                160786.2
                            2.82
4219
       3115.9
                                                                     1427.18
                                                             -0.05
                                        1856.0
                                                 1221.05
                            2.79
                163778.7
43.9
       3085.2
                                                                     1419.01
                                                 1206.99
                                                             -0.05
                                        1650.6
                             2.76
4439
       3054.6
                166739.4
                                                             -0.05
                                                                     1411.03
                                                 1193.08
                            2.73
                                        1469.4
4529
       3024.0
                169668.3
                                                             -0.05
                                                                     1403.22
                                                 1179.30
                            2.71
                                        1309.6
       2993.4
                172565.4
4619
                                                             -0.05
                                                                     1395.59
                                        1169.2
                                                 1165.50
47.9
       2962.9
                175430.9
                             2.68
                                                                     1388.13
                                                             -0.05
                                        1069.9
                                                 1145.16
                             2.67
4819
       2932.4
                178264.6
                                                             -0.04
                                                                     1380.81
                                                 1125.05
                                         978.6
                181066.7
                             2.66
4939
       2901.9
                                                                     1373.64
                                                             -0.04
                                         894.9
                                                 1105.19
                             2.65
                183837.0
5019
       2871.5
```

				010.2	1005 AO	-0.04	1366.61
51.9		186575.7	2.64	818.2 747.8	1085.60	-0.04	1359.72
5249	2810.9	189282.7	2.63		1047.05	-0.04	1352.97
5349	2780.6	191958-1	2.62	683.2		-0.04	1346.35
5419	2750.4	194601.9	2.61	624.1	1028.15	-0.04	1339.85
5519	2720.2	197214.0	2.60	569.9	1009.45		1333.48
56.9	2690.0	199794.6	2.59	520.3	990.98	-0.04	1327.23
5719	2659.9	202343.6	2.58	474.9	972.75	-0.04	1321.10
5819	2629.9	204860.9	2.56	433.3	954.78	-0.04	
5949	2599.9	207346.7	2.55	395.3	937.02	-0.04	1315.08
6019	2569.9	209801-0	2.54	360.6	919.48	-0.04	1309.17
6119	2540.0	212223.6	2.53	328.8	902-18	-0.04	1303.37
6219	2510.1	214614.8	2.52	299.8	885.10	-0.03	1297.68
6319	2480.3	216974.4	2.50	273.3	868.27	-0.03	1292.08
6419	2450.5	21930245	2.49	249.0	851.64	-0.03	1286.58
6549	2420.8	221599.0	2.48	226.9	835.26	-0.03	1281.18
6619	2391.1	223864.1	2.46	206.7	819.09	-0.03	1275.88
6719	2361.5	226097.6	2.45	188.3	803-17	-0.03	1270.66
8819	2332.0	228299.7	2.44	171.5	787.49	-0.03	1265.54
6919	2302.5	230470.2	2.42	156.2	772.02	-0.03	1260.50
7019	2273.1	232609.3	2.41	142.3	756.78	-0.03	1255.54
7119	2243.7	234716.9	2.39	129.5	741.76	-0.02	1250.67
7219	2214.4	236793.1	2.38	117.9	726.97	-0.02	1245.87
7349	2185.1	238837.7	2.36	107.4	712.39	-0.02	1241.16
7419	2156.0	240851.0	2.35	97.8	698.08	-0.02	1236.52
7519	2126.9	242832.7	2.33	89.0	683.97	-0.02	1231.95
1649	2097.8	244783.1	2.32	81.0	670.07	-0.02	1227-45
7719	2068.9	246702:0	2.30	73.8	656.43	-0.02	1223.02
7819	2040.0	248589.5	2.28	67.2	642.99	-0.02	1218.66
7919	2011.2	250445.5	2.27	61.2	629.79	-0.02	1214.37
8019	1982.5	252270.2	2.25	55.7	616.81	-0.02	1210.14
8149	1953.9	254063.4	2.23	50.7	604.07	-0.02	1205.97
18249	1925.4	255825.2	2.21	46.2	591.55	-0.02	1201.86
8349	1897.0	257555.6	2.20	42.1	579.26	-0.01	1197.81
8429	1868.6	259254.6	2.18	38.4	567.16	-0.01	1193.82
8519	1840.4	260922-3	2.16	35.0	555.32	-0.01	1189.88
86.9	1812.3	262558.5	2.14	31.8	543.96	-0.01	1186.00
8719	1784.3	264163.4	2.11	28.4		-0.01	1182.18
88.19	1756.4	265736.9	2.07	25.4	529.03	-0.01	1178.40
8929	1728.6	267279.0	2.04	22.7	521.78	-0.01	1174.68
90.39	1701.0	268789.8	2-01	20.4	514.70	-0.01	1171.01
9149	1673.5	270269.2	1:98	18.3	507.76	-0.01	1167.38
9249	1646.2	271717.2	1.)4	16.5	500.98	-0.01	1163.80
93.9	1618.9	273133.9	1.91	14.9	494.31	-0.01	1160-27
9419	1591.9	274519.2	1.88	13.4	487.82	-0.01	1156.78
9519	1565.0	275873.2	1.85	12.2	481.46	-0.01	1153.34
9619	1538.3	277195.9	1.82	11.0	475.26	-0.01	1149.94
9739	1511.8	278487.2	1.79	10.0	469.22	-0.01	1146.58
98.9	1485.4	279747.2	1.75	9.1	463.29	-0.01	1143-26
9949	1459.3	280975.8	1.72	8.3	457.54	-0.01	1139.98
7747	F47303	20071710		=			

```
1136.74
                               1.69
                                              7.6
                                                     451.94
                                                                 -0.01
 100.9
         1433.4
                  282173.2
                                             6.9
                                                    446.45
                                                                -0.01
                                                                        1133.54
        1407.6
                 283339.2
                              1.66
101.9
                                                                -0.01
                 284473.9
                              1.63
                                             6.3
                                                    441.15
                                                                        1130.37
        1382.2
102.9
                              1.60
                                             5.8
                                                    435.96
                                                                -0.01
                                                                        1127.24
                 285577.3
        1356.9
103.9
                                                                -0.01
                                                                        1124.15
                              1.57
                                             5.4
                                                    430.95
10429
        1332.0
                 286649.3
                                                                -0.01
                                                                        1121.09
                              1.54
                                             4.9
10529
        1307.3
                 287690.1
                                                    426.08
                                                                -0.01
                                                                        1118:07
                 288699.6
                              1.51
                                             4.5
                                                    421.35
        1282.9
10629
                                             4.2
                                                                -0.00
                                                                        1115.08
                 289677.7
                              1.49
                                                    416.76
10739
        1258.8
                                                    412.32
                                                                -0.00
                                                                        1112.12
        1235.0
                 290624.6
                              1.46
                                             3.9
10819
                                                                -0.00
                                                                        1109.19
                 291540.1
                              1.43
                                             3.6
                                                    408.04
10939
        1211.6
        1188.6
                 292424.4
                              1.40
                                             3.4
                                                    403.91
                                                                -0.00
                                                                        1106.30
110.9
                              1.38
                                             3.1
                                                    349.91
                                                                -0.00
                                                                        1103.43
        1165.9
                 293277.4
11129
                              1.35
                                             2.9
                                                    396.05
                                                                -0.00
                                                                        1100.60
        1143.6
                 294099.1
112.19
11329
        1121.8
                 294889.5
                              1.32
                                             2.7
                                                     392.36
                                                                -0.00
                                                                        1097.80
                              1.30
                                             2.5
                                                     388.80
                                                                -0.00
                                                                        1095.02
11439
        1100.4
                 295648.6
                              1.27
                                             2.4
                                                     385.39
                                                                -0.00
                                                                        1092.27
        1079.5
                 296376.4
11529
                              1.25
                                             2.2
                                                     382.14
                                                                -0.00
                                                                        1089.56
11649
        1059.2
                 297073.0
                                                    379.02
                                                                -0.00
                              1.23
                                             2.1
                                                                        1086.86
11729
                 297738.3
        1039.3
                                                                -0.00
                                                                        1084.20
118.9
        1020.1
                 298372.3
                              1.20
                                             2.0
                                                     376.06
                                                                        1081.56
                              1.18
                                             1.9
                                                     373.23
                                                                -0.00
119.19
        1001.4
                 298975.0
                                                     370.62
                                                                -0.00
                                                                        1078.95
                 299546.5
                              1.16
                                             1.8
         983.4
120.9
                 300086.7
                              1.14
                                             1.7
                                                     369.24
                                                                -0.00
                                                                        1076.36
121.9
         966.1
                                                                -0.00
                                                                        1073.80
                                             1.6
                                                     367.93
122.19
         949.5
                 300595.6
                              1.12
                              1.10
                                             1.5
                                                     366.70
                                                                -0.00
                                                                        1071.27
123.9
         933.6
                 301073-3
                                                     365.55
                                                                -0.00
                                                                        1068.75
         918.5
                 301519.7
                              1.08
                                             1.5
12429
                                                                -0.00
                                                                        1066.26
                                             1.4
                                                     364.48
         904.3
                              1.06
12529
                 301934.8
                                                     363.49
                                                                -0.00
                                                                        1063.80
126.9
         890.9
                 302318.7
                              1.04
                                              1.3
                                                                -0.00
                                                                        1061.36
         878.5
                 302671.3
                              1.03
                                             1.3
                                                     362.60
12729
                                                     361.77
                                                                -0.00
                                                                        1058.93
                                             1.2
         867.0
                              1.01
128-9
                 302492.7
                                                     361.02
                                                                -0.00
                                                                        1056.54
                 303282.7
                              1.00
                                              1.2
129:9
         856.4
                                                                        1054-16
                                                     360.35
                                                                -0.00
130.9
         846.9
                 303541.6
                              0.99
                                              1.2
                                                     359.77
                                                                -0.00
                                                                        1051.80
         838.5
                              0.98
                                              1.1
131.9
                 303769.2
                              0.97
                                              1.1
                                                     359.26
                                                                -0.00
                                                                        1049-47
         831.1
                 303965.5
132-9
                                                                -0.00
                                                                        1047.16
                                                     358.84
         824.9
                  304130.5
                              0.96
                                              1.1
133.9
                                                     358.50
                                                                -0.00
                                                                        1044.86
                              0.95
                                              1.1
13429
         819.8
                  304264.3
                                                                -0.00
                                                                        1042.59
         815.9
                 304366.9
                              0.95
                                              1.1
                                                     358.23
13529
                                                     358.06
                                                                -0.00
                                                                        1040.34
                                              1.0
136.9
         813.2
                 304438.2
                              0.94
                                                     357.95
                                                                -0.00
                                                                        1038-10
                                              1.0
         811.6
                  304478.2
                              U.94
137-9
                                                                -0.00
                                                                        1035.89
                              0.94
                                              1.0
                                                     357.93
13829
         811.3
                  304487.0
                                                     357.99
                                                                -0.00
                                                                        1033.69
         817.2
                  304464.5
                              0.94
                                              1.0
139.9
                              0.95
                                              1.1
                                                     358.12
                                                                -0.00
                                                                         1031.51
         814.2
                  304410.8
140.9
                                                                         1029.35
                                                     358.34
                                                                -0.00
                              0.95
                                              1.1
141.9
         817.5
                  304325.8
```

CASE 3

MATERIAL CHARACTERISTICS

V(w) = 000.0042 FT3	FT3	042	1 : 1	=000	(🖼)	V
---------------------	-----	-----	-------	------	-------	---

A(W)	=	1.000	FT2		1(0)	=	505.000	DEG	R
C (.W.)	=	0.109	BTU/L8-DEG	F	E(W)	=	0.550		
R	=	485.600	LB/FT3		L	=	0.0042	FT	

X = 0.1040 FT

TIME (SEC)	VEL (FT/SEC)	ALT (FT)	۲	RN	T(R) (DEG R)	Q (BTU/ FT2-SEC)	I(W)
1.2501	(FIF3EG)	(11)			(DEO N)	112 3601	(OLO IN)
.04	0.1	-0.	0.00	66.3	518.69	0.00	505.00
0.1	231.3	11.3	0.21	153395.7	522.65	0.04	505.00
0.2	470.0	45.7	0.42	311447.0	535.06	0.10	505.03
043	716.7	104-0	0.64	474272.4	556.76	0.21	505.08
	971.4	186.9	0.87	641565.3	588.63	0.39	505.21
044				813185.4	631.66	0.66	505.43
0.5	1234.4	295.3	1.11			1.05	505.81
016	1506.0	429.9	1.35	988963.4	686.87		
0.7	1786.3	591.6	1.60	1168562.6	755.35	9.19	507.68
0.48	2075.6	781.3	1.86	1351742.5	838.28	13.54	513.12
0.29	2374.0	999.9	2.13	1538097.2	936.86	19.21	520.36
1.0	2681.8	1248.2	2.41	1727319.1	1052.42	26.37	530.53
1.1	2999.2	1527.3	2.70	1918987.0	1186.35	35.23	544.31
1:2	3326.3	1838.0	3.00	2112591.5	1340.07	45.99	562.49
1.3	3663.4	2181.3	3.30	2307705.1	1515.16	58.85	585.98
1.4	4010.7	2558.2	3.62	2503799.1	1713.26	74.02	615.76
1.5		2969.8	3.95	2700238.1	1936.00	91.69	652.91
1.46	4736.6	3417.0	4.29	2896548.4	2185.34	112.05	698.61
1.7		3900.9	4.64	3092021.5	2463.10	135.29	754.10
1.8		4422.6	5.01	3286093.7	2771.46	161.59	820.71
		4752.8	5.23	3401186.7	2971.33	176.23	897.30
1:9				3401186.7	2971.33	176.23	897.30
1.9	5744.8	4752.8	5.23	3401100.1	27110JJ	110027	071470

2.9	5427.1	10233.€	5.04	2803713.1		86.02	1461-27
3.9	5176.1	15436.1	4.90	2336747.9	2468.52	43.04	1733.85
4.9	4973.3	20415.6	4.80	1962718.2	2296.77	21.40	1862.14
5.9	4806.5	25213.4	4.73	1657398.2	2157.63	9.96	1918.47
6.9	4667.3	29860.5	4.69	1404460.1	2042.42	3.84	1933.59
7.9	4549.5	34380.6	4.66	1192441.0	1945.11	0.53	1927.37
8.9	4448.9	38792.7	4.59	971854.1	1871.07	-0.18	1911.93
9.49	4363.3	43112.5	4.50	775079.7	1814.63	-0.33	1896.05
10.9	4289.1	47352.9	4.43	621967.0	1766.59	-0.41	1880.15
1129	4223.7	51523.9	4.36	501696.8	1724.92	-0.45	1864.33
12.9	4165.2	55633.0	4.30	406491.1	1688.20	-0.47	1848.84
1349	4112.0	59686.2	4.25	330619.9	1655.25	-0.47	1833.74
14.9	4063.0	63688.1	4.19	269823.8	1625.28	-0.46	1819.08
15.9	4017.4	67642.4	4.15	220879.3	1597.70	-(1.44	1804.86
1619	3974.5	71552.2	4.10	181310.3	1572.05	-0.42	1791.10
1749	3933.7	75419.6	4.06	149203.9	1547.90	-0.40	1777.77
18:9	3894.7	79246.8	4.02	123070.6	1525.06	-0.38	1764.87
19.9	3,857.1	83035.1	3.98	101221.4	1504.37	-0.36	1752.39
2019	3820.8	86785.8	3.91	81722.6	1489.64	-0.33	1740.31
21.9	3785.4	90500.0	3.84	66326.8	1475.56	-0.31	1728.65
22.19	3750.7	94178.6	3.78	54099.6	1461.99	-0.28	1717.36
23.9	3716.8	97822.3	3.72	44338.3	1448.99	-0.26	1706.43
24.9	3683.3	101431.4	3.66	36502.5	1436.32	-0.24	1695.84
2529	3650.3	105006.7	3.60	30182.6	1424.04	-0.22	1685.55
26.9	3617.6	108548.3	3.55	25060.7	1412.02	-0.21	1675.57
27.9	3585.2	112056.6	3.49	20891.3	1400.28	-0.19	1665.86
2849	3553.0	115531.8	3.44	17482.5	1388.73	-0.18	1656.41
2919	3521.1	118974.2	3.39	14684.6	1377.45	-0.17	1647.21
3049	3489.3	122383.8	3.33	12378.5	1366.32	-0.16	1638.25
3149	3457.7	125761.0	3.28	10470.8	1355.38	-0.15	1629.51
3249	3426.2	129105.7	3.24	8886.7	1344.59	-0.14	1620.98
3319	3394.8	132418.0	3.19	7566.6	1333.95	-0.13	1612.65
3419	3363.6	135698.2	3.14	6463.1	1323.50	-0.12	1604.51
35.9	3332.4	138946.2	3.09	5537.1	1313.15	-0.12	1596.56
36.9	3301.3	142162.1	3.05	4757.9	1302.93	-0.11	1588.78
3749	3270.2	145345.9	3.00	4099.9	1292.81	-0.10	1581.17
3849	3239.3	148497.8	2.96	3542.9	1282.87	-0.10	1573.71
39.9	3208.3	151617.7	2.92	3069.8	1272.98	-0.09	1566.42
4019	3177.5	154705.7	2.88	2666.9	1263.27	-0.09	1559.27
41.9	3146.7	157761.9	2.84	2354.8	1249.73	-0.08	1552.26
42.9	3115.9	160786.2	2.82	2089.5	1235.30	-0.08	1545.38
4339	3085.2	163778.7	2.79	1856.0	1221.05	-0.08	1538.63
4449	3054.6	166739.4	2.76	1650.6	1206.99	-0.08	1532.00
4519	3024.0	169668.3	2.73	1469.4	1193.08	-0.07	1525.49
4639	2993.4	172565.4	2.71	1309.6	1179.30	-0.07	1519.09
47.9	2962.9	175430.9	2.68	1169.2	1165.50	-0.07	1512.81
4819	2932.4	178264.6	2.67	1069.9	1145.16	-0.07	1506.63
4929	2901.9	181066.7	2.66	978.6	1125.05	-0.07	1500.55
		183837.0	2.65	894.9	1105.19	-0.06	1494.57
5049	2871.5	T07021*A	C • 0)	07707	LIUJOLI	J-00	_

```
-0.06
                                                                     1488.69
                              2.64
                                          818.2 1085.60
        2841.2
                 186575.7
 51.9
                                         747.8
                                                 1066.22
                                                             -0.06
                                                                     1482.90
       2810.9
                189282.7
                            2.63
52.9
                                                             -0.06
                                                                     1477.20
                                                 1047.05
                            2.62
                                         683.2
53.49
       2780.6
                191958.1
                                                             -0.06
                                                                     1471.59
                                         624.1
                                                 1028.15
5429
       2750.4
                194601.9
                            2:61
                                                                     1466.07
                                         569.9
                                                 1009.45
                                                             -0.06
                            2.60
55.9
       2720.2
                197214.0
                                                                     1460.64
                            2.59
                                                  990.98
                                                             -0.06
                                         520.3
                199794.6
5649
       2690.0
                                                  972:75
                                                             -0.05
                                                                     1455.28
                                         474.9
                            2.58
5749
       2659.9
                202343.6
                                                                     1450.01
                                                  954.78
                                                             -0.05
                             2.56
                                         433.3
5849
       2629.9
                204860.9
                                                                     1444.82
                                                  937.02
                                                             -0.05
                             2.55
                                         395.3
                207346.7
59.9
       2599.9
                                                             -0.05
                                                                     1439.71
                                         360.6
                                                  919.48
                             2.54
                2098C1.0
6019
       2569.9
                                                             -0.05
                                                                     1434.67
                             2.53
                                         328.8
                                                  902.18
                212223.6
6119
       2540.0
                                                                     1429.71
                                                             -0.05
                                         299.8
                                                  885.10
                             2.52
                214614.8
62.9
       2510.1
                                                                      1424.81
                                                             -0:04
                                         273.3
                                                  868.27
                             2.50
                216974.4
6319
       2480.3
                                                                      1419.99
                                                             -0:04
                                         249,0
                                                  851.64
                             2.49
       2450.5
                219302.5
6419
                                                             -0.04
                                         226.9
                                                  835.26
                                                                      1415.24
                             2.48
                221599.0
6549
       2420.8
                                                             -0.04
                                                                      1410.56
                                         206.7
                                                  819.09
                             2.46
6619
       2391.1
                223864.1
                                                              -0.04
                                                                     1405.94
                                         188.3
                                                  803:17
                226097.6
                             2.45
6719
       2361.5
                                                              -0.04
                                                                      1401.39
                                         171.5
                                                  787.49
                             2.44
                228299.7
6819
       2332.0
                                                                      1396.90
                                         156.2
                                                  772:02
                                                              -0.03
                             2.42
       2302.5
                230470.2
6919
                                                              -0.03
                                                                      1392.47
                                         142.3
                                                  756.78
                             2.41
7049
       2273.1
                232609.3
                                                              -0.03
                                                                      1388.10
                                         129.5
                                                  741.76
                             2.39
       2243.7
7119
                234716.9
                                                                      1383.79
                                         117.9
                                                              -0.03
                             2.38
                                                  726.97
7219
       2214-4
                236793.1
                                                              -0.03
                                                                      1379.54
                             2.36
                                         107.4
                                                  712.39
                238837.7
       2185.1
7319
                                                  698.08
                                                              -0.03
                                                                      1375.34
                                           97.8
                             2.35
7419
       2156.0
                240851.0
                                                                      1371.20
                                           89.0
                                                  683.97
                                                              -0.03
                             2.33
7519
       2126.9
                242832.7
                                                                      1367.11
                                                              -0.02
                                                  670.07
                             2.32
                                           81.0
       2097.8
                244783.1
7619
                                           73.8
                                                  656.43
                                                              -0.02
                                                                      1363.08
                             2.30
                246702.0
7719
       2068.9
                                                              -0.02
                                                                      1359.09
                                           67.2
                                                  642.99
                             2.28
7839
       2040.0
                248589.5
                                                                      1355.16
                                                              -0.02
                                           61.2
                                                   629.79
       2011.2
                250445.5
                             2.27
7939
                                                                      1351.27
                                                              -0.02
                             2.25
                                           55.7
                                                   616.81
                252270.2
       1982.5
80.9
                                                                      1347.43
                                                              -0.02
                                           50.7
                                                   604.07
                             2:23
                254063.4
8119
       1953.9
                                                   591.55
                                                              -0.02
                                                                      1343.64
                                           46.2
                255825.2
                             2.21
8249
       1925.4
                                                   579.26
                                                              -0.02
                                                                      1339.89
                                           42.1
                             2:20
                257555.6
       1897.0
8349
                                                                      1336.19
                                                              -0.02
                             2.18
                                           38.4
                                                   567.16
84:9
       1868.6.
                259254.6
                                                              -0:02
                                                                      1332.53
                                           35.0
                                                   555.32
                260922-3
                             2.16
8519
       1840.4
                                                                      1328.92
                                                   543.96
                                                              -0.02
                                           31.8
                             2.14
       1812.3
                262558.5
86.39
                                                              -0.01
                                                                      1325.34
                                           28.4
                                                   536.43
                             2.11
8719
       1784.3
                264163.4
                                                              -0.01
                                                                      1321.81
                                                   529.03
                             2.07
                                           25.4
                 265736:9
8819
       1756.4
                                                              -0.01
                                                                      1318.31
                                           22.7
                                                   521.78
                             2.04
8949
       1728.6
                 267279.0
                                                              -0.01
                                                                      1314.86
                             2.01.
                                                   514.70
                                           20.4
9019
       1701.0
                 268789.8
                                                              -0.01
                                                                      1311-44
                                                   507.76
                                           18.3
                 270269-2
                             1.98
       1673.5
9139
                                                                      1308.06
                                                              -0.01
                                                   500.98
                             1.94
                                           16.5
                 271717.2
9219
        1646.2
                                                              -0.01
                                                                      1304.72
                                           14.9
                                                   494.31
                             1.91
                 273133.9
 9339
        1618.9
                                                                      1301:41
                                                   487.82
                                                              -0:01
                                           13.4
                             1.88
9439
        1591.9
                 274519.2
                                                              -0.01
                                                                      1298.14
                                                   481.46
                             1.85
                                           12.2
        1565.0
                 275873.2
 9519
                                                              -0.01
                                                                      1294.90
                                                   475.26
                                           11.0
                             1.82
                 277195.9
        1538.3
 9619
                                                                      1291.70
                                                              -0.01
                                                   469.22
                                           10.0
                 278487.2
                             1.79
 9749
        1511.8
                                                                      1288.52
                                            9.1
                                                              -0.01
                                                   463.29
                             1.75
                 279747.2
 9839
        1485.4
                                                              -0.01
                                                                      1285.38
                                                   457.54
                                            8:3
                 280975.8
                             1.72
 9919
        1459.3
```

```
-0.01
                                                                        1282.28
                                                    451.94
                                             7.6
                              1.69
                  282173.2
100.9
        1433.4
                                                                       1279.20
                                                               -0.01
                                                   446.45
                                            6.9
                             1.66
       1407.6
                 283339.2
10149
                                                               -0.01
                                                                       1276.15
                                            6.3
                                                   441.15
                             1.63
10219
                 284473.9
       1382.2
                                                               -0.01
                                                                       1273.14
                                                   435.96
                                            5.8
                             1.60
       1356.9
                 285577.3
10339
                                                                       1270.15
                                                               -0.01
                             1.57
                                            5.4
                                                   430.95
                 286649.3
104.9
       1332.0
                                                                       1267.19
                                            4.9
                                                   426.08
                                                               -0.01
                             1.54
                 287690.1
10519
       1307.3
                                                                       1264.26
                                                               -0.01
                                                   421.35
                                            4.5
                 288699.6
                             1.51
        1282.9
10619
                                                               -0.01
                                                                       1261.36
                                            4.2
                                                   416.76
                             1.49
                 289677.7
        1258.8
10729
                                                               -0.01
                                                                       1258.48
                                            3.9
                                                   412.32
                              1.46
                 290624.6
        1235.0
10819
                                                                       1255.63
                                                               -0.01
                                                   408.04
                                            3.6
                              1.43
                 291540.1
        1211.6
10939
                                                                       1252.81
                                                   403.91
                                                               -0.01
                                            3.4
                              1.40
                 292424.4
        1188.6
11039
                                                               -0.01
                                                                       1250.01
                                                    399.91
                                             3.1
                              1.38
                 293277.4
        1165.9
11129
                                                                       1247.24
                                                               -0.01
                                                    396.05
                             1.35
                                             2.9
                 294099.1
        1143.6
11219
                                                                       1244.49
                                             2.7
                                                    392.36
                                                               -0.00
                              1.32
                 294889.5
11349
        1121.8
                                                                       1241.77
                                                               -0.00
                                                    388.80
                                             2.5
                              1.30
        1100.4
                 295648.6
F1449
                                                               -0.00
                                                                       1239.08
                                                    385.39
                                             2.4
                              1.27
                 296376.4
        1079.5
11529
                                                               -0.00
                                                                       1236.40
                                             2.2
                                                    382.14
                              1.25
        1059.2
                 297073.0
11619
                                                                       1233.75
                                                               -0.00
                                                    379.02
                                             2.1
                              1.23
                 297738.3
117.9
        1039.3
                                                                       1231.12
                                                               -0.00
                                                    376.06
                              1.20
                                             2.0
        1020.1
                 298372.3
11819
                                                                       1228.52
                                                    373.23
                                                               -0.00
                                             1.9
                 298975.0
                              1.18
        1001.4
119.9
                                                               -0.00
                                                                       1225.94
                                                    370.62
                                             1.8
                              1.16
                 299546.5
         983.4
12029
                                                                       1223.37
                                                               -0.00
                                             1.7
                                                    369.24
                              1.14
                 300086.7
12139
         966.1
                                                                       1220.83
                                                               -0.00
                              1.12
                                                    367.93
                                             1.6
                 300595.6
         949.5
12219
                                                                       1218.32
                                                               -0.00
                                             1.5
                                                    366.70
                              1.10
                 301073.3
         933.6
12319
                                                               -0.00
                                                                        1215.82
                                                    365.55
                                             1.5
                              1.08
                  301519.7
         918.5
F2419
                                                                        1213.34
                                                               -0.00
                                                    364.48
                                             1.4
                              1.06
         904.3
                  301934.8
125.9
                                                               -0.00
                                                                        1210-89
                                             1.3
                                                    363.49
                              1.04
                  302318.7
1.26:9
         890.9
                                                                        1208-45
                                                               -0.00
                                             1.3
                                                    362.60
                              1.03
         878.5
                  302671.3
12719
                                                                        1206.03
                                                               -0.00
                                             1.2
                                                    361.77
                  302992.7
                              1.01
         867.0
12819
                                                                        1203.64
                                                    361.02
                                                               -0.00
                                             1.2
                              1.00
         856.4
                  303282.7
12939
                                                                        1201.26
                                                               -0.00
                                                    360.35
                                             1.2
                              0.99
                 303541.6
13049
         846.9
                                                                        1198.90
                                                               -0.00
                                             1.1
                                                    359.77
                              0.98
         838.5
                  303769.2
13119
                                                    359.26
                                                               -0.00
                                                                        1196.56
                                             1.1
                              0.97
         831.1
                  303965.5
13219
                                                                        1194.23
                                                               -0.00
                                                    358.84
                              0.96
                                             1.1
                  304130.5
          824.9
13349
                                                                        1191.93
                                                    358.50
                                                               -0.00
                                             1.1
                              0.95
                  304264.3
13419
          819.8
                                                                        1189.64
                                                                -0.00
                                             1.1
                                                    358.23
                              0.95
          815.9
                  304366.9
13519
                                                                        1187.37
                                                                -0.00
                                                    358.06
                                             1.0
                              0.94
          813.2
                  304438.2
 13619
                                                                -0.00
                                                                        1185.12
                                                    357.95
                                              1.0
                               0.94
          811.6
                  304478.2
 13729
                                                                        1182.88
                                                    357,93
                                                                -0.00
                                              1.0
                               0.94
                  304487.0
 13849
          811.3
                                                                        1180.67
                                                     357.99
                                                                -0.00
                                              1.0
                               0.94
          812.2
                  304464.5
 13919
                                                                        1178.46
                                                                -0.00
                                                     358.12
                                              1.1
                               0.95
          814.2
                  304410.8
 14019
                                                                        1176.28
                                                                -0.00
                                                     358.34
                                              1.1
                               0.95
          817.5
                  304325.8
 141:9
```

MATERIAL CHARACTERISTICS

V(W) = C.017C FT3 T(O) = 505.000 DEG, R E(W) = 0.350 L = C.0170 FT = 1.000 FT2 = 0.109 BTU/LB-DEG F = 485.500 LB/FT3

X = 0.5026 FT

TIME	VEL	ALT	۳	RN	T(R)	Q 487144	T(W)
4 SECS	IETISECS	(FT)			(DEG R)	(8TU/	/ DCC - D.
6-	(FT/SEC)	-0-	C.00	320.6	518.69	FT2-SEC) 0.00	(DEG R) 505-00
0.1	231.3	11.3	0.21	741314.4	522.65	0.06	505.00
0.2	470.C	45.7	C.42	1505127.3	535.06	0.65	505.04
0.3	716.7	104-0	0.64	2292012.4	556.76	1.56	505.16
0.4	971.4	186.9	C.87	3100487.9	588.63	3.20	505.41
0.5	1234.4	295.3	1.41	3929875.C	631.66	5.84	505.91
0.6	1506.C	429.9	1.35	4779356.1	686.87	9.78	506.76
9.7	1786.3	591.6	1.60	5647303.3	755.35	15.32	508-14
9.0	2075.6	781.3	1.86	6532555.7	838.28	22.81	510.23
0.9	2374.C	999.9	2.13	743315C.8	936.86	32.62	513.29
1.C	2681.8	1248.2	2.41	8347602.0	1052-42	45.12	517.58
1.1	2999.2	1527.3	2.70	9273873.9	1186.35	60.73	523.44
1.2	3326.3	1838.C	3.0C	10209504.7	1340.07	79.81	531.21
1.3	3663.4	2181.3	3.30	11152428.7	1515.16	102.97	541.34
1.4	4010.7	2558.2	3.62	12100090.9	1713.26	130.50	554.27
1.5	4368.3	2969.8	3.95	13049419.9	1936.00	162.90	570.53
1.6	4736.6	3417.C	4.29	13998127.2	2185.34	200.65	590.68
1.7	5115.7	3900-9	4.64	14942788.5	2463.1C	244.21	615.34
1.8	5506.C	4422.6	5.01	15880679.6	2771.46	294.06	645.20
1.9	5744.8	4752-8	5.23	16436889.2	2971.33	325.06	679.89
1.9	5744.8	4752.8	5.23	16436885.2	2971.33	325.06	679.89
2.9	5427.1	10233.8	5.04	13549482.7	2686.2C	201.52	967.35
3.9	5176.1	15436.1	4-90	11292783.5	2468.52	129.14	1148.19
4.9	4973.3	20415.6	4.80	9485213.0	2296.77	84.79	1265-15
5.9	48C6.5	25213.4	4.73	8CC9695.6	2157.63	56.66	1342-44
6.9	4667.3	2586C.5	4.69	6787323.5	2042.42	38.23	1394.01
7.9	4549.5	3438C.6	4.66	576270C.7	1945.11	25.82	1428.53
8.9	4448.9	38792.7	4.59	4696671.6	1871.07	17.52	1451.58
9.5	4363.3	43112.5	4.5C	3745721.8	1814-63	12.11	1467.03
10.5	4289.1	47352.9	4.43	3CG5775.2	1766.59	8.45	1477.52
11.9	4223.7	51523.9	4.36	2424546.5	1724.92	5.91	1484.57
12.9	4165.2	55633.C	4.30	1964446.6	1688.20	4-14	1489.23
13.9	4112.C	59686.2	4.25	1597784.2	1655.25	2.87	1492-22
14.5	4063.C	63688.1	4.19	1303975.3	1625.28	1.97	1494.00
15.9	4017.4	67642.4	4-15	1067441.5	1597.70	1.31	1494.91
16.9	3974.5	71552.2	4.10	876216.7	1572.05	0.23	1494.96
17.9	3933.7	75419.6	4.C6	721056.4	1547.90	0.15	1494-13
18.9	3894.7	79246.8	4.02	594762.2	1525.06	0.08	1493.41
19.9	3857.1	83035.1	3.98	489171.9			1492.58
20.9	3820.8	86785.8	3.91	39494C.C	1489-64	-0.00	1491.71
21.9	3785.4	9C5CC.C	3.84	320537.2	1475.56	-0.03	1490-82
22.9	3750.7	94178.6	3.78	261446.5	1461.99	-0.05	1489.89
23.9	3716.8	97822.3	3.72	214273-2	1448-99	-0.06	1488.96
24.5	3683.3	101431.4	3.66	176405.5	1436.32	-0.C8	1488-G1
25.9	3650.3	1C5CC6.7	3.60	145863.2	1424.04	-0-08	1487.05
26.9	3617.6	108548.3	3.55	121110-6	1412.02	-0.09	1486.08
27.9	3585.2	112056.6	3.49	100961.3	1400-28	-0.10	1485.11
28 - 9	3553.C	115531.8	3.44	84487.7	1388.73	-0.1C	1484.13
29.9	3521.1	118974.2	3.39	70966.4	1377.45	-0.10	1483.16
30.9	3489.3	122383.8	3.33	59821.6	1366.32	-0.11	1482-18

				E0400:1	1266 26	. 6 11	1401 21
31.9	3457.7	125761.0	3.28	50602-1	1355.38	-0.11	1481.21
32 - 9	3426.2	129105.7	3.24	42946.5	1344.59	-0.11	1480-24
33.9	3394.8	132418-0	3.19	36567.2	1333.95	-0-11	1479.27
34.9	3363.6	135698-2	3.14	31234.0	1323.50	-0.11	1478.30
35.9	3332.4	138946.2	3.09	26759.2	1313.15	-0.11	1477.33
	3301.3	142162.1	3.05	22993.3	1302-93	-0-10	1476.37
36.9						-0.10	1475.41
37.9	3270.2	145345.9	3.00	19813.7	1292.81		
38.9	3239.3	146497-8	2.96	17121-9	1282.87	-0.10	1474.46
39.9	3208.3	151617.7	2.92	14835.2	1272.98	-0.10	1473-51
40.9	3177.5	154705.7	2.88	12888-3	1263.27	-0.10	1472.56
41.9	3146.7	157761.9	2.84	1138C.2	1249.73	-0.10	1471-62
42.9	3115.9	160786.2	2.82	10097.7	1235.30	-0.10	1470-68
		163778.7	2.79	8969.7	1221.05	-0.10	1469.74
43.9	3085.2					-0.10	1468.80
44.9	3054.6	166739.4	2.76	7976.7	1206.99		
45 . 9	30/24-0	165668.3	2.73	7101-2	1193.08	-0.10	1467.87
46.3	2993.4	172565.4	2.71	6328.7	1179.30	-0.09	1466.94
47.9	2962.9	175430.9	2.68	565C.6	1165.50	-0.09	1466.01
48.9	2932.4	178264.6	2.67	5170.4	1145.16	-0.09	1465.09
	2901.9	181066.7	2.66	4729.4	1125.05	-0.C9	1464.17
49.9					1105.19	-0.09	1463.25
50.9	2871.5	183837.0	2.65	4324.9			1462.33
51.9	2841.2	186575.7	2.64	3953.9	1085.60	-0.09	
52.9	2810.9	189282.7	2.63	3613.6	1066.22	-0.09	1461.41
53.9	2786.6	191958.1	2.62	3301.7	1047.05	-0.09	1460.50
54.9	2750.4	1946C1.9	2.61	3015.9	1028-15	-0.09	1459.60
	2720.2	197214.0	2.60	2754-1	1009.45	-0.09	1458-69
55.9				2514.3	990.98	-0.09	1457.79
56 . 9	2690-0	199794.6	2.59				1456.89
57.9	2659.9		2.58	2294.9	972.75	+0.08	
58.9	2629.9	204860.9	2.56	2094.2	954.78	-0.08	1456-00
59.9	2599.9	207346.7	2.55	1910.5	937.02	-0-08	1455.11
60.5	2569.9	209801-0	2.54	1742.5	919.48	-0.08	1454-23
61.9	2540.C	212223.6	2.53	1589.0	902-18	-0.08	1453.35
	2510.1	214614.8	2.52	1448.7	885-10	-0.C7	1452.47
82.9					868-27	-0.07	1451.60
63.9	2480.3	216974.4	2.50	1320-6			1450.73
84. 9	2450.5	219302.5	2.49	1203.5	851-64	-0.07	
45.9	2420.8	221599.0	2.48	1096.7	835.26	-0.C7	1449.87
66.9	2391.1	223864.1	2.46	999.1	819.09	-0.07	1449.01
67.5	2361.5	226097.6	2.45	910.2	803-17	-0.06	1448.16
68.9	2332.0	228299.7	2.44	829.0	787.49	-0.06	1447.31
			2.42	755.C	772.02	-0.C6	1446-46
69.9	2302.5	23C47C-2				-0.C6	1445-62
70.9	2273.1	232609.3	2.41	687.5	756.78		
71.9	2243.7	234716-9	2.39	626.0	741.76	-0.05	1444-79
72.9	2214.4	236793.1	2.38	57C.O	726.97	-0.05	1443.95
73.9	2185.1	238837.7	2.36	519.0	712.39	-0.05	1443-13
74.9	2156.C	240851-0	2.35	472.5	698.08	-0.05	1442.30
		242832-7	. 2.33	43C-2	683.97	-0.05	1441-48
.75 . 9	2126.9			391.6	670-07	-0.04	1440-67
76.9	2097.8	244783.1	2.32		656.43	-0.04	1439.85
77.9	2668.9	246702-C	2.30	356.6			
78.9	2040.0	248589.5	2.28	324.6	642.99	-0.C4	1439.05
79.9	2011.2	25C445.5	2.27	295.6	629.79	-0.04	1438-24
80.9	1982.5	252270.2	2.25	269.2	616.81	-0.04	1437.44
81.9	1953.9	254063.4	2.23	245.2	604.07	-0.03	1436-64
			2.21	223.3	591.55	-0.03	1435-85
82.9	1925.4	255825.2		203.5	579.26	-0.03	1435.06
83.9	1897.C	257555.6	2.20			-0.03	1434.27
84.5	1868.6	259254.6	2.18	185.4	567.16		
85.9	1840.4	260922.3	2.16	169.0	555.32	-0.03	1433.49
86.9	1812.3	262558.5	2.14	153.8	543.96	-0.C3	1432-70
87.9	1784.3	264163-4	2.11	137.3	536.43	-0.03	1431.93
88.9	1756.4	265736.9	2.07	122.7	529.03	-0.02	1431.15
		267279-C	2.04	109.9	521.78	-0.02	1430.38
89.9	1728.6			98.5	514.7C	-0.02	1429.61
90.9	17C1.C	276 6 7 8 9 . 8	2.01			-0.02	1428.84
91.9	1673.5	270269-2	1.98	88.6	507.76		
92.9	1646.2	27:1717.2	1.94	79.7	500.98	-0.02	1428.08
93.9	1618-9	273133.9	1.91	71.9	494-31	-0.02	1427-32
94.9	1591.9	274519.2	1.88	64.9	487.82	-0-02	1426-56
95.5	1565.0	275873.2	1.85	58.8	481.46	-0.02	1425.80
			1.82	53.3	475.26	-0.02	1425-05
96.9	1538.3	277195.9	1.02		,,,,,,		

```
-0202
                                                                        1424-30
                                                    469.22
                                            48.4
                              1.79
 97.9
        1511.8
                 278487-2
                                                                        1423-55
                                                                -0.02
                                                    463.29
                              1.75
                                            44.0
                 279747-2
 98.9
        1485.4
                                                                -0:02
                                                                        1422-80
                                                    457.54
        1459.3
                              1.72
                                            40.1
                  280975.8
 99.9
                                                                        1422-06
                                            36.6
                                                    451.94
                                                                -0.01
        1433.4
                  282173-2
                              1.69
100 .9
                                                                -0.01
                                                                        1421-32
                                            33.5
                                                    446.45
                              1.66
                  283339-2
101.49
        1407.6
                                                                        1420-58
                                                    441-15
                                                                -0.01
                                            30.7
102:9
        1382.2
                  284473.9
                              1.63
                                                                        1419.84
                                            28.1
                                                    435.96
                                                                -0.01
                  285577.3
                              1.60
103.9
        1356.9
                                                                        1419-10
                              1.57
                                            25.9
                                                    430.95
                                                                -0.01
                  286649.3
104.9
        1332.0
                                            23.8
                                                    426-08
                                                                -0.01
                                                                        1418-37
                              1.54
        1307.3
                  28769C-1
105.9
                                                                -0.01
                                                                        1417.64
                                            22.0
                                                    421.35
                  288699-6
                              1.51
106.9
        1282.9
                                                                -0.01
                                                                        1416.91
                                                    416.76
                                            20.3
                  289677.7
                              1.49
        1258.8
107.9
                                                                        1416-18
                                                                -0.01
                                            18.8
                                                    412.32
                              1.46
108.39
        1235.0
                  290624.6
                                                                        1415-45
                                            17.4
                                                    408-04
                                                                -0.0I
                              1.43
                  291540.1
109.9
        1211.6
                                                                -0.01
                                                                        1414.73
                                            16.2
                                                    403.91
                              1.40
1.10.9
        1188.6
                  292424-4
                                                                        1414.01
                                                    399.91
                                                                -0.01
                                            15.1
        1165.9
                  293277.4
                              1.38
111.9
                                                                        1413.29
                                                     396.05
                                                                -0.01
                              1.35
                                            14.1
                  294099-1
        1143.6
112.9
                                                                -0.01
                                                                        1412.57
                                            13.2
                                                    392.36
                              1.32
        1121.8
                  294889.5
113.9
                                                                        1411.85
                                                                -0.01
                              1.30
                                            12.3
                                                    388.80
114.5
        1100.4
                  295648.6
                                                                        1411.13
                                                                -0.01
                                                     385.39
                              1.27
                                            11.6
                  296376.4
        1079.5
145.9
                                                                -0.01
                                                                        1410-42
                                                     382-14
                              1.25
                                            10.9
        1059.2
                  297073.0
116.5
                                                                        1409.71
                                             1C-2
                                                     379-02
                                                                -0.01
                              1.23
                  297738.3
117.79
        1039.3
                                                                -0.01
                                                                        1409.00
                                              9.7
                                                     376.06
                  298372.3
                               1.20
118 39
         1620.1
                                              9.2
                                                                -0.01
                                                                        1408-29
                                                     373.23
                               1.18
         100F-4
                  298975.0
119.9
                                                                        1407-58
                                                                -0.01
                                              8.7
                                                     370.62
                               1.16
                  299546.5
120.9
          983.4
                                                                -0.01
                                                                        1406.88
                                              8.2
                                                     369.24
                               1.14
                  360086.7
121.9
          966.1
                                                                -0.01
                                                                        1406-17
                                              7.8
                                                     367.93
                               1.12
                  300595.6
122 19
          949.5
                                                                -0.C1
                                                                        1405-47
                                              7.4
                                                     366.70
                  301073.3
                               1.10
123.9
          933.6
                                                                        1404-77
                                                                -0.01
                                              7.0
                                                     365.55
                  301519.7
                               1.08
          918.5
124.9
                                                     364-48
                                                                -0.01
                                                                        1404-07
                                              6.7
                               1.06
                  301934.8
125.9
          904.3
                                                                        1403.37
                                                     363.49
                                                                -0.01
                                              6.4
                               1.04
126 34
          890.9
                  302318.7
                                                                -0.01
                                                                        1402.67
                                                     362.60
                               1.03
                                              6.2
          678.5
                  302671.3
127.9
                                                                -0.01
                                                                        1401-98
                                                     361.77
                               1.01
                                              6.0
128.9
                  302992-7
          867.0
                                                                -0.01
                                                                        1401-29
                                              5.8
                                                     361.02
                  303282.7
                               1.00
129 39
          856.4
                                                     360.35
                                                                -0.01
                                                                        1400.59
                                              5.6
          846.9
                               0.99
                  303541.6
 140.9
                                                                -0.01
                                                                        1399.90
                                              5.5
                                                     359.77
                               0.98
131.9
          838.5
                  303769.2
                                                                        1399-21
                                                                -0.01
                                                     359.26
                                              5.3
                  303965.5
                               0.97
132.9
          831.1
                                                                -0.01
                                                                        1398.53
                                              5.2
                                                     358.84
                  304130.5
                               0.96
          824.9
 133.5
                                                                        1397.84
                                                                -0.01
                                              5.2
                                                     358.50
                               0.95
134.9
          819.8
                  304264.3
                                                                -0.01
                                                                        1397-16
                               0.95
                                              5:1
                                                     358-23
          815.9
                  304366.9
 135.9
                                                                -0.01
                                                                        1396-47
                                                     358.06
                                              5.1
                  304438.2
                               0.94
          813.2
 136.9
                                                                         1395.79
                                                                -0.01
                                                     357.95
                               0.94
                                              5.0
                  304478.2
137.9
          811.6
                                                                -0.01
                                                                         1395.11
                               0.94
                                              5.0
                                                     357.93
                  304487.0
 138.9
          811.3
                                                                         1394.43
                                                     357.99
                                                                -0.01
                                              5.0
                               0.94
 199.9
          812.2
                  304464.5
                                                                         1393.75
                                                     358.12
                                                                -0.01
                               0.95
                                              5. L
                  304410-8
          814.2
 140.9
                                                                         1393.07
                                                                -0.01
                                                     358.34
                                              521
          817.5
                  304325.8
                               0.95
 141 .4
```

X = 0.9518 FT

TIME	ÄEL	ALT	· M	RN	T(R)	Q (BTU/	T(W)
(SEC)	(FT/SEC)	(FT)			(DEG R)	FT2-SEC)	(DEG R)
0.	0.1	-0.	0.00	607.1	518.69	0.00	505.00
0:1	231.3	11.3	0.21	1403866.0	522.65	0.19	505.00
6.2	470.0	45.7	0.42	2850338.6	535.06	0.57	505.04
0.3	716.7	104.0	0.64	4340504.2	556.76	1.37	505.14
0.4	971.4	186.9	C.87	5871556.6	588.63	2.82	505.37
0.5	1234.4	295.3	1.11	744221C.4	631.66	5.15	505-80
0.6	1506.C	429.9	1.35	9050917.4	686.87	8.61	506.55
0.7	1786.3	591.6	1.60	10694594.7	755.35	13.50	507-77
3.0	2075.6	781.3	1.86	12371043.7	838.28	20.12	509-62
0.9	2374.0	999.9	2.13	14076547.9	936.86	28.77	512.31
1.0	2681.8	1248.2	2.41	15808292.0	1052-42	39.82	516-10
1.1	2999.2 3326.3	1527.3 1838.C	2.70 3.00	17562421.5 19334275.0	1186.35 1340.07	53.63 70.56	521.27 528.14
1.2	3663.4	2181.3	3.30	21119939.7	1515-16	91:02	537.08
1.4	4010.7	2558.2	3.62	22914577.2	1713.26	115.43	548.51
1.5	4368.3	2969.8	3.95	24712371.2	1936.00	144.17	562.90
1.6	4736.6	3417.G	4.29	26508588.2	2185.34	177.70	580.74
1.7	5115.7	3900.9	4.64	28297942.7	2463.10	216.42	602.59
1.8	5506.C	4422.6	5.01	30074076.5	2771.46	260.77	629.06
1.9	5744.8	4752-8	5.23	31127399.7	2971.33	288.59	659.84
1.9	5744.8	4752-8	5.23	31127399.7	2971.33	288.59	659.84
2.9	5427.1	10233.8	5.04	25659366.5	2686.20	182.51	917.41
3.9	5176.1	15436.1	4.90	21385736.7	2468.52	119.30	1082.71
4.9	4973.3	20415.6	4.80	17962645.7	2296-77	79.93	1191-81
5.9	4806.5	25213-4	4.73	15168380.7	2157.63	54.58	1265-42
6.9		25860.5	4.69	12853510.7	2042.42	37.70	1315.73
7.9		34380.6	4.66	10913128.7	1945.11	26.16	1350.33
8.9	4448.9	38792.7	4.59	8894333.5	1871.07	18.26	1374.16
9.9		43112.5	4.50	7093469.9	1814.63	13.00	1390-69
10.9		47352.9	4.43 4.36	5692194.2 459149C.9	1766.59 1724.92	9.37 6.81	1402.35 1410.57
11.9 12.9	4223.7	51523.9 55633.0	4.30	3720175.7	1688.20	4.98	1416.36
13.9		59686.2	4.25	3025807.8	1655.25	3.64	1420.39
14.5		63688.1	4.19	2469406.5	1625-28	2.67	1423-15
15.5	4017.4	67642.4	4.15	202147C.C	1597.70	1.94	1424.95
16.9		71552.2	4.10	1659337.6	1572.05	1.40	1426.06
17.9		75419.6	4.06	1365502.3	1547.90	1.00	1426.65
18.9		79246.8	4.C2	1126332.4	1525.06	0.69	1426-84
19.9		83035.1	3.98	92637C.6	1504.37	0.13	1426.60
20.9		86785.8	3.91	747918.6	1489.64	0.10	1425.91
21.9	3785.4	90500.0	3.84	607018.1	1475.56	0.07	1425-29
22.9		94178.6	3.78	495115.C	1461-99	0.05	1424.62
23.9		97822.3	3.72	405780.5	1448.99	0.03	1423.93
24.9		101431-4	3.66	334068.4	1436.32	0.01	1423-22
25.9		1C5CC6.7	3.60	276228.7	1424.04	0.00	1422.50
26 - 9		108548.3	3.55	229353.4	1412-02	-0.01 -0.02	1421.77 1421.03
27.9		112056.6	3.49	191195.7 159998.8	1400.28 1388.73	-0.02	1420-28
28.9		115531-8	3.44 3.39	134392.7	1377.45	-0.63	1419.53
29.9 30.9		118974.2 122383.6	3.33	113287.4	1366.32	-0.03	1418.77
31.9		125761.C	3.28	95827.8	1355.38	-C.04	1418.01
32.5		129105.7	3.24	8133C.C	1344.59	-0.04	1417.25
33.9		132418.C	3.19	69249.3	1333.95	-0.04	1416-49
34.9		135698.2	3.14	59145.5	1323.50	-0.C5	1415.72
35 .9		138946-2	3.C9	50675.3	1313.15	-0.65	1414.96
36.9		142162.1	3.C5	43543.7	1302.93	-0.05	1414.19
37.9	3270.2	145345.9	3.CG	37522.2	1292.81	-0.05	1413.43
38.9		148497.8	2.96	32424.7	1282.87	-0.C5	1412.66

39.9	3208.3	151617.7	2.92	28094.2	1272.98	-0.05	1411.90
40.9	3177.5	154705.7	2.88	24407.2	1263.27		1411-14
41.9		157761.9	2.84	21551.3	1249.73	-0.05	1410.38
42.9	3115.9	160786-2	2.82	19122.5	1235.30	-0-05	1409-62
43.9	3085.2	163778.7	2-79	16986-4	1221.05	-0.05	1408.86
44.9	3054.6	166739-4	2.76	15105.8	1206.99	-0.05	1408.10
45.9	3024.G	169668.3	2.73	13448-0	1193.08	-0.05	1407-34
46.9	2993.4	172565.4	2.71	11985.C	1179.30	-0.05	1406.58 1405.83
47.9	2962.9	17543C-9	2.68	10700-9	1165.50	-0.05 -0.06	1405.07
48.9	2932.4	178264.6	2.67	9791.4	1145.16 1125.05	-0.06	1404.32
49.9	2901.9	181066-7	2.66	8956.3 8190.3	1105-19	-0.06	1403.57
50.9	2871-5	183837.0	2.65	7487.7	1085.60	-0.06	1402-81
51.9	2841.2	186575-7	2.64 2.63	6843-4	1066-22	-0.06	1402-06
52.9	2810.9	185282.7 191958.1	2.62	6252-6	1047-05	-0.06	1401-31
53.9	2780.6 2750.4	194601.9	2.61	5711.4	1028.15	-0.06	1400-57
54.9	2720.2	197214-0	2.60.	5215.6	1009-45	-0.06	1399.82
55.9 56.9	2690.0	199794.6	2.59	4761.5	990.98	-0.05	1399.08
57.9	2659.9	202343.6	2.58	4346.0	972.75	-0.05	1398.34
58.9	2629.9	204860.9	2.56	3965.9	954.78	-0.05	1397.60
59.9	2599.9	207346-7	2.55	3618.1	937.02	-0.05	1396.86
60.9	2569.9	209801-0	2.54	3299.9	919.48	-0.05	1396.13
61.9	2540-C	212223.6	2.53	3009.2	902.18	-0.05	1395.40
62.9	2510.1	214614.8	2.52	2743.5	885-10	-0.05	1394-67
63.9	2480.3	216974-4	2.50	2500-8	868.27	-0.05	1393.95 1393.22
64.9	2450.5	219302-5	2.49	2279.2	851.64	-0.05 -0.04	1392.51
65.9	2420.8	221599-0	2.48	2076.8	835.26	-0.04	1391.79
66.9	2391-1	223864-1	2-46	1892.1	819-09 803-17	-0.04	1391.08
67.9	2361.5	226097.6	2.45	1723.6 1570.0	787.49	-0.04	1390.36
68 - 9	2332.C	228299-7	2.44	1429.8	772.02	-0.04	1389.66
69.9	2302.5	230470-2	2.42 2.41	1302-0	756.78	-0.04	1388.95
70.9	2273.1	232609.3	2.39	1185.6	741.76	-0.04	1388.25
71.9	2243.7	234716.9 236793.1	2.38	1079-5	726.97	-0.C3	1387.55
72.9	2214.4 2185.1	238837.7	2.36	982.8	712.39	-0.03	1386.86
73.9 74.9	2156.C	24C851-C	2.35	894.8	698.08	-0.03	1386.16
75.9	2126.9	242832.7	2.33	814.6	683.97	-0.03	1385.47
76.9	2097-8	244783.1	2.32	741.6	670.07	-0.03	1384-79
77.9	2068-9	246702.C	2.30	675.2	656.43	-0.03	1384-10
78.9	2040-0	248589.5	2.28	614.8	642.99	-0.03	1383.42
79.9	2011.2	250445.5	2.27	559.8	629.79	-0.03	1382.74
80.9	1982.5	25227C-2	2.25	509.8	616.81	-0.02	1382-06
81.9	1953.9	254063.4	2.23	464.3	604-07	-0.02	1381.39 1380.71
82 49	1925.4	255825-2	2.21	422.9	591.55	-0.02	1380.04
83.9	1897.0	257555-6	2.20	385.3	579.26	-0.02 -0.02	1379.38
84.9	1868.6	259254.6	2.18	351.1	567.16	-0.02	1378.71
85.9	1840.4	260922.3	2.16	320.0	555.32 543.96	-0.02	1378.05
86.9	1812.3	262558.5	2.14	291.3	536.43	-0.C2	1377.39
87.9	1784.3	264163.4	2.11	259.9 232.3	529.03	-0.02	1376.73
88.9	1756.4	265736.9	2.07	208.0	521.78	-0.C2	1376-07
89.9	1728.6	267279.0	2.04 2.01	186.6	514.70	-0.02	1375.42
90 - 9	1701.0	268789.8 270269.2	1.98	167.7	507.76	-0.61	1374.76
91.9	1673.5	271717.2	1.94	151.C	500-98	-0.01	1374.11
92.9	1646.2	273133.9	1.91	136.1	494.31	-0.G1	1373.47
93.9		274519-2	1.88	123.0	487.82	-0.01	1372.82
9 4. 9		275873-2	1.85	111.3	481.46	-0.01	1372.17
96.9		277195.9	1.82	10C.9	475.26	-0.01	1371.53
97.9		278487-2	1.79	91.6		-0.01	1370.89
98.9		279747.2	1.75	83.3	463.29	-0.01	1370.25
99.9		280975.8	1.72	75.9		-0.C1	1369.61
100.9		282173-2	1.69	69.3		-0.01	1368.98
101.9			1.66	63.4		-0.01	1368.34
102.9		284473.9	1.63	58.0		-0.01	1367.71
103.9			1.60	53.3		-0.01	1367.08
.104.9			1-57	49.0	430-95	-0.01	1366.45
				56			

		•					
105.5	1307.3	287690-1	.54	45.1	426.08	-0.01	1365.82
106.9	1282.9	248699.6	1-51	41.6	421.35	-0.01	1365.19
107.9	1258.8	285677.7	1.49	38.5	416.76	-0.01	1364.56
108.9	1235.0	290624.6	1.46	35.6	412.32	-0.01	1363.94
109.9	1211.6	291540-1	1.43	33.0	408-04	-0.01	1363-32
110.9	1188.6	292424.4	1.40	3C.7	403.91	-0.01	1362.70
111.9	1165.9	293277.4	1.38	28.6	399.91	-0.01	1362-07
112.9	1143.6	294099.1	1.35	26.7	396-05	-0.01	1361-46
113.9	1121.8	294889.5	1.32	24.9	392.36	-0.01	1360.84
314.9	1100.4	295648.6	1.30	23.3	388.80	-0.01	1360-22
115.9	1079.5	296376.4	1.27	21.9	385.39	-0.01	1359.61
116.9	1059.2	297073.C	1.25	2026	382-14	-0.01	1358.99
217.9	1639.3	297738.3	1.23	19.4	379.02	-0.01	1358.38
118.9	1020.1	298372.3	1.20	18.3	376.06	-0.01	1357-77
119.9	1001.4	298975.0	1.18	17.3	373.23	-0.01	1357-16
120.9	983.4	299546.5	1.16	16.4	370.62	-0.01	1356.55
121.9	966.1	300086.7	1-14	15.5	369.24	-0.01	1355.95
122.9	948.5	30C595.6	1-12	14.7	367.93	-0.01	1355.34
123.9	933.6	301C73.3	1-10	14.0	366.70	-0.00	1354-73
124.9	918.5	301519.7	1.08	13.3	365.55	-0.0C	1354-13
125.9	904.3	301934.8	1.06	12.7	364.48	-0.CO	1353.53
126.9	890.9	302318.7	1.04	12.2	363.49	-0.00	1352.93
127.9	878.5	302671.3	1.03	11.7	362.60	-0.00	1352.33
128.9	867.0	302992.7	1.01	11.3	361.77	-0.00	1351.73
129.9	856.4	303282.7	1.00	10.9	361-02	-0.00	1351.13
130.9	846.9	303541.6	0.99	10.6	360-35	-0.00	1350-53
131.9	838.5	303769.2	G.98	1C.4	359.77	-0.00	1349-94
132.9	831.1	303965.5	0.97	10.1	359.26	-0-00	1349-34
143.9	824.9	304130.5	0.96	9.9	358.84	-0.00	1348.75
134.9	£19.8	304264.3	0.95	9.8	358.50	-0.00	1348-16
135.39	815.9	304366.9	0.95	9.7	358-23	-0.00	1347.56
136.9	813.2	304438.2	0.94	9.6	358-06	-0.00	1346-97
137.49	811.6	304478.2	C.94	9.5	357.95	-0.00	1346.38
136.9	8113	304487.C	0.94	95	357.93	-0.00	1345-80
139.4	812.2	304464.5	C-94	9.6	357.99	-0.00	1345-21
140.9	814.2	304410.8	0.95	9.6	358.12	-0:00	1344-62
141.9	817.5	304325.8	0.95	9.7	358.34	-0.00	1344-04




FIG. I DART-BOOSTER ASSEMBLY DRAWING




FIG. 2 MAXIMUM ALTITUDES FOR THE 1.0-INCH DART




FIG. 3 TRAJECTORIES FOR THE 1.0-INCH, 50 LB DART FOR THE MK 32 MOD 0 MOTOR






FIG. 4 STATIC STABILITY MARGIN OF I.O-INCH DART-BOOSTER COMBINATION








FIG. 7 MOTOR WALL TEMPERATURE AND STRESS AS A FUNCTION OF TIME




FIG. 8 ALUMINUM 2024-T4 FIN TEMPERATURES AND STRENGTH AS A FUNCTION OF TIME




FIG. 9 STAINLESS STEEL FIN TEMPERATURES AND STRENGTH AS A FUNCTION OF TIME




FIG.10 NOSE CONE TEMPERATURE AS A FUNCTION OF TIME

No. of Copies

6

Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C. 20360

Attn: DLI-30 Attn: R-14 Attn: RRRE-4 Attn: RMGA-811 RMMO-42 FA

Office of Naval Research Room 2709, T-3

Washington 25, D. C. Attn: Head, Mechanics Branch

Attn: Head, Fluid Dynamics Branch

Director, David Taylor Model Basin Aerodynamics Laboratory Washington 7, D. C. Attn: Library

Commander, U. S. Naval Ordnance Test Station China Lake, California Attn: Technical Library

Attn: Code 406

Director, Naval Research Laboratory Washington 25, D. C. Attn: Code 2027

Commanding Officer Officer of Naval Research Branch Office Box 39, Navy 100 Fleet Post Office New York, New York

NASA High Speed Flight Station Box 273 Edwards Air Force Base, California Attn: W. C. Williams

Ames Research Center Moffett Field, California Attn: Librarian

	Copies
NASA	
Langley Research Center	
Langley Field, Virginia	
Attn: Librarian	3
Attn: C. H. McLellan Attn: Adolf Busemann	
Attn: Adolf Busemann	
Attn: Comp. Res. Div. Attn: Theoretical Aerodynamics Division	
Attn: Theoretical Aerodynamics Division	_
Attn: H. Morrow	3
NASA	
Lewis Research Center	
21000 Brookpark Road	
Cleveland 11, Ohio	
Attn: Librarian	
Attn: Chief, Propulsion Aerodynamics Div.	
NASA	
600 Independence Avenue, S. W.	
Washington 25, D. C.	
Attn: Chief, Division of Research Information	
Attn: Dr. H. H. Kurzweg, Asst. Director of Research Attn: W. Spreen	5
Office of the Assistant Secretary of Defense (R&D)	
Room 3E1065, The Pentagon	
Washington 25, D. C.	
Attn: Technical Library	
Research and Development Board	
Room 3D1041, The Pentagon	
Washington 25, D. C.	
Attn: Library	•
Defense Documentation Center	20
Cameron Station	20
Alexandria Va 22314	
Commander, Pacific Missile Range	
Point Mugu, California	
Attn: Technical Library	
Attn: Code 3250	5
Commanding General	
Aberdeen Proving Ground, Maryland	
Attn: Technical Information Branch	
Attn: Ballistic Research Laboratory	
Attn: J. Brown	2

No. of Copies

2

Commander, Naval Weapons Laboratory Dahlgren, Virginia Attn: Library

Director, Special Projects
Department of the Navy
Washington 25, D. C.
Attn: SP-2722

Director of Intelligence Headquarters, USAF Washington 25, D. C. Attn: AFOIN-3B

Headquarters - Aero. Systems Division Wright-Patterson Air Force Base Dayton, Ohio Attn: WWAD

Attn: RRLA-Library

Commander
Air Force Ballistic Systems Division
Norton Air Force Base

San Bernardino, California Attn: BSRVA

Chief, Defense Atomic Support Agency Washington 25, D. C.
Attn: Document Library

Headquarters, Arnold Engineering Development Center Air Research and Development Center Arnold Air Force Station, Tennessee

Attn: Technical Library

Attn: AEOR Attn: AEOIM

Commanding Officer, Harry Diamond Laboratories Washington 25, D. C.

Attn: Library, Room 211, Bldg. 92

Commanding General
U. S. Army Missile Command
Redstone Arsenal
Redstone Arsenal, Alabama

Attn: Mr. N. Shapiro (AMSMI-RR)

Attn: Redstone Scientific Information Center (AMSMI-RB)

No. of Copies

2

NASA

George C. Marshall Space Flight Center

Huntsville, Alabama

Attn: Dr. E. Geissler Attn: Mr. T. Reed Attn: Mr. H. Paul Attn: Mr. W. Dahm

Attn: Mr. H. A. Connell Attn: Mr. J. Kingsbury

Attn: ORDAB-DA

APL/JHU (C/NOw 7386) 8621 Georgia Avenue Silver Spring, Maryland

Attn: Technical Reports Group

Attn: Mr. D. Fox Attn: Dr. F. Hill

Air Force Systems Command Scientific & Technical Liaison Office Room 3710, Main Navy Department of the Navy Washington 25, D. C. Attn: Alonzo P. Mercier

CATALOGING INFORMATION FOR LIBRARY USE

			BIBLÌO	GRAPHIC I	BIBLIOGRAPHIC INFORMATION			
	DESCRIPTORS	PTORS	00	copes			DESCRIPTORS	CODES
SOURCE	NOL technical rep	report	NOLTR		SECURITY CLASSIFICATION AND CODE COUNT	CATION	Unclassified - 30	Ø8Øn .
REPORT NUMBER	63-210		630210		CIRCULATION LIMITATION	ATION		
REPORT DATE	30 April 1964		10	phot	CIRCULATION LIMITATION OR BIBLIOGRAPHIC	-ATION		
					BIBLIOGRAPHIC (SUPPL., VOL., ETC.)	r:		
			SUBJE	CT ANALY	SUBJECT ANALYSIS OF REPORT			
	DESCRIPTORS	CODES	DESCI	DESCRIPTORS		CODES	DESCRIPTORS	CODES
HASP		HASP	High altitude	apn		HIGA	Analysis	ANAL
Aerodynamic	amic	AERD	Sounding			SOUN	Trajectory	TRAJ
Aerothe	Aerothermodynamic	AERT	Pro jectil es	20		PROJ	Dynamic	DYNA
Studies		STUY	Altitude			ALTT	Static	STAC
1.0		1xøø	Aerodynamic heating	c heat	ing	AERY	Stability	STBI
Inch		INCH	Fin			FINS	Meteorology	METE
Diameter	¥	DIAM	Angle			ANGL		
Dart		DART	Material			MATE		
Design		DESI	Thermal			THER		
Rocket motor	notor	ROCK	Protection			PROT		
Mark		MARK	Casing			CASE		
32 mod 0	0	32MON	Performance	•		PERF		
PENC-NOL-2070/25 (5-68	39-S)							

1. Projectiles – 2. Projectiles – Aerodynamics 3. Projectiles, Meteoro- logical I. Title II. Gauzza, Harry J. III. Series IV. Project V. Project V. Project	1. Projectiles - HASP 2. Projectiles - Aerodynamics 3. Projectiles, Meteoro- logical I. Title II. Gauzza, III. Series IV. Project V. Project V. Project
Navel Ordnance Laboratory, White Oak, Md. (NOL technical report 63-210) AEROYYALIC AND AEROTHERMODYNAMIC STUDIES OF THE HASP 1.0-INCH DIAMETER DART (U), by H. J. Gauzze. 30 Apr. 1964. 20p. illus., tables. (Aerodynamics research report 208) Buweps tasks FANE 04001/212-4/F003-02-003 and FAME 04002/212-4/F003-02-003. The NOL high altitude sounding projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system.	Naval Ordnance Laboratory, White Cak, Md. (NOL technical report 63-210) AERODYNAMIC AND AEROTHERMOUTMANIC STUDIES OF THE HASP 1.0-INCH DIAMETER DART (U), by H. J. Gauzza. 30 Apr. 1964. 20p. illus., tables. (Aerodynamics research report 208) Buweps tasks FAME 04001/212-4/F003-02-003 and FAME 04002/212-4/F003-02-003. The NOL high altitude sounding projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system.
1. Projectiles HASP 2. Projectiles Aerodynamics 3. Projectiles, Meteoro- logical I. Title II. Gauzza, Harry J. III. Series IV. Project V. Project V. Project unclassified.	1. Projectiles Z. Projectiles Z. Projectiles, Aerodynamics 3. Projectiles, Neteore- 10gical II. Title III. Series IV. Project V. Project V. Project V. Project
Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-210) AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES OF THE HASP 1.0-INCH DIAMETER DART (U), by H. J. Gauzza. 30 Apr. 1964. 20p. illus., tables. (Aerodynamics research report 208) BuWeps tasks FAME 04001/212-4/F003-02-003 and FAME 04002/212-4/F003-02-003. The NOL bigh altitude sounding projectile (HASP) is the subject of a design study almed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modification to the system.	Navel Ordnance Laboratory, White Oak, Md. (NOL technical report 63-210) AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES OF THE HASP 1.0-INCH DIAMETER DART (U), by H. J. Gauzza. 30 Apr. 1964. 20p. illus., tables. (Aerodynamics research report 208) Buweps tasks FAME 04001/212-4/F003-02-003 and FAME 04002/212-4/F003-02-003. The NOL Migh altitude sounding projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are de- soribed. Improved performance is indicated by reduction in size of the dart, but modifi- oations are required to insure stability and structural integrity of the system.

The NOL Migh altitude sounding projectile (HASP) is the subject of a design study almed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system.

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 63-210)
AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES OF
THE HASP 1.0-INCH DIAMETER DART (U), by H. J.
Gauzza. 30 Apr. 1964. 20p. illus., tables.
(Aerodynamics research report 208) Buweps
tasks FAME 04001/212-4/F003-02-003 and FAME
04002/212-4/F003-02-003. UNCLASSIFIED

The NOL Migh altitude seunding Projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system.

Abstract card is

unclassified.

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 63-210)
AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES OF
THE HASP 1.0-INCH DIAMETER DART (U), by H. J.
Gauzza. 30 Apr. 1964. 20p. illus., tables.
(Aerodynamics research report 208) Buweps
tasks FAME 04001/212-4/F003-02-003 and FAME
04002/212-4/F003-02-003. ł Projectiles -

Aerodynamios Projectiles, Projectiles

Meteoro-

logical

ritle

Gauzza, Harry J.

Project Project

id.

Series

Projectiles -

å ě

Projectiles HASP

Aerodynamios Projectiles,

Meteoro-

ogical

Title

Gauzza. Harry J.

UNCLASSIFIED

Project Project

Series

soribed. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system. The NOL high altitude sounding projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are de-

Abstract card is unclassified.

Abstract card is

unclassified.

Navel Ordnance Laboratory, White Cak, Md.
(NOL technical report 63-210)
AERODYNAMIC AND AEROTHERMODYNAMIC STUDIES OF
THE HASP 1.0-INCH DIAMETER DART (U), by H. J.
Gauzza. 30 Apr. 1964. 20p. illus., tables.
(Aerodynamics research report 208) Buweps
tasks FAME 04001/212-4/F003-02-003 and FAME
04002/212-4/F003-02-003. Projectiles -

Aerodynamics Projectiles,

Meteoro-

logical

ritie

ιť

Gauzza

Harry J

Series

Project Project

HA.

Projectiles

The NOL Migh altitude sounding projectile (HASP) is the subject of a design study aimed at enhancing the round's performance. Techniques and results of this study are described. Improved performance is indicated by reduction in size of the dart, but modifications are required to insure stability and structural integrity of the system.

Projectiles -Aerodynamics Projectiles, Projectiles HASP Meteoroogical Gauzza, Title 2 UNCLASSIFIED

Abstract card is

Project

Project

, ...

Series

Harry

unclassified.